



SECTION A-A

*** NOTE ***

1. APPLICABLE CONTACT P/N : 175087 , 175090.
2. APPLICABLE HSG P/N : 176143 , 176146.

GREY	85024-1
COLOR	PART NO.

GENERAL TOLERANCES	
10 MAX	±0.2
10 OVER 30 MAX	±0.25
30 OVER 100 MAX	±0.3
ANGLES	±5'

DATE	CHK	DR	REVISION RECORD
4/19/83	CS	JK	RELEASED(P93-042)

© 19 AMP MFG KOREA ALL RIGHT RESERVED AMP PRODUCTS COVERED BY PATENTS AND OR PATENTS PENDING		AMP * AMP MFG KOREA	
WIRE RANGE 0.3-1.25 mm²	INSULATION DIA φ1.6 - φ2.9mm	NAME RUBBER PLUG FOR 187 SEALED CONNECTOR	
MATERIAL NBR	FINISH/COLOR SEE TABLE	TOLERANCES 0 < X < 10 ±0.2 10 ≤ X < 30 ±0.25 30 ≤ X < 100 ±0.3 ANGLES 3	NO 85024
DR EH HONG	APP CS LEE	SIZE A3	LOC DS
CHK JK SONG	REL JK SONG	SCALE 10/1	REV 0
		SHEET 1/1	

PRINT DIST. DO NOT SCALE PRINT

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)