

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	26DEC2018	AL	CW
	AI	ECR-19-002478	16FEB2019	AL	CW
	B	ECR-21-111798	18SEP2021	WQR	CW

2 X AXIAL SCREW TERMINATION
(HEXAGONAL DRIVER SW2)
RECOMMENDED TIGHTENING TORQUE 2Nm
2X轴向螺纹端子(六角驱动SW2), 推荐锁紧力矩 2Nm

NOTES:

1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 1000V
RATED CURRENT: 40A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 8KV
POLLUTION DEGREE: 3
CONTACT RESISTANCE: $\leq 3m\Omega$
FLAMMABILITY: UL94V-0
MATING CYCLES: 500
WIRE RANGE: 6~10mm²
CONTACT TYPE: AXIAL SCREW TYPE.

注释:

1. 技术参数:
绝缘材料: PC
额定电压: 1000V
额定电流: 40A
绝缘电阻: $\geq 400M\Omega$
脉冲电压: 8KV
污染等级: 3
接触电阻: $\leq 3m\Omega$
阻燃等级: UL94V-0
插拔次数: 500
接线范围: 6~10mm²
接线类型: 轴向连接

S2111025201-000	HMN-S2-FD, 6-10	HMN-S2 FEMALE MODULE INSERT, 6-10 HMN-S2模块母插, 6-10
-----------------	-----------------	---

PART NUMBER
零件料号

PART DESCRIPTION
零件描述

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 26DEC2018

CHK ANDY LIN 26DEC2018

GINO YAO 26DEC2018

APVD CHRIS WANG 26DEC2018

PRODUCT SPEC

108-137123

APPLICATION SPEC

114-137123

WEIGHT

-

CUSTOMER DRAWING

TE Connectivity

NAME
HMN-S2-FD, 6-10

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
------	-----------	------------	---------------

A3	00779	©-S2111025201000	-
----	-------	------------------	---

SCALE	SHEET	OF	REV
3:2	1	1	B

DIMENSIONS:
mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±-
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±-

FINISH

-

MATERIAL

-

-

1470-19 (3/13)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)