



| REVISIONS | | | |
|-----------|--------------------------------|----------------|----------|
| REV | DESCRIPTION | DATE | APPROVED |
| 010 | RELEASED | | |
| 011 | REDRAWN IN CAD PER ECN 88-0678 | EFH 6/28/90 | KCM |

| ELECTRICAL | MECHANICAL | ENVIRONMENTAL |
|---|---|---|
| Nominal Impedance (Ohms) <u>50</u> | Interface Dimensions <u>MIL-STD-348, FIG. 310.2</u> | Temperature Rating <u>-65°C TO 125°C</u> |
| Frequency Range (GHz) <u>0-12.4</u> | Recommended Mating <u>Torque N/A</u> | Vibration - MIL-STD-202, Method <u>204, Condition B</u> |
| Volt Rating (VRMS MAX) <u>335</u> | Mating Characteristics: | Shock - MIL-STD-202, Method 213, <u>Condition I</u> |
| VSWR <u>N/A</u> | Insertion (MAX Lbs) <u>3</u> | Thermal shock - MIL-STD-202, <u>Method 102, Condition B</u> |
| Insertion Loss (dB MAX) <u>.03 x √f(GHz)</u> | Withdrawal (MIN Oz) <u>1</u> | Moisture Resistance - MIL-STD-202, <u>Method 106, Except Step 7b</u> |
| RF Leakage <u>N/A</u> | Connector Engagement and Disengagement (In/Lbs MAX) <u>2</u> | (Vibration) Shall Be Omitted |
| Corona, 70,000 Ft (VRMS MIN) <u>250</u> | Center Contact Captivation: | Corrosion - MIL-STD-202, Method <u>101, Condition B</u> |
| Dielectric Withstanding Voltage (VRMS MIN) <u>1000</u> | Axial <u>N/A</u> | |
| Contact Resistance (Milliohms MAX) | Radial <u>N/A</u> | |
| Center Contact <u>3</u> | Cable Retention <u>N/A</u> | |
| Outer Contact <u>2</u> | Weight (Grams) <u>1.9</u> | |
| RF High Potential (VRMS MIN @ 5 MHz) <u>670</u> | | |
| I.R. (Megohms) <u>10,000</u> | | |

| COMPONENT | MATERIAL | FINISH | | | | | | | |
|---|---|---|--|-----------------------|---|-------------------|-----------------------------|--------------------------|------------------------------|
| HOUSING | STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303 QQ-N-290 | PASSIVATE PER ASTM-A-380 | | | | | | | |
| DIELECTRIC | TFE FLUOROCARBON PER ASTM-D-1457, MIL-P-19468, AND FED. SPEC L-P-403 | N/A | | | | | | | |
| CENTER CONTACT | BERYLLIUM COPPER PER ASTM-196, ALLOY 173 | GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550 | | | | | | | |
| <table border="1"> <tr> <td>UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON</td> <td>DATE <u>5/1/68</u></td> <td rowspan="3"> AMP AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599 </td> </tr> <tr> <td>FRAC. DEC. ANGLES</td> <td>CHECKED BY <u>R.M.F.</u></td> </tr> <tr> <td><u>± 1/64 ± .005 ± °</u></td> <td>APPROVED BY <u>R.B.D.</u></td> </tr> </table> | | | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON | DATE <u>5/1/68</u> | AMP AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599 | FRAC. DEC. ANGLES | CHECKED BY <u>R.M.F.</u> | <u>± 1/64 ± .005 ± °</u> | APPROVED BY <u>R.B.D.</u> |
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON | DATE <u>5/1/68</u> | AMP AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599 | | | | | | | |
| FRAC. DEC. ANGLES | CHECKED BY <u>R.M.F.</u> | | | | | | | | |
| <u>± 1/64 ± .005 ± °</u> | APPROVED BY <u>R.B.D.</u> | | | | | | | | |
| USE ASSY PROCEDURE | TITLE OSM SURFACE LAUNCH JACK STRIPLINE TURRET TERMINAL | | | | | | | | |
| NO. AP. <u>N/A</u> | SIZE <u>B</u> | CODE IDENT NO. <u>26805</u> | | | | | | | |
| | SCALE <u>5:1</u> | <u>2066-1321-02</u> | | | | | | | |
| | | REV <u>01</u> | | | | | | | |
| | | SHEET 1 OF 1 | | | | | | | |

CUSTOMER DRAWING AMP PART # 1053403-1 SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)