

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

SUGGESTED MATING TAB

Technical drawing of a suggested mating tab. Dimensions include: 1.02 [.040] / 0.76 [.030] (width), 3.38 [.133] / 2.97 [.117] (length), 1.52 [.060] / 1.27 [.050] (DIA HOLE), 5.40 [.213] MIN (height), 4.83 [.190] / 4.67 [.184] (height), 3.30 [.130] / 3.10 [.122] (width), 1.14 [.045] / 0.89 [.035] X 45° (2 PLC), 6.35 [.250] (width), 8.26 [.325] MIN CLEARANCE, 0.25 [.010] MAX CUT-OFF, 0.84 [.033] / 0.79 [.031] (width), 0.13 [.005] R MAX BOTH SIDES, and a 10° ±2° angle.

- MATL: #2 HARD BRASS OR NICKEL PLATE STEEL.
- NO BURRS PERMISSIBLE AT HOLE.
- TIN PLATING IS REQUIRED ON BRASS WHEN TERMINAL TEMPERATURE IS OVER 225°F
- MUST BE FLAT WITHIN 0.076 [.003] OVER THIS LENGTH.
- HOLE MUST BE SYMMETRICAL ABOUT TAB C_t WITHIN 0.076 [.003].

* TO BE USED ONLY WHEN SHOULDER IS ELIMINATED.

SECTION A-A technical drawing showing dimensions: 17.02 [.670] (total length), 3.43 [.135] (width), and 6.30 [.248] (width).

SECTION A-A technical drawing showing dimensions: 6.48 [.255] (width), 3.56 [.140] (width), 2.03 [.080] (height), and 0.356 ± 0.025 [.014 ± .001] (height).

SECTION B-B technical drawing showing dimensions: 5.94 [.234] (width), 1.32 [.052] (width), and 2.59 [.102] (height). SECTION B-B ROTATED 90° CW.

SECTION C-C technical drawing showing dimensions: 3.30 [.130] / 2.67 [.105] (width), and 2.60 [.102] REF (height).

SECTION D-D technical drawing showing dimensions: 5.59 [.220] / 4.95 [.195] (width), and 4.03 [.158] REF (height).

This specification lists various figures which indicate the direction a product comes off the top of the reel.

Diagram showing wire barrel and contact portion with END FEED arrow. Figure 6.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
F1		REVISED PER ECR-15-016360	10MAR2016	NK	LP

- CONTINUOUS STRIP ON REELS.
- ACCEPTS #22-#18 SINGLE WIRE SIZES, WIRE CRIMP IS 2.03 [.080], F TYPE.
- FITS INSULATION RANGE 2.29-3.30 [.090-.130] DIA, INSULATION CRIMP IS 3.94 [.155] F TYPE.

REELING
107-3 FIG.6

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm [INCHES]	
0 PLC	± -
1 PLC	± -
2 PLC	± 0.25 [.010]
3 PLC	± -
4 PLC	± -
ANGLES	± -

MATERIAL: BRASS
FINISH: SEE TABLE

DWN	JR RUTH	6/26/98
CHK	MS FEHER	6/26/98
APVD	E HOWARD	6/26/98
PRODUCT SPEC		
APPLICATION SPEC		
WEIGHT	0	
CUSTOMER DRAWING		

TIN	1217097-2
OBSOLETE	-1217097-1-
FINISH	PART NO.
TE TE Connectivity	
RECEPTACLE, POSITIVE-LOCK, MARK III, 4.75 [.187] SERIES	
SIZE	A2
CAGE CODE	00779
DRAWING NO	C=1217097
RESTRICTED TO	-
SCALE	6:1
SHEET	1 of 1
REV	F1

1471-9 (1/15)

Downloaded From Onevac.com

1217097

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)