

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By -

ALL RIGHTS RESERVED.

LOC
HBDIST
-

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
G		ADD "VDE" RATING	ECO-09-014074	23-JUL-09	HYS YBH
H		UPDATE DRAWING	ECO-09-021062	22-DEC-09	HYS YBH
H1		CORRECT MISTAKE	ECO-10-011629	10-JUN-10	HYS YBH

D

D

PART A

PART B

PCH-112L2MH

10A 125V~ Res.
5A 277V~ Res.
5A 277V~ Res.

VDE

OEG

C

MADE IN CHINA:C

3.8±0.2

0.45

0.8

0.8

15.2

⊙ G

⊙ F LOT NO

CONNECTION DIAGRAM (BOTTOM VIEW)

DRILLING DIAGRAM (BOTTOM VIEW)

C

C

B

B

20

1.1

10.16±0.2

7.62±0.2

0.24

0.2

10

7.6±0.2

1

2

3

4

5

Diagram dimension	Tolerance
0.99mm max.	±0.1mm
1 - 2.99mm	±0.2mm
3mm min.	±0.3mm

NOTES:

1. TERMINAL DIMENSIONS BEFORE SOLDER DIP

2. LAST SUFFIX
NON : WASHABLE TYPE

⊙ 3. LOT NO SYSTEM AS FOLLOWING

WEEK

YEAR

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN H.SASAKI		TE Connectivity	
DIMENSIONS: mm		CHK N.FUNAYAMA		NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD A.NAGAI		PCH-L2M CUSTOMER DRAWING	
0 PLC ± -		PRODUCT SPEC		SIZE CAGE CODE DRAWING NO RESTRICTED TO	
1 PLC ± -		APPLICATION SPEC		A3 00779 C=1461352	
2 PLC ± -		WEIGHT -		SCALE 5:1 SHEET 1 OF 2 REV H1	
3 PLC ± -		CUSTOMER DRAWING			
4 PLC ± -					
ANGLES ± -					
FINISH -					
MATERIAL -					

1470-19 (3/11)

Downloaded From Onevac.com

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

-. - .

© COPYRIGHT - By -


ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
HB	-	P	LTR	DESCRIPTION	DATE	DWN	APVD
		-	-	SEE SHEET 1	-	-	-

1461352-6	PCH-124L2M,000	107-79019	24V	PCH-124L2M	f
1461352-5	PCH-112L2M,000	107-79019	12V	PCH-112L2M	e
1461352-4	PCH-109L2M,000	107-79019	9V	PCH-109L2M	d
1461352-3	PCH-106L2M,000	107-79019	6V	PCH-106L2M	c
1461352-2	PCH-105L2M,000	107-79019	5V	PCH-105L2M	b
1461352-1	PCH-103L2M,000	107-79019	3V	PCH-103L2M	a
TE PART NO	DESCRIPTION	PACKAGE SPEC	PART B	PART A	TYPE

RELAY TYPE

		EPOXY RESIN	SEAL	15
CLASS E		UEW	MAGNETIC WIRE	14
	SOLDER DIP	CP WIRE	COIL TERMINAL	13
		Ag ALLOY	STATONARY CONTACT	12
		Ag ALLOY	MOVABLE CONTACT	11
		Cu ALLOY	HINGE SPRING	10
	SOLDER DIP	Cu ALLOY	NO TERMINAL	9
	SOLDER DIP	Cu ALLOY	MOVABLE SPRING	8
UL 94V-0		PA NYLON	CARD	7
UL 94V-0		PBT	CASE	6
UL 94HB		PBT	BOBBIN	5
UL 94V-0		PBT	BASE	4
	Ni PLATED	STEEL	CORE	3
	CuNi PLATED	STEEL	ARMATURE	2
	CuNi PLATED	STEEL	YOKE	1
INCOMBUSTIBILITY	TREATMENT	MATERIAL	DESCRIPTION	ITEM

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	H.SASAKI	
		CHK	N.FUNAYAMA	
		APVD	A.NAGAI	
		PRODUCT SPEC		
		APPLICATION SPEC		
		WEIGHT	-	
		CUSTOMER DRAWING		
DIMENSIONS: mm 		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		NAME PCH-L2M CUSTOMER DRAWING
MATERIAL		FINISH	SIZE	RESTRICTED TO
-		-	A3	-
			CAGE CODE	DRAWING NO
			00779	C=1461352
			SCALE	SHEET
			5:1	2 of 2
			REV	H1

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)