

4 3 2 1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
AF	50	AD1	REVISED PER ECR-20-009164	12AUG2020	MK DH

- 1 CONTINUOUS STRIP ON REELS
- △ 2 MAX FIRST INSERTION FORCE, 88.96 NEWTON [20 LBS] USING GAGE 100505.
- 3 WIRE SIZE IS #14-10 AWG
- 4 INSULATION RANGE IS 3.81-5.08 [.150-.200] DIA
- 5 MATING TAB THK IS 0.84-0.76 [.033-.030]
- △ 6 FOREIGN PRODUCTION ONLY
- △ 7 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

3.81
[.150]

SIMA

8.08
[.318]

3.15
[.124]

GAP AS REQUIRED TO MEET FORCE SPECIFICATION AND 0.71 [.028] MAX

VIEW A-A
SCALE 10:1

19.56
[.770]

2.79
[.110]

4.44
[.175]

7.75
[.305]

±0.025
0.457
±.001
[.018]

4.45
3.81
[.175]
[.150]

5.46
4.83
[.215]
[.190]

SECTION B-B
SCALE 8:1

6.35
5.72
[.250]
[.225]

6.73
6.10
[.265]
[.240]

SECTION C-C
SCALE 8:1

TYPE	WIDTH	STRIP LENGTH ±0.38 ±[.015]	TYPE	WIDTH	±.051 [±.002] HEIGHT	WIRE
F	5.33 [.210]	6.4 [.252]	F	3.30 [.130]	2.108 [083] 2.413 [095] 2.921 [115]	2.0mm [14] 3.0mm [12] 5.0mm [10]
INSUL BARREL CRIMP		WIRE BARREL CRIMP				

FINISH	MATERIAL	PART NO.
△/△ OBSOLETE	SILVER	TEMP3 PHOS BRZ
	TIN	TEMP3 PHOS BRZ
OBSOLETE	-	TEMP3 PHOS BRZ
OBSOLETE	SILVER	TEMP4 BRASS
	TIN	BRASS
OBSOLETE	-	TEMP4 BRASS
	FINISH	MATERIAL
		PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	JR RUTH	7/10/89		TE Connectivity		
DIMENSIONS: mm [INCHES]		CHK	MS FEHER	7/10/89		RECEPTACLE, FASTON, .250 SERIES		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	C MEYERS	7/10/89		SIZE	CAGE CODE	DRAWING NO
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± 0.38 [.015] 4 PLC ± - ANGLES ± -		PRODUCT SPEC	-			A2	00779	C=42437
MATERIAL	SEE TABLE	FINISH	SEE TABLE	WEIGHT	-	SCALE	5:1	
CUSTOMER DRAWING		SHEET		1 OF 1	REV	AD1		

1471-9 (3/11) Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)