



- 1 HOUSING MATERIAL: GLASS-FILLED POLYESTER. COLOR: GRAY.
- 2 CONTACT MATERIAL: PHOSPHOR BRONZE.
- 3 CONTACT FINISH: DIN 41612 CLASS 2 IN CONTACT AREA. TIN ON POSTS.
- 4 PART NUMBER, DATE CODE IDENTIFICATION, CSA LOGO IN THIS APPROXIMATE AREA.
- 5 POINT OF MEASUREMENT FOR GOLD.
- 6 ACTION PIN POSTS REQUIRE 1.57 [.062] MINIMUM THICK PC BOARD. RECOMMENDED PC BOARD HOLES ARE Ø1.151±0.02 [.0453±.001] DRILLED HOLE WITH 0.02-0.07 [.001-.003] COPPER AND 0.008 [.0003] MINIMUM TIN-LEAD PLATING. FINISHED HOLE AFTER PLATING, Ø0.94-1.09 [.037-.043].
- 7 CONTACT FINISH: 0.00127 [.000050] GOLD IN CONTACT AREA. 0.00127 [.000050] NICKEL UNDERPLATE ALL OVER. TIN-LEAD ON POSTS.
- 8 CONTACT FINISH: DIN 41612 CLASS 3 IN CONTACT AREA. TIN-LEAD ON POSTS.
- 9 CONTACT FINISH: DIN 41612 CLASS 2 IN CONTACT AREA. TIN-LEAD ON POSTS.

| | | | | | | | |
|--------------------------|------------------|-----------|---|---|------------------------|------------------|------------|
| SUPERSEDED BY: 5535032-4 | 3 | 1 THRU 32 | X | X | X | 96 | 7-535032-4 |
| | 8 | 1 THRU 32 | X | X | X | 96 | 535032-9 |
| | 9 | 1 THRU 32 | X | X | X | 96 | 535032-5 |
| | 9 | 1 THRU 32 | X | X | X | 96 | 535032-4 |
| | 7 | 1 THRU 32 | X | X | X | 96 | 535032-1 |
| NOTES | POSITIONS LOADED | C | B | A | NO. OF LOADED POSITION | ASSY PART NUMBER | |

| | | | | | |
|--|---------------|------------------|---------|-------------------|--|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DIN | 12/6/88 | L. BRINER | |
| DIMENSIONS: mm [INCHES] | | CHK | 2/27/89 | J. BROWN | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | APVD | | NAME | |
| 0 PLC | ± - | PRODUCT SPEC | | | |
| 1 PLC | ± - | APPLICATION SPEC | | | |
| 2 PLC | ± 0.13 [.005] | SIZE | | | |
| 3 PLC | ± - | CAGE CODE | | | |
| 4 PLC | ± - | DRAWING NO | | | |
| ANGLES | ± - | WEIGHT | | | |
| MATERIAL | | FINISH | | A1 00779 C=535032 | |
| 1/2 | | 3/8/9 | | CUSTOMER DRAWING | |
| SCALE | | SHEET | | REV | |
| 4:1 | | 1 of 1 | | R1 | |

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)