

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 20
 © COPYRIGHT 20 BY - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
CM	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
		D		REVISED PER ECO-11-017731	31AUG11	JR	TM

- FLASH ALLOWANCE TO BE 0.05 MAX HIGH x 0.03 MAX THICK.
- FLASH NOT PERMITTED IN THIS AREA.
- FLASH MAY BE PRESENT ON THIS EDGE. NO FORM, FIT OR FUNCTION ISSUES IF LESS THAN 0.21 LONG.
- INSULATION DIAMETER MUST BE MET REGARDLESS OF WHICH WIRE SIZE IS USED.
- THIS SEAL IS NOT COMPATIBLE WITH 26-30 AWG CONTACTS. 26 AWG WIRE MUST BE USED WITH 22-26 AWG CONTACTS.
- OPTIONAL CONSTRUCTION.

SECTION A-A

3 DIMENSIONAL VIEW
SCALE 10:1

35.45 mm ³	BLUE	1.02-2.11	18-26 AWG	1.0	794758-1
VOLUME	COLOR	INSULATION DIAMETER Δ 4	WIRE RANGE Δ 4	DIM A	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN K. WHITAKER 15FEB2001	STE TE Connectivity	
DIMENSIONS: mm		CHK C. JONES 15FEB2001		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD C. JONES 15FEB2001	NAME SINGLE WIRE SEAL, MINI UNIVERSAL MATE-N-LOK(TM)	
0 PLC ±.2		PRODUCT SPEC	SIZE	
1 PLC ±.2		APPLICATION SPEC	CAGE CODE	
2 PLC ±.		WEIGHT	DRAWING NO	
3 PLC ±.		RESTRICTED TO	A200779C-794758	
4 PLC ±.			SCALE 20:1	
ANGLES ±2°			SHEET 1 OF 1	
FINISH			REV D	
MATERIAL SILICON RUBBER		CUSTOMER DRAWING		

1471-9 (3/11) Downloaded From Onevac.com Pro/ENGINEER DRAWING

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)