



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
010	RELEASED	6/25/98	<i>J. Cornelli</i>
B	REVISED PER 0U20-0262-01	GV 1/6/03	JGH

ELECTRICAL	MECHANICAL	ENVIRONMENTAL	HOUSING	MATERIAL	FINISH
Nominal Impedance (Ohms) 50	Interface Dimensions MIL-STD-348, Fig. 321.1	TEMPERATURE RATING -65°C TO 125°C	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35	
Frequency Range (GHz) DC to 2	Force to Engage (Lbs MAX) 3	Vibration MIL-STD-202, Method 204, Condition D	TFE FLUOROCARBON PER ASTM-D-1457	N/A	
Volt Rating (VRMS MAX) @ Sea Level 335	Force to Disengage (Lbs MAX) 1.5	Shock MIL-STD-202, Method 213, Condition I	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204	
VSWR 1.12 MAX	Center Contact Captivation	Thermal Shock MIL-STD-202, Method 107, Condition B,	FLUOROSILICONE PER MIL-R-25988, CLASS I, TYPE I.	N/A	
Insertion Loss (dB MAX) .08√F(GHz)	Axial (Lbs) 6.0	Moisture Resistance MIL-STD-202, Method 106, Except Vibration			
RF Leakage (dB MIN) -[90-F(GHz)]	Radial (In/Øz) 4.0	Shall Be Omitted			
Corona, 70,000 Ft (VRMS MIN) 250	Weight (Grams) TBD	Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray			
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1,000					
Contact Resistance (Milliohms MAX)					
Center Contact 3.0					
Outer Contact 2.0					
Cable to Housing N/A					
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670					
I.R.(Megohms MIN) 10,000					

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DRAWN BY <i>J. Cornelli</i> DATE 5/7/98		M/A-COM a Division of AMP Incorporated 140 Fourth Avenue Waltham, MA 02154-7577
GEN. TOL. ±.010 ANGLES ± 1°	CHECKED BY		
	APP'D BY <i>J. Cornelli</i> 6/25/1998		

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	TITLE OSP RIGHT ANGLE 4 HOLE FLANGE MOUNT PLUG RECEPTACLE STRAIGHT TERMINAL		
	.XXX = in	SIZE B	CODE IDENT NO. 26805
	XX.X = mm (REF)	4553-5005-02	
	SCALE 4:1		REV 010 SHEET 1 OF 1

CUSTOMER DRAWING AMP PART # 1312302-1 SHEET 1 OF 1 REV B

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)