

SPECIFICATION CONTROL DRAWING

55PC0236

TITLE THREE CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, 600 VOLT

Date 12-6-96

Revision A

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.

COMPONENT WIRES - 55PC0216



CONSTRUCTION DETAILS

PART NUMBER	CONDUCTOR SIZE (AWG)	DIAMETER (in.)			WEIGHT (lb/1000 ft.)	
		LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC0236-24-*	24	.081	.085	.089	6.02	6.30
55PC0236-22-*	22	.094	.098	.102	8.82	9.13
55PC0236-20-*	20	.112	.116	.121	13.32	13.68
55PC0236-18-*	18	.132	.137	.142	20.04	20.66
55PC0236-16-*	16	.148	.153	.158	25.46	26.13

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C
 Maximum continuous conductor temperature
 VOLTAGE RATING: 600 volts (rms)
 INSULATION FLAWS:
 Impulse Dielectric Test, 8.0 kV (peak)

PART NUMBER:
 The "*" in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors.
 Example: AWG 22, white, black and red component wires; 55PC0236-22-9/0/2

COLOR AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681.

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)