

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	10MAR2015	DL	CW
	B	ECR-21-108559	06AUG2021	BS	CW

PANEL CUT OUT FOR INSERT FOR USING WITHOUT HOODS/HOUSINGS

NOTES:

1. TECHNICAL CHARACTERISTICS:

INSULATION MATERIAL: PA

RATED VOLTAGE: 200 V

RATED CURRENT: 16 A

INSULATION RESISTANCE:  $\geq 400M\Omega$ 

RATED IMPULSE VOLTAGE: 3 KV

FLAMMABILITY: UL94V-0

MATING CYCLES: 200 FOR SILVER PLATED

500 FOR GOLD PLATED

WIRE RANGE: 1.5 mm<sup>2</sup> (16 AWG)

CONTACT TYPE: SOLDERING

注释:

1. 技术参数:

绝缘材料: PA

额定电压: 200V

额定电流: 16A

绝缘电阻:  $\geq 400M\Omega$ 

额定脉冲电压: 3 KV

阻燃等级: UL94V-0

插拔次数: 镀银端子: 200次

镀金端子: 500次

接线范围: 1.5 mm<sup>2</sup> (16 AWG)

接线类型: 焊接 (电路焊接形式)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
mmTOLERANCES UNLESS  
OTHERWISE SPECIFIED:

0 PLC	±0
1 PLC	±0.1
2 PLC	±0.15
3 PLC	±0.2
4 PLC	±0.25
ANGLES	±0.5
FINISH	-

MATERIAL

-

DWN 10MAR2015

DAVID LI

CHK 10MAR2015

CHRIS WANG

APVD 10MAR2015

XU XIANG

PRODUCT SPEC

-

APPLICATION SPEC

-

WEIGHT

-

Customer Drawing

HEE-015-M

T2800152101-000

DESCRIPTION

PART NUMBER

TE Connectivity

NAME

HEE-015-M

SIZE

A3

CAGE CODE

-

DRAWING NO

-

RESTRICTED TO

-

SCALE

1:1

SHEET

1

OF

1

REV

B

1470-19 (3/13)

Downloaded From [Oneyac.com](http://Oneyac.com)

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)