



ELECTRICAL
Nominal Impedance (Ohms) <u>50</u>
Frequency Range (GHz) DC to <u>18</u>
Volt Rating (VRMS MAX) @ Sea Level <u>335</u>
VSWR <u>1.35±.01F(GHz)</u>
Insertion Loss (dB MAX) <u>.07 F(GHz)</u>
RF Leakage (dB MIN) <u>-60dB</u>
Corona, 70,000 Ft (VRMS MIN) <u>250</u>
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level <u>1000</u>
Contact Resistance (Milliohms MAX) Center Contact <u>3.0</u> Outer Contact <u>2.0</u> Cable to Housing <u>N/A</u>
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) <u>670</u>
LR.(Megohms MIN) <u>5000</u>

MECHANICAL
Interface Dimensions MIL-STD-348, Fig. <u>310-2</u>
Recommended Mating Torque <u>7-10 In-Lbs</u>
Mating Characteristics: Insertion (MAX Lbs) <u>2.0</u> Withdrawal (MIN Oz) <u>1.0</u>
Force to Engage and Disengage (In/Lbs MAX) <u>2</u>
Center Contact Captivation Axial (Lbs) <u>6.0</u> Radial (In/Oz) <u>4.0</u>
Weight (Grams) <u>2.2</u>

ENVIRONMENTAL
Temperature Rating <u>-65°C To 105°C</u>
Vibration MIL-STD-202, Method 204 204, Condition B
Shock MIL-STD-202, Method 213, Condition I
Thermal Shock MIL-STD-202, Method 107, Condition B,
Moisture Resistance MIL-STD-202, Method 106
Corrosion - MIL-STD-202, Method 101, Condition B, 5% salt spray
 .XXX=INCHES X.X=MILLIMETERS

COMPONENT	MATERIAL	FINISH
HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM- A582, TYPE 303	PASSIVATE PER ASTM-A380
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± °		
DRAWN BY <u>DWW</u> DATE <u>7/17/75</u> CHECKED BY <u>RMF</u> <u>7/18/75</u> APPD BY <u>BWC</u> <u>7/21/75</u>		
TITLE OSM FLANGE MOUNT JACK RECEPTACLE - SLOTTED TERMINAL		
AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599		
NO. AP. <u>N/A</u>	SIZE <u>B</u>	CODE IDENT NO. <u>26805</u>
	SCALE <u>5:1</u>	2052-1612-02
		REV <u>011</u>
		SHEET 1 OF 1

CUSTOMER DRAWING AMP PART # 1052563-1 SHEET 1 OF 1 REV A

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)