



P.C. BOARD MOUNTING DIMENSIONS $\Delta 3$

- $\Delta 1$ HOUSING: FLAME RETARDANT, 94V-0 RATED, GLASS FILLED, NYLON OR POLYESTER, COLOR: BLACK.
CONTACTS: BRASS.
INSERTS: ZINC.
- $\Delta 2$ CONTACTS: SEE TABLE.
INSERTS: CLEAR CHROMATE COATING.
- $\Delta 3$ REFER TO APPLICATION SPEC FOR RECOMMENDED P.C. BOARD MOUNTING DIMENSIONS FOR AUTOMATIC INSERTION.
- $\Delta 4$ GOLD FLASH ON THE MATING SURFACES, .000100 MIN TIN ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.
- $\Delta 5$.000030 MIN GOLD PLATE ON THE MATING SURFACES, .000100 MIN TIN PLATE ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT
-OR-
GOLD FLASH OVER PALLADIUM-NICKEL PLATE, .000030 MIN TOTAL ON THE MATING SURFACES, .000100 MIN TIN ON THE SOLDER END, .000050 MIN NICKEL UNDERPLATE ON THE ENTIRE CONTACT.

WITH INSERTS	$\Delta 5$	5747467-4
WITH .120 DIA HOLE	$\Delta 5$	5747467-2
WITH .120 DIA HOLE	$\Delta 4$	5747467-1
REMARKS	FINISH	PART NUMBER

**COPYRIGHT 2005
TYCO ELECTRONICS CORP
ALL RIGHTS RESERVED**

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN G. PETERS 19SEP05	19SEP05	NAME	PLUG ASSY, SIZE 1, 9 POSN, RIGHT ANGLE, .590 SERIES, .026 DIA POSTS, AMPLIMITE HD-20
ϕ	0. PLC \pm -	CHK S. BOLASH 19SEP05	19SEP05	APVD M. WALMSLEY 19SEP05	RESTRICTED TO
ϕ	1. PLC \pm -	PRODUCT SPEC		108-40025	SIZE
ϕ	2. PLC \pm -	APPLICATION SPEC		114-40015	SCALE
ϕ	3. PLC \pm .005	WEIGHT		—	SHEET
ϕ	4. PLC \pm -	CUSTOMER DRAWING		100779	1 OF 1
ϕ	ANGLES \pm -	FINISH		5747467	REV
ϕ		MATERIAL		—	B

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)