

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	G	SEE ECR 11-010607	17MAY2011	JS	LB
	G1	ECR-14-007191	25JUN2014	SK	JS

SECTION A-A

SECTION B-B

SECTION C-C

Kontakt geeignet für:
 Draht Groessenbereich 0.5 - 1.5 mm
 Isolationsbereich Ø2.0 - 3.0 mm

Notes

1 OBSOLETE

Leitungsquerschnitt in mm²

	Einzelanschlag	0.5	0.75	1.0	1.5
0.5	X	X			
0.75	X				
1.0	X				
1.5	X				

927936-4	1	STANDARD-TIMER Kontakt	vorverzinkt	CuNiSi	926965-4	1	F
927936-3	1	STANDARD-TIMER Kontakt	vorverzinkt	Kupfereisen	926965-3	1	F
927936-2	1	STANDARD-TIMER Kontakt	vorverzinkt	Bronze	926965-2		G
927936-1	1	STANDARD-TIMER Kontakt	vorverzinkt	Messing	926965-1		G
EINZELAUSFUEHRUNG	BENENNUNG EINZELTEIL	OBERFLÄCHE	WERKSTOFF	BANDWARE	REV.		

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	01FEB1988	TE Connectivity	
		GOERKE			
		CHK	27JUN2014		
		BITSCH			
		APVD	19JUN07		
		Bleicher, M.			
		PRODUCT SPEC			
		APPLICATION SPEC			
		WEIGHT	-		
MATERIAL		SEE TABLE			
FINISH		SEE TABLE			
Customer Drawing		SCALE	5:1		
		SHEET	1 OF 1		
		REV	G1		

1470-19 (3/13)

Downloaded From Onevac.com

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)