

LOC AI	DIST 00	REVISIONS				
P	LTR	DESCRIPTION	DATE	DWN	APVD	
	A1	ECR-15-002378	12FEB15	LS	GS	

HTV10 CRIMPING HEAD, MATE-N-LOK, 0.2-0.82 SQ.MM

FRONT VIEW



SIDE VIEW



Eigenschaften / Features

Der Crimpkopf verfügt über zwei Crimpnester in denen zwei Leitungsquerschnitte verarbeitet werden können. Die Kontakte werden mittels Klapppositionierer in die richtige Ausgangsposition gesetzt und gehalten.

Crimping head featured with two crimping nests to enable processing of two different wire sizes. Terminals will be correct inserted by means of a flap locator.

Einsatz in / Used for

HTV10 HAND TOOL MATE-N-LOK,
0.2-0.82 SQ.MM
- TE P/N 1579024-8

Abmessungen / Dimensions:

Länge / Length: 66 mm
Breite / Width: 37 mm
Tiefe / Depth: 22 mm

CUSTOMER MANUAL:
411-18580 / 744017-9

Anwendungsbereich / Application range

Leiterquerschnitt Cross section range (in sq.mm)	Leitercrimphöhe Conductor Crimp Height ±0,05 (in mm)	Leitercrimpbreite Conductor Crimp Width gemessen an den Tangenten der Radien in (mm)	Isolationscrimphöhe Insulation Crimp Height ±0,05 (in mm)	Isolationscrimpbreite Insulation Crimp Width gemessen an den Tangenten der Radien in (mm)	TE P/N- Kontakt TE P/N- Contact UNIVERSAL MATE-N-LOK
0,2 - 0,37	0,98	1,76 F	2,03	2,47 F	350689-1 - Buchse / Socket
0,5 - 0,82	1,13		2,03		350690-1 - Stift / Pin

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL INTERNATIONAL RIGHTS RESERVED.

BY TYCO ELECTRONICS CORPORATION.

© COPYRIGHT

DIMENSIONS: mm	DWN L.Sandhu	27 JAN 2015	MATERIAL	FINISH
	CHK C. Witt	27 JAN 2015	TE Connectivity	
TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD C. Witt	27 JAN 2015		
	0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -	PRODUCT SPEC	APPLICATION SPEC	SIZE A4
	WEIGHT 0.1kg	DRAWING NO 8-1579016-1	RESTRICTED TO -	
	CUSTOMER DRAWING	SCALE	SHEET 1 OF 1	REV A1

单击下面可查看定价，库存，交付和生命周期等信息

[>>TE Connectivity\(泰科\)](#)