

## P-channel 4V (G-S) MOSFET

### FEATURES

- Low On Resistance
- Ultra High Speed Switching
- -4V Driving
- EU RoHS Compliant, Pb Free

### APPLICATIONS

- Switching

### PRODUCT NAME

PRODUCT NAME	PACKAGE	ORDER UNIT
XP202A0003MR-G	SOT-23	3,000/Reel

\* The "-G" suffix denotes Halogen and Antimony free as well as being fully EU RoHS compliant.


### ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNITS
Drain-Source Voltage	$V_{DS}$	-30	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Drain Current (DC)	$I_D$	-3	A
Drain Current(Pulse) <sup>(*1)</sup>	$I_{DP}$	-12	A
Channel Power Dissipation <sup>(*2)</sup>	$P_d$	1	W
Channel Temperature	$T_{ch}$	+150	°C
Storage Temperature	$T_{stg}$	- 55 ~ +150	°C

(\*1)  $PW \leq 10 \mu s$ , duty cycle  $\leq 1\%$

(\*2) Ceramic Board (900mm<sup>2</sup> × 0.8mm) Mounting

### PIN CONFIGURATION





SOT-23(TOP VIEW)


### ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNITS
			MIN.	TYP.	MAX.	
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D = -1mA, V_{GS} = 0V$	-30	-	-	V
Drain-Source Cut-Off Current	$I_{DSS}$	$V_{DS} = -30V, V_{GS} = 0V$	-	-	-1	$\mu A$
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS} = \pm 16V, V_{DS} = 0V$	-	-	$\pm 10$	$\mu A$
Gate-Source Cut-Off Voltage	$V_{GS(off)}$	$V_{DS} = -10V, I_D = -1mA$	-1.2	-	-2.6	V
Forward Transfer Admittance	$ y_{fs} $	$V_{DS} = -10V, I_D = -3A$	-	8.0	-	S
Drain-Source ON Resistance	$R_{DS(ON)1}$	$I_D = -1.5A, V_{GS} = -10V$	-	45	-	m $\Omega$
	$R_{DS(ON)2}$	$I_D = -1.0A, V_{GS} = -4.5V$	-	67	-	m $\Omega$
	$R_{DS(ON)3}$	$I_D = -1.0A, V_{GS} = -4V$	-	76	-	m $\Omega$
Input Capacity	$C_{iss}$	$V_{DS} = -10V, f = 1MHz$	-	435	-	pF
Output Capacity	$C_{oss}$	$V_{DS} = -10V, f = 1MHz$	-	110	-	pF
Feedback capacity	$C_{rss}$	$V_{DS} = -10V, f = 1MHz$	-	85	-	pF
Turn on Delay time	$t_{d(on)}$	$I_D = -1A$	-	6	-	ns
Rise Time	$t_r$	$I_D = -1A$	-	12	-	ns
Turn off Delay Time	$t_{d(off)}$	$I_D = -1A$	-	28	-	ns
Fall Time	$t_f$	$I_D = -1A$	-	10	-	ns
All Gate Charge Amount	$Q_g$	$V_{DS} = -15V, V_{GS} = -10V, I_D = -3A$	-	10	-	nC
Gate Source Charge Amount	$Q_{gs}$	$V_{DS} = -15V, V_{GS} = -10V, I_D = -3A$	-	1.2	-	nC
Gate Drain Charge Amount	$Q_{gd}$	$V_{DS} = -15V, V_{GS} = -10V, I_D = -3A$	-	2.2	-	nC
Diode Forward Voltage	$V_{SD}$	$I_S = -3A, V_{GS} = 0V$	-	-0.8	-1.2	V

## SWITCHING-TIME TEST CIRCUIT




## EQUIVALENT CIRCUIT




## PACKAGING INFORMATION

### SOT-23



## MARKING RULE



① represents product series

MARK	PRODUCT SERIES
6	XP202*****-G

② ③ represents product group and number


MARK		PRODUCT GROUP	PRODUCT NUMBER	PRODUCT SERIES
②	③			
A	D	00	03	XP202A0003**-G

④, ⑤ represents production lot number


01 to 09, 0A to 0Z, 11 to 9Z, A1 to A9, AA to Z9, ZA to ZZ repeated (G, I, J, O, Q, W excluded)

# TYPICAL PERFORMANCE CHARACTERISTICS


(1) Drain Current vs. Drain-Source Voltage




(2) Drain Current vs. Drain-Source Voltage




(3) Drain-Source On-State Resistance vs. Gate-Source Voltage




(4) Drain-Source On-State Resistance vs. Ambient Temperature



(5) Forward Transfer Admittance vs. Drain Current




(6) Source Current vs. Diode Forward Voltage




## TYPICAL PERFORMANCE CHARACTERISTICS


(7) Switching Time vs. Drain Current




(8) Ciss, Coss, Crss vs. Drain-Source Voltage



(9) Gate-Source Voltage vs. Gate Charge



(10) Area of Safe Operation



1. The products and product specifications contained herein are subject to change without notice to improve performance characteristics. Consult us, or our representatives before use, to confirm that the information in this datasheet is up to date.
2. We assume no responsibility for any infringement of patents, patent rights, or other rights arising from the use of any information and circuitry in this datasheet.
3. Please ensure suitable shipping controls (including fail-safe designs and aging protection) are in force for equipment employing products listed in this datasheet.
4. The products in this datasheet are not developed, designed, or approved for use with such equipment whose failure or malfunction can be reasonably expected to directly endanger the life of, or cause significant injury to, the user.  
(e.g. Atomic energy; aerospace; transport; combustion and associated safety equipment thereof.)
5. Please use the products listed in this datasheet within the specified ranges.  
Should you wish to use the products under conditions exceeding the specifications, please consult us or our representatives.
6. We assume no responsibility for damage or loss due to abnormal use.
7. All rights reserved. No part of this datasheet may be copied or reproduced without the prior permission of TOREX SEMICONDUCTOR LTD.

**TOREX SEMICONDUCTOR LTD.**

单击下面可查看定价，库存，交付和生命周期等信息

[>>Torex Semiconductor\(特瑞仕\)](#)