


SMD kHz Crystals 3.2 x 1.5 x 0.75 mm 9H T10 Series

Quartz Crystals
Series

Features

- 2 pads surface mount package.
- Application for variety of automotive products reference clocks.
- High reliable environmental performance.
- RoHS compliant /Pb Free.




Electrical Specifications

Item / Type	9H T10
Norminal Frequency	32.768 kHz
Frequency Tolerance(at 25 °C)	± 20 ppm , or specify
Operation Temperature Range	- 40 ~ + 85 °C
Shunt Capacitance (C0)	1.0pF typical
Motional Capacitance (C1)	3.4fF typical
Insulation Resistance (IR)	500 MΩ Min.
Drive Level (DL)	1.0 μW Max.
Load Capacitance(CL)	12.5 pF , other spec.
Turnover Temperature (Ti)	25 °C ± 5 °C
Parabolic Coefficient (B)	(- 0.03 ± 0.01) * 10 ⁻⁶ / °C ²
Aging (at 25 °C)	± 3 ppm at first year
Storage Temperature Range	- 55 ~ +125 °C

Equivalent Series Resistance(ESR)

T10
70 KΩ Max

Dimensions



Units: mm

Remark : Specification subject to change without prior notice. Please confirm with our sales. <http://www.txccorp.com>

单击下面可查看定价，库存，交付和生命周期等信息

[>>TXC\(台湾晶技\)](#)