



Vincotech

30-FT12B2A200H705-PK49L06

datasheet

flowBOOST 2 dual

1200 V / 200 A

Topology features

- Auxiliary diodes for FC pre-charge (patent pending)
- Dual Flying Cap Booster
- Kelvin Emitter for improved switching performance
- Temperature sensor

Component features

- High speed switching
- Low collector emitter saturation voltage
- Low turn-off losses
- Optimized for hard switching topologies
- Positive temperature coefficient

Housing features

- Base isolation: Al_2O_3
- Convex shaped baseplate for superior thermal contact
- Cu baseplate
- Thermo-mechanical push-and-pull force relief
- Solder pin


Target applications

- Energy Storage Systems
- Solar Inverters


Types

- 30-FT12B2A200H705-PK49L06

flow 2 13 mm housing



Schematic





Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Inner Boost Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	156	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	600	A
Turn off safe operating area		$T_j = 150\text{ °C}$, $V_{CE} = 1200\text{ V}$	600	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	287	W
Gate-emitter voltage	V_{GES}		± 20	V
Maximum junction temperature	T_{jmax}		175	°C

Inner Boost Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	114	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	204	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 110\text{ °C}$	516	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	231	W
Maximum junction temperature	T_{jmax}		175	°C

Inner Boost Sw. Protection Diode

Peak repetitive reverse voltage	V_{RRM}		1600	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	78	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	480	A
Surge current capability	I^2t		1100	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	92	W
Maximum junction temperature	T_{jmax}		150	°C



Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
-----------	--------	------------	-------	------

Outer Boost Switch

Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	156	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	600	A
Turn off safe operating area		$T_j = 150\text{ °C}$, $V_{CE} = 1200\text{ V}$	600	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	287	W
Gate-emitter voltage	V_{GES}		± 20	V
Maximum junction temperature	T_{jmax}		175	°C

Outer Boost Diode

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	114	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	204	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 110\text{ °C}$	516	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	231	W
Maximum junction temperature	T_{jmax}		175	°C

Outer Boost Sw. Protection Diode

Peak repetitive reverse voltage	V_{RRM}		1600	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	78	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$	480	A
Surge current capability	I^2t		1100	A ² s
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_a = 80\text{ °C}$	92	W
Maximum junction temperature	T_{jmax}		150	°C



Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Aux Diode H				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	74	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	150	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 25\text{ °C}$	600	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	145	W
Maximum junction temperature	T_{jmax}		175	°C

Aux Diode L

Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	74	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	150	A
Surge (non-repetitive) forward current	I_{FSM}	Single Half Sine Wave, $t_p = 10\text{ ms}$ $T_j = 25\text{ °C}$	600	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	145	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Creepage distance			>12,7	mm
Clearance			>12,7	mm
Comparative Tracking Index	CTI		≥ 600	

*100 % tested in production



Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inner Boost Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0032	25	4,7	5,5	6,2	V
Collector-emitter saturation voltage	V_{CEsat}		15		200	25 125 150		1,78 1,94 1,98	2,15 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			8	µA
Gate-emitter leakage current	I_{GES}		20	0		25			200	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 100 \text{ kHz}$	0	25		25		26000		pF
Output capacitance	C_{oes}							480		pF
Reverse transfer capacitance	C_{res}							144		pF
Gate charge	Q_g	$V_{CC} = 960 \text{ V}$	0/15		200	25		1428		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,33		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 2 \text{ } \Omega$ $R_{goff} = 2 \text{ } \Omega$	± 15	700	200	25 125 150		157,6 160,68 162,12		ns
Rise time	t_r					25 125 150		12,43 13,97 14,06		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		172,21 205,54 214,87		ns
Fall time	t_f					25 125 150		44,81 65,58 72,71		ns
Turn-on energy (per pulse)	E_{on}					25 125 150		4,03 4,38 4,32		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		6,66 9,8 10,72		mWs



Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Inner Boost Diode

Static

Forward voltage	V_F				80	25 125 150		1,37 1,56 1,63	2 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1200$ V				25		20	2000	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,41		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RM}	$di/dt=11054$ A/µs $di/dt=10367$ A/µs $di/dt=10213$ A/µs	± 15	700	200	25 125 150		74,88 77,51 79,69		A
Reverse recovery time	t_{rr}					25 125 150		21,93 18,21 18,07		ns
Recovered charge	Q_r					25 125 150		0,777 0,74 0,745		µC
Reverse recovered energy	E_{rec}					25 125 150		0,183 0,162 0,163		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		8445,01 9338,74 10185,06		A/µs



Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Inner Boost Sw. Protection Diode

Static

Forward voltage	V_F				40	25 125 150		1,06 0,987 0,974	1,5 ⁽¹⁾	V
Reverse leakage current	I_R	$V_i = 1600$ V				25 150			100 2000	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,76		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----



Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Outer Boost Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0032	25	4,7	5,5	6,2	V
Collector-emitter saturation voltage	V_{CEsat}		15		200	25 125 150		1,78 1,94 1,98	2,15 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			8	μA
Gate-emitter leakage current	I_{GES}		20	0		25			200	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}	$f = 100 \text{ kHz}$	0	25		25		26000		pF
Output capacitance	C_{oes}							480		pF
Reverse transfer capacitance	C_{res}							144		pF
Gate charge	Q_g	$V_{CC} = 960 \text{ V}$	0/15		200	25		1428		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4 \text{ W/mK}$ (PSX)						0,33		K/W
--	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 2 \text{ } \Omega$ $R_{goff} = 2 \text{ } \Omega$	± 15	700	200	25 125 150		153,76 156,72 157,81		ns
Rise time	t_r					25 125 150		14,8 16,6 17,05		ns
Turn-off delay time	$t_{d(off)}$					25 125 150		168,41 202,16 211,65		ns
Fall time	t_f					25 125 150		34,56 59,01 68,41		ns
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD} = 0,725 \text{ } \mu\text{C}$ $Q_{tFWD} = 0,736 \text{ } \mu\text{C}$ $Q_{tFWD} = 0,747 \text{ } \mu\text{C}$				25 125 150		3,38 3,56 3,51		mWs
Turn-off energy (per pulse)	E_{off}					25 125 150		4,9 8,5 9,35		mWs



Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max	

Outer Boost Diode

Static

Forward voltage	V_F				80	25 125 150		1,37 1,56 1,63	2 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 1200$ V				25		20	2000	µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,41		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RM}	$di/dt=12410$ A/µs $di/dt=12064$ A/µs $di/dt=11035$ A/µs	± 15	700	200	25 125 150		83,94 84,02 84,41		A
Reverse recovery time	t_{rr}					25 125 150		14,59 14,99 15,17		ns
Recovered charge	Q_r					25 125 150		0,725 0,736 0,747		µC
Reverse recovered energy	E_{rec}					25 125 150		0,105 0,111 0,113		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		17742,76 17838,91 17343,81		A/µs



Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]		Min	Typ	Max	

Outer Boost Sw. Protection Diode

Static

Forward voltage	V_F				40	25 125 150		1,06 0,987 0,974	1,5 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 1600$ V				25 150			100 2000	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,76		K/W
--	---------------	------------------------------------	--	--	--	--	--	------	--	-----

Aux Diode H

Static

Forward voltage	V_F				75	25 125 150		2,59 2,16 2,07	3,3 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 1200$ V				25 150			250 2000	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,66		K/W
--	---------------	------------------------------------	--	--	--	--	--	------	--	-----



Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
			V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]		Min	Typ	Max	

Aux Diode L

Static

Forward voltage	V_F				75	25 125 150		2,59 2,16 2,07	3,3 ⁽¹⁾		V
Reverse leakage current	I_R	$V_i = 1200$ V				25 150			250 2000		µA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,66			K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	--	-----

Thermistor

Static

Rated resistance	R					25		22			kΩ
Deviation of R100	$\Delta_{R/R}$	$R_{100} = 1484$ Ω				100	-5		5		%
Power dissipation	P					25		130			mW
Power dissipation constant	d					25		1,5			mW/K
B-value	$B_{(25/50)}$	Tol. ± 1 %						3962			K
B-value	$B_{(25/100)}$	Tol. ± 1 %						4000			K
Vincotech Thermistor Reference									I		

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.



Vincotech

30-FT12B2A200H705-PK49L06


datasheet

Inner Boost Switch Characteristics

figure 1. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 2. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150 ^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 48 V$
 $T_j:$ 25 °C, 125 °C, 150 °C

figure 4. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0,331 K/W$
IGBT thermal model values

$R (K/W)$	$\tau (s)$
3,72E-02	4,28E+00
7,68E-02	6,09E-01
1,42E-01	7,68E-02
6,11E-02	1,66E-02
1,38E-02	8,44E-04



Vincotech

30-FT12B2A200H705-PK49L06


datasheet

Inner Boost Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$




$D = \text{single pulse}$
 $T_s = 80 \text{ } ^\circ\text{C}$
 $V_{GE} = 15 \text{ V}$
 $T_j = T_{jmax}$

figure 6. IGBT

Gate voltage vs gate charge

$$V_{GE} = f(Q_g)$$



$I_C = 100 \text{ A}$
 $T_j = 25 \text{ } ^\circ\text{C}$



Vincotech

30-FT12B2A200H705-PK49L06

datasheet

Inner Boost Diode Characteristics

figure 7. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 8. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T
$R_{th(j-s)} =$	0,411 K/W
FWD thermal model values	
R (K/W)	τ (s)
3,61E-02	4,15E+00
4,65E-02	7,98E-01
1,31E-01	1,00E-01
1,47E-01	1,86E-02
5,10E-02	1,58E-03



Vincotech

Inner Boost Sw. Protection Diode Characteristics

figure 9. Rectifier

Typical forward characteristics

$I_F = f(V_F)$





figure 10. Rectifier

Transient thermal impedance as a function of pulse width

$Z_{th(j-s)} = f(t_p)$



$D =$	t_p / T
$R_{th(j-s)} =$	0,765 K/W
Rectifier thermal model values	
R (K/W)	τ (s)
4,68E-02	5,24E+00
1,43E-01	5,88E-01
3,57E-01	7,04E-02
1,61E-01	1,86E-02
5,74E-02	1,54E-03



Vincotech

30-FT12B2A200H705-PK49L06

datasheet


Outer Boost Switch Characteristics

figure 11.

IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j: 25^\circ C, 125^\circ C, 150^\circ C$

figure 12.

IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$
 $T_j = 150^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 13.

IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$
 $V_{CE} = 48 V$
 $T_j: 25^\circ C, 125^\circ C, 150^\circ C$

figure 14.

IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 0.331 K/W$
IGBT thermal model values

$R (K/W)$	$\tau (s)$
3,72E-02	4,28E+00
7,68E-02	6,09E-01
1,42E-01	7,68E-02
6,11E-02	1,66E-02
1,38E-02	8,44E-04



Vincotech

30-FT12B2A200H705-PK49L06


datasheet

Outer Boost Switch Characteristics

figure 15. IGBT

Safe operating area

$$I_C = f(V_{CE})$$




$D =$ single pulse
 $T_s = 80$ °C
 $V_{GE} = 15$ V
 $T_j = T_{jmax}$

figure 16. IGBT

Gate voltage vs gate charge

$$V_{GE} = f(Q_g)$$



$I_C = 100$ A
 $T_j = 25$ °C



Vincotech

Outer Boost Diode Characteristics

figure 17. FWD

Typical forward characteristics

$I_F = f(V_F)$





figure 18. FWD

Transient thermal impedance as a function of pulse width

$Z_{th(j-s)} = f(t_p)$





Outer Boost Sw. Protection Diode Characteristics

figure 19. Rectifier

Typical forward characteristics
 $I_F = f(V_F)$





figure 20. Rectifier

Transient thermal impedance as a function of pulse width
 $Z_{th(j-s)} = f(t_p)$





Vincotech

Aux Diode H Characteristics

figure 21. FWD





figure 22. FWD





Aux Diode L Characteristics

figure 23.

FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 24.

FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D =$	t_p / T
$R_{th(j-s)} =$	0,657 K/W
FWD thermal model values	
R (K/W)	τ (s)
6,51E-02	2,52E+00
1,04E-01	3,73E-01
3,01E-01	7,08E-02
1,34E-01	1,87E-02
5,30E-02	2,00E-03



Vincotech

30-FT12B2A200H705-PK49L06
datasheet


Thermistor Characteristics

figure 25.

Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$





Vincotech

30-FT12B2A200H705-PK49L06

datasheet


Inner Boost Switching Characteristics

figure 26.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 2 \text{ } \Omega$
 $R_{goff} = 2 \text{ } \Omega$


T_j : — 25 °C
— 125 °C
— 150 °C

figure 27.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 200 \text{ A}$


T_j : — 25 °C
— 125 °C
— 150 °C

figure 28.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 2 \text{ } \Omega$


T_j : — 25 °C
— 125 °C
— 150 °C

figure 29.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 200 \text{ A}$

T_j : — 25 °C
— 125 °C
— 150 °C



Vincotech

30-FT12B2A200H705-PK49L06


datasheet

Inner Boost Switching Characteristics

figure 30.

IGBT

Typical switching times as a function of collector current
 $t = f(I_c)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 700$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 2$ Ω
 $R_{goff} = 2$ Ω

figure 31.

IGBT

Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 700$ V
 $V_{GE} = \pm 15$ V
 $I_c = 200$ A

figure 32.

FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$




With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 2$ Ω
 $T_j: 25$ °C (blue), 125 °C (black), 150 °C (red)

figure 33.

FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = \pm 15$ V
 $I_c = 200$ A
 $T_j: 25$ °C (blue), 125 °C (black), 150 °C (red)



Vincotech

30-FT12B2A200H705-PK49L06
datasheet


Inner Boost Switching Characteristics

figure 34.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 2 \text{ } \Omega$


T_j : — 25 °C
— 125 °C
— 150 °C

figure 36.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 2 \text{ } \Omega$


T_j : — 25 °C
— 125 °C
— 150 °C

figure 35.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 200 \text{ A}$


T_j : — 25 °C
— 125 °C
— 150 °C

figure 37.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 200 \text{ A}$

T_j : — 25 °C
— 125 °C
— 150 °C




Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Inner Boost Switching Characteristics

figure 38. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 2 \text{ } \Omega$
 $T_j = 25 \text{ } ^\circ\text{C}$
 $T_j = 125 \text{ } ^\circ\text{C}$
 $T_j = 150 \text{ } ^\circ\text{C}$

figure 39. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$




With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 200 \text{ A}$
 $T_j = 25 \text{ } ^\circ\text{C}$
 $T_j = 125 \text{ } ^\circ\text{C}$
 $T_j = 150 \text{ } ^\circ\text{C}$

figure 40. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 150 \text{ } ^\circ\text{C}$
 $R_{gon} = 2 \text{ } \Omega$
 $R_{goff} = 2 \text{ } \Omega$



Vincotech

30-FT12B2A200H705-PK49L06 datasheet


Outer Boost Switching Characteristics

figure 41.

IGBT

Typical switching energy losses as a function of collector current

$$E = f(I_C)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 2 \text{ } \Omega$
 $R_{goff} = 2 \text{ } \Omega$


T_j : 25 °C
125 °C
150 °C

figure 42.

IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor

$$E = f(R_g)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 200 \text{ A}$


T_j : 25 °C
125 °C
150 °C

figure 43.

FWD

Typical reverse recovered energy loss as a function of collector current

$$E_{rec} = f(I_C)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 2 \text{ } \Omega$


T_j : 25 °C
125 °C
150 °C

figure 44.

FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor

$$E_{rec} = f(R_g)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 200 \text{ A}$

T_j : 25 °C
125 °C
150 °C




Vincotech

30-FT12B2A200H705-PK49L06 datasheet

Outer Boost Switching Characteristics

figure 45. IGBT

Typical switching times as a function of collector current
 $t = f(I_C)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 700$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 2$ Ω
 $R_{goff} = 2$ Ω

figure 46. IGBT

Typical switching times as a function of IGBT turn on gate resistor
 $t = f(R_g)$




With an inductive load at

$T_j = 150$ °C
 $V_{CE} = 700$ V
 $V_{GE} = \pm 15$ V
 $I_C = 200$ A

figure 47. FWD

Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_C)$




With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 2$ Ω

T_j : 25 °C
125 °C
150 °C

figure 48. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor
 $t_{rr} = f(R_{gon})$



With an inductive load at

$V_{CE} = 700$ V
 $V_{GE} = \pm 15$ V
 $I_C = 200$ A

T_j : 25 °C
125 °C
150 °C



Vincotech

30-FT12B2A200H705-PK49L06
datasheet


Outer Boost Switching Characteristics

figure 49.

FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_C)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 2 \text{ } \Omega$


T_j : — 25 °C
— 125 °C
— 150 °C

figure 50.

FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 200 \text{ A}$


T_j : — 25 °C
— 125 °C
— 150 °C

figure 51.

FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_C)$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 2 \text{ } \Omega$


T_j : — 25 °C
— 125 °C
— 150 °C

figure 52.

FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 200 \text{ A}$

T_j : — 25 °C
— 125 °C
— 150 °C




Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Outer Boost Switching Characteristics

figure 53. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_r/dt = f(I_C)$




With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 2 \text{ } \Omega$
 $T_j = 25 \text{ } ^\circ\text{C}$
 $T_j = 125 \text{ } ^\circ\text{C}$
 $T_j = 150 \text{ } ^\circ\text{C}$

figure 54. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor
 $di_f/dt, di_r/dt = f(R_{gon})$




With an inductive load at

$V_{CE} = 700 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 200 \text{ A}$
 $T_j = 25 \text{ } ^\circ\text{C}$
 $T_j = 125 \text{ } ^\circ\text{C}$
 $T_j = 150 \text{ } ^\circ\text{C}$

figure 55. IGBT

Reverse bias safe operating area

$I_C = f(V_{CE})$



At $T_j = 150 \text{ } ^\circ\text{C}$
 $R_{gon} = 2 \text{ } \Omega$
 $R_{goff} = 2 \text{ } \Omega$



Vincotech

30-FT12B2A200H705-PK49L06 datasheet

Switching Definitions

figure 56. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 57. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 58. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 59. IGBT

Turn-on Switching Waveforms & definition of t_r





Vincotech

Switching Definitions

figure 60.

FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 61.

FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





Vincotech

30-FT12B2A200H705-PK49L06

datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	30-FT12B2A200H705-PK49L06
With thermal paste (3,4 W/mK, PSX-P7)	30-FT12B2A200H705-PK49L06-/3/


Marking						
	Text	Name	Date code	UL & VIN	Lot	Serial
		NN-NNNNNNNNNNNNNNNN- TTTT TVV	WWYY	UL VIN	LLLLL	SSSS
	Datamatrix	Type&Ver TTTTTTTV	Lot number LLLLL	Serial SSSS	Date code WWYY	

Outline							
Pin table [mm]							
Pin	X	Y	Function	26	70,9	0	C22
1	0	0	C12	27	53,9	0	DC-Boost2
2	17	0	DC-Boost1	28	50,9	0	DC-Boost2
3	20	0	DC-Boost1	29	50,9	3	DC-Boost2
4	20	3	DC-Boost1	30	38	0	DC+Boost2
5	32,9	0	DC+Boost1	31	38	3	DC+Boost2
6	32,9	3	DC+Boost1	32	38	6	DC+Boost2
7	32,9	6	DC+Boost1	33	67,9	13	G27
8	3	13	G17	34	70,9	13	S27
9	0	13	S17	35	62,9	18,5	FC22
10	8	18,5	FC12	36	54,4	21,5	Boost2
11	16,5	21,5	Boost1	37	51,4	18,5	Boost2
12	19,5	18,5	Boost1	38	51,4	21,5	Boost2
13	19,5	21,5	Boost1	39	44,4	18,5	FC21
14	26,5	18,5	FC11	40	not assembled		
15	32,9	25	Therm11	41	not assembled		
16	32,9	22	Therm12	42	70,9	36,9	G25
17	0	36,9	G15	43	67,9	36,9	S25
18	3	36,9	S15	44	64,9	36,9	FC22
19	6	36,9	FC12	45	61,9	36,9	FC22
20	9	36,9	FC12	46	58,9	36,9	FC22
21	12	36,9	FC12	47	51,9	36,9	FC21
22	19	36,9	FC11	48	48,9	36,9	FC21
23	22	36,9	FC11	49	45,9	36,9	FC21
24	25	36,9	FC11	50	38	36,9	C21
25	32,9	36,9	C11				



Vincotech

Pinout



Identification

ID	Component	Voltage	Current	Function	Comment
T15, T25	IGBT	1200 V	200 A	Inner Boost Switch	
D15, D25	FWD	1200 V	80 A	Inner Boost Diode	
D45, D55	Rectifier	1600 V	40 A	Inner Boost Sw. Protection Diode	
T17, T27	IGBT	1200 V	200 A	Outer Boost Switch	
D17, D27	FWD	1200 V	80 A	Outer Boost Diode	
D47, D57	Rectifier	1600 V	40 A	Outer Boost Sw. Protection Diode	
D19, D29	FWD	1200 V	75 A	Aux Diode H	
D18, D28	FWD	1200 V	75 A	Aux Diode L	
Rt	Thermistor			Thermistor	



Vincotech

30-FT12B2A200H705-PK49L06
datasheet

Packaging instruction				
Standard packaging quantity (SPQ) 36	>SPQ	Standard	<SPQ	Sample
Handling instruction				
Handling instructions for <i>flow 2</i> packages see vincotech.com website.				
Package data				
Package data for <i>flow 2</i> packages see vincotech.com website.				
Vincotech thermistor reference				
See Vincotech thermistor reference table at vincotech.com website.				
Application Note				
For use of pre-charging auxiliary diodes see application note: "The Advantages and Operation of Flying-Capacitor Boosters" at vincotech.com				
UL recognition and file number				
This device is UL 1557 recognized under E192116 up to a junction temperature under switching condition $T_{j,op}=175^{\circ}\text{C}$ and up to 4000VAC/1min isolation voltage. For more information see vincotech.com website.				

Document No.:	Date:	Modification:	Pages
30-FT12B2A200H705-PK49L06-D1-14	6 Aug. 2024	Initial Release	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Vincotech\(威科\)](#)