



flowPIM 1

600 V / 50 A

Topology features

- Kelvin Emitter for improved switching performance
- Open Emitter configuration
- Temperature sensor
- Converter+Brake+Inverter

Component features

- Easy paralleling
- Low turn-off losses
- Low collector emitter saturation voltage
- Positive temperature coefficient
- Short tail current

Housing features

- Base isolation: Al<sub>2</sub>O<sub>3</sub>
- Convex shaped substrate for superior thermal contact
- Thermo-mechanical push-and-pull force relief
- Solder pin


Target applications

- Industrial drives
- Embedded drives


Types

- V23990-P586-A20-PM

flow 1 17 mm housing



Schematic





Vincotech

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

| Parameter                         | Symbol     | Conditions   | Value    | Unit               |
|-----------------------------------|------------|--|----------|--------------------|
| <b>Inverter Switch</b>            |            |  |          |                    |
| Collector-emitter voltage         | $V_{CES}$  |  | 600      | V                  |
| Collector current (DC current)    | $I_C$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                  | 44       | A                  |
| Repetitive peak collector current | $I_{CRM}$  | $t_p$ limited by $T_{jmax}$  | 150      | A                  |
| Total power dissipation           | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                  | 90       | W                  |
| Gate-emitter voltage              | $V_{GES}$  |  | $\pm 20$ | V                  |
| Short circuit ratings             | $t_{SC}$   | $V_{GE} = 15\text{ V}$ , $V_{CC} = 360\text{ V}$ $T_j = 150\text{ °C}$ | 6        | $\mu\text{s}$      |
| Maximum junction temperature      | $T_{jmax}$ |  | 175      | $^{\circ}\text{C}$ |

|                                 |            |                                       |     |                    |
|---------------------------------|------------|---------------------------------------|-----|--------------------|
| <b>Inverter Diode</b>           |            |                                       |     |                    |
| Peak repetitive reverse voltage | $V_{RRM}$  |                                       | 600 | V                  |
| Forward current (DC current)    | $I_F$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 39  | A                  |
| Repetitive peak forward current | $I_{FRM}$  | $t_p$ limited by $T_{jmax}$           | 100 | A                  |
| Total power dissipation         | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 68  | W                  |
| Maximum junction temperature    | $T_{jmax}$ |                                       | 175 | $^{\circ}\text{C}$ |

|                                   |            |  |          |                    |
|-----------------------------------|------------|--|----------|--------------------|
| <b>Brake Switch</b>               |            |  |          |                    |
| Collector-emitter voltage         | $V_{CES}$  |  | 600      | V                  |
| Collector current (DC current)    | $I_C$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                  | 33       | A                  |
| Repetitive peak collector current | $I_{CRM}$  | $t_p$ limited by $T_{jmax}$  | 90       | A                  |
| Total power dissipation           | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                  | 64       | W                  |
| Gate-emitter voltage              | $V_{GES}$  |  | $\pm 20$ | V                  |
| Short circuit ratings             | $t_{SC}$   | $V_{GE} = 15\text{ V}$ , $V_{CC} = 360\text{ V}$ $T_j = 150\text{ °C}$ | 6        | $\mu\text{s}$      |
| Maximum junction temperature      | $T_{jmax}$ |  | 175      | $^{\circ}\text{C}$ |



Vincotech

## Maximum Ratings

$T_j = 25\text{ °C}$ , unless otherwise specified

| Parameter                       | Symbol     | Conditions                            | Value | Unit |
|---------------------------------|------------|---------------------------------------|-------|------|
| <b>Brake Diode</b>              |            |                                       |       |      |
| Peak repetitive reverse voltage | $V_{RRM}$  |                                       | 600   | V    |
| Forward current (DC current)    | $I_F$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 22    | A    |
| Repetitive peak forward current | $I_{FRM}$  | $t_p$ limited by $T_{jmax}$           | 40    | A    |
| Total power dissipation         | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$ | 37    | W    |
| Maximum junction temperature    | $T_{jmax}$ |                                       | 175   | °C   |

## Rectifier Diode

|  |            |  |      |                  |
|--|------------|--|------|------------------|
| Peak repetitive reverse voltage        | $V_{RRM}$  |  | 1600 | V                |
| Forward current (DC current)           | $I_F$      | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                | 44   | A                |
| Surge (non-repetitive) forward current | $I_{FSM}$  | Single Half Sine Wave,<br>$t_p = 10\text{ ms}$ $T_j = 150\text{ °C}$ | 270  | A                |
| Surge current capability               | $I^2t$     |  | 370  | A <sup>2</sup> s |
| Total power dissipation                | $P_{tot}$  | $T_j = T_{jmax}$ $T_s = 80\text{ °C}$                                | 56   | W                |
| Maximum junction temperature           | $T_{jmax}$ |  | 150  | °C               |

## Module Properties

### Thermal Properties

|   |           |  |                            |    |
|---|-----------|--|----------------------------|----|
| Storage temperature                             | $T_{stg}$ |  | -40...+125                 | °C |
| Operation temperature under switching condition | $T_{jop}$ |  | -40...+( $T_{jmax} - 25$ ) | °C |

### Isolation Properties

|                            |            |                                     |          |    |
|----------------------------|------------|-------------------------------------|----------|----|
| Isolation voltage          | $V_{isol}$ | DC Test Voltage* $t_p = 2\text{ s}$ | 4000     | V  |
| Isolation voltage          | $V_{isol}$ | AC Voltage $t_p = 1\text{ min}$     | 2500     | V  |
| Creepage distance          |            |                                     | min 12,7 | mm |
| Clearance                  |            |                                     | min 12,7 | mm |
| Comparative Tracking Index | CTI        |                                     | ≥ 600    |    |

\*100 % tested in production



### Characteristic Values

| Parameter | Symbol | Conditions                   |   |                                     |            |     | Values |     |  | Unit |
|-----------|--------|------------------------------|---|-------------------------------------|------------|-----|--------|-----|--|------|
|           |        | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min | Typ    | Max |  |      |

#### Inverter Switch

##### Static

|                                      |               |                   |    |     |        |           |      |              |                     |    |
|--------------------------------------|---------------|-------------------|----|-----|--------|-----------|------|--------------|---------------------|----|
| Gate-emitter threshold voltage       | $V_{GE(th)}$  | $V_{CE} = V_{GE}$ |    |     | 0,0008 | 25        | 5    | 5,8          | 6,5                 | V  |
| Collector-emitter saturation voltage | $V_{CE(sat)}$ |                   | 15 |     | 50     | 25<br>125 | 1,05 | 1,76<br>2,07 | 1,85 <sup>(1)</sup> | V  |
| Collector-emitter cut-off current    | $I_{CES}$     |                   | 0  | 600 |        | 25        |      |              | 2,6                 | µA |
| Gate-emitter leakage current         | $I_{GES}$     |                   | 20 | 0   |        | 25        |      |              | 600                 | nA |
| Internal gate resistance             | $r_g$         |                   |    |     |        |           |      | None         |                     | Ω  |
| Input capacitance                    | $C_{ies}$     |                   |    |     |        |           |      | 3140         |                     | pF |
| Output capacitance                   | $C_{oes}$     | $f = 1$ Mhz       | 0  | 25  |        | 25        |      | 200          |                     | pF |
| Reverse transfer capacitance         | $C_{res}$     |                   |    |     |        |           |      | 93           |                     | pF |

##### Thermal

|  |               |                                       |  |  |  |  |  |      |  |     |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4$ W/mK<br>(PSX) |  |  |  |  |  | 1,06 |  | K/W |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|

##### Dynamic

|                             |              |   |  |  |  |                  |  |                            |  |     |
|-----------------------------|--------------|---|--|--|--|------------------|--|----------------------------|--|-----|
| Turn-on delay time          | $t_{d(on)}$  |   |  |  |  | 25<br>125<br>150 |  | 187,32<br>185,79<br>186,12 |  | ns  |
| Rise time                   | $t_r$        |   |  |  |  | 25<br>125<br>150 |  | 29,43<br>33,19<br>33,33    |  | ns  |
| Turn-off delay time         | $t_{d(off)}$ |   |  |  |  | 25<br>125<br>150 |  | 230,26<br>252,25<br>257,76 |  | ns  |
| Fall time                   | $t_f$        |   |  |  |  | 25<br>125<br>150 |  | 46,24<br>81,64<br>91,61    |  | ns  |
| Turn-on energy (per pulse)  | $E_{on}$     | $Q_{tFWD} = 1,4$ µC<br>$Q_{tFWD} = 3,14$ µC<br>$Q_{tFWD} = 3,63$ µC |  |  |  | 25<br>125<br>150 |  | 1,23<br>1,61<br>1,7        |  | mWs |
| Turn-off energy (per pulse) | $E_{off}$    |   |  |  |  | 25<br>125<br>150 |  | 1,18<br>1,53<br>1,62       |  | mWs |



### Characteristic Values

| Parameter  | Symbol               | Conditions  |   |                                     |            |           | Values |              |                    | Unit |
|--|----------------------|---|---|-------------------------------------|------------|-----------|--------|--------------|--------------------|------|
|  |                      | $V_{GE}$ [V]<br>$V_{GS}$ [V]                                | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min       | Typ    | Max          |                    |      |
| <b>Inverter Diode</b>                              |                      |   |   |                                     |            |           |        |              |                    |      |
| <b>Static</b>                                      |                      |   |   |                                     |            |           |        |              |                    |      |
| Forward voltage                                    | $V_F$                |   |   |                                     | 50         | 25<br>125 | 1,2    | 1,85<br>1,94 | 1,9 <sup>(1)</sup> | V    |
| Reverse leakage current                            | $I_R$                | $V_i = 600$ V   |   |                                     |            | 25        |        |              | 27                 | μA   |
| <b>Thermal</b>                                     |                      |   |   |                                     |            |           |        |              |                    |      |
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$        | $\lambda_{paste} = 3,4$ W/mK<br>(PSX)                       |   |                                     |            |           |        | 1,4          |                    | K/W  |
| <b>Dynamic</b>                                     |                      |   |   |                                     |            |           |        |              |                    |      |
| Peak recovery current                              | $I_{RRM}$            | $di/dt=2130$ A/μs<br>$di/dt=2041$ A/μs<br>$di/dt=1746$ A/μs | ±15                                       | 350                                 | 50         | 25        |        | 32,06        |                    | A    |
| Reverse recovery time                              | $t_{rr}$             |   |   |                                     |            | 125       |        | 41,26        |                    |      |
|  |                      |   |   |                                     |            | 150       |        | 44,23        |                    |      |
|  |                      |   |   |                                     |            | 25        |        | 161,66       |                    |      |
| Recovered charge                                   | $Q_r$                |   |   |                                     |            | 125       |        | 221,71       |                    |      |
|  |                      |   |   |                                     |            | 150       |        | 240,15       |                    |      |
|  |                      | 25  |   | 1,4                                 |            |           |        |              |                    |      |
| Reverse recovered energy                           | $E_{rec}$            | 125   |   | 3,14                                |            |           |        |              |                    |      |
|  |                      | 150   |   | 3,63                                |            |           |        |              |                    |      |
|  |                      | 25  |   | 0,301                               |            |           |        |              |                    |      |
| Peak rate of fall of recovery current              | $(di_{rr}/dt)_{max}$ | 125   |   | 0,695                               |            |           |        |              |                    |      |
|  |                      | 150   |   | 0,81                                |            |           |        |              |                    |      |
|  |                      | 25  |   | 2514,84                             |            |           |        |              |                    |      |
|  |                      |   |   |                                     |            | 125       |        | 1010,64      |                    | A/μs |
|  |                      |   |   |                                     |            | 150       |        | 981,58       |                    |      |



Vincotech

V23990-P586-A20-PM  
datasheet

### Characteristic Values

| Parameter | Symbol | Conditions                   |   |                                     |            |     | Values |     |  | Unit |
|-----------|--------|------------------------------|---|-------------------------------------|------------|-----|--------|-----|--|------|
|           |        | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min | Typ    | Max |  |      |

### Brake Switch

#### Static

|                                      |               |                   |    |     |         |           |     |              |                    |    |
|--------------------------------------|---------------|-------------------|----|-----|---------|-----------|-----|--------------|--------------------|----|
| Gate-emitter threshold voltage       | $V_{GE(th)}$  | $V_{CE} = V_{GE}$ |    |     | 0,00043 | 25        | 5   | 5,8          | 6,5                | V  |
| Collector-emitter saturation voltage | $V_{CE(sat)}$ |                   | 15 |     | 30      | 25<br>125 | 1,1 | 1,55<br>1,75 | 1,9 <sup>(1)</sup> | V  |
| Collector-emitter cut-off current    | $I_{CES}$     |                   | 0  | 600 |         | 25        |     |              | 1,6                | µA |
| Gate-emitter leakage current         | $I_{GES}$     |                   | 20 | 0   |         | 25        |     |              | 300                | nA |
| Internal gate resistance             | $r_g$         |                   |    |     |         |           |     | None         |                    | Ω  |
| Input capacitance                    | $C_{ies}$     |                   |    |     |         |           |     | 1630         |                    | pF |
| Output capacitance                   | $C_{oes}$     | $f = 1$ Mhz       | 0  | 25  |         | 25        |     | 108          |                    | pF |
| Reverse transfer capacitance         | $C_{res}$     |                   |    |     |         |           |     | 50           |                    | pF |

#### Thermal

|  |               |                                       |  |  |  |  |  |      |  |     |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4$ W/mK<br>(PSX) |  |  |  |  |  | 1,49 |  | K/W |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|

#### Dynamic

|                             |              |   |  |  |  |                  |  |                            |  |     |
|-----------------------------|--------------|---|--|--|--|------------------|--|----------------------------|--|-----|
| Turn-on delay time          | $t_{d(on)}$  |   |  |  |  | 25<br>125<br>150 |  | 20,2<br>19,58<br>19,11     |  | ns  |
| Rise time                   | $t_r$        |   |  |  |  | 25<br>125<br>150 |  | 27,61<br>28,44<br>28,57    |  | ns  |
| Turn-off delay time         | $t_{d(off)}$ |   |  |  |  | 25<br>125<br>150 |  | 182,75<br>204,09<br>210,02 |  | ns  |
| Fall time                   | $t_f$        |   |  |  |  | 25<br>125<br>150 |  | 62,53<br>76,57<br>85,53    |  | ns  |
| Turn-on energy (per pulse)  | $E_{on}$     | $Q_{tFWD} = 0,703$ µC<br>$Q_{tFWD} = 1,52$ µC<br>$Q_{tFWD} = 1,77$ µC |  |  |  | 25<br>125<br>150 |  | 0,701<br>0,931<br>0,996    |  | mWs |
| Turn-off energy (per pulse) | $E_{off}$    |   |  |  |  | 25<br>125<br>150 |  | 0,744<br>0,994<br>1,06     |  | mWs |



### Characteristic Values

| Parameter | Symbol | Conditions   |              |              |              |           |           | Values     |     |     | Unit |
|-----------|--------|--------------|--------------|--------------|--------------|-----------|-----------|------------|-----|-----|------|
|           |        | $V_{GE}$ [V] | $V_{GS}$ [V] | $V_{CE}$ [V] | $V_{DS}$ [V] | $I_C$ [A] | $I_D$ [A] | $T_j$ [°C] | Min | Typ |      |

#### Brake Diode

##### Static

|                         |       |               |  |  |    |           |      |              |                     |    |
|-------------------------|-------|---------------|--|--|----|-----------|------|--------------|---------------------|----|
| Forward voltage         | $V_F$ |               |  |  | 20 | 25<br>125 | 1,25 | 1,74<br>1,67 | 1,95 <sup>(1)</sup> | V  |
| Reverse leakage current | $I_R$ | $V_i = 600$ V |  |  |    | 25        |      |              | 27                  | μA |

##### Thermal

|  |               |                                       |  |  |  |  |  |     |  |     |
|--|---------------|---------------------------------------|--|--|--|--|--|-----|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4$ W/mK<br>(PSX) |  |  |  |  |  | 2,6 |  | K/W |
|--|---------------|---------------------------------------|--|--|--|--|--|-----|--|-----|

##### Dynamic

|                                       |                      |  |      |       |      |     |  |        |    |   |
|---------------------------------------|----------------------|--|------|-------|------|-----|--|--------|----|---|
| Peak recovery current                 | $I_{RRM}$            | $di/dt=860$ A/μs<br>$di/dt=861$ A/μs<br>$di/dt=949$ A/μs | 0/15 | 400   | 30   | 25  |  | 10,28  |    | A |
| Reverse recovery time                 | $t_{rr}$             |  |      |       |      | 125 |  | 13,34  | ns |   |
|                                       |                      |  |      |       |      | 150 |  | 14,49  |    |   |
|                                       |                      |  |      |       |      | 25  |  | 167,93 |    |   |
| Recovered charge                      | $Q_r$                |  |      |       |      | 125 |  | 242,98 | μC |   |
|                                       |                      |  |      |       |      | 150 |  | 263,64 |    |   |
|                                       |                      | 25   |      | 0,703 |      |     |  |        |    |   |
| Reverse recovered energy              | $E_{rec}$            | 125  |      | 1,52  | mWs  |     |  |        |    |   |
|                                       |                      | 150  |      | 1,77  |      |     |  |        |    |   |
|                                       |                      | 25   |      | 0,195 |      |     |  |        |    |   |
| Peak rate of fall of recovery current | $(di_{rr}/dt)_{max}$ | 125  |      | 0,429 | A/μs |     |  |        |    |   |
|                                       |                      | 150  |      | 0,505 |      |     |  |        |    |   |
|                                       |                      | 25   |      | 44,97 |      |     |  |        |    |   |
|                                       |                      |  |      |       |      | 125 |  | 88,68  |    |   |
|                                       |                      |  |      |       |      | 150 |  | 94,34  |    |   |



### Characteristic Values

| Parameter | Symbol | Conditions                   |   |                                     |            |     | Values |     |  | Unit |
|-----------|--------|------------------------------|---|-------------------------------------|------------|-----|--------|-----|--|------|
|           |        | $V_{GE}$ [V]<br>$V_{GS}$ [V] | $V_{CE}$ [V]<br>$V_{DS}$ [V]<br>$V_F$ [V] | $I_C$ [A]<br>$I_D$ [A]<br>$I_F$ [A] | $T_j$ [°C] | Min | Typ    | Max |  |      |

#### Rectifier Diode

##### Static

|                         |       |                |  |  |    |           |  |                |   |    |
|-------------------------|-------|----------------|--|--|----|-----------|--|----------------|---|----|
| Forward voltage         | $V_F$ |                |  |  | 13 | 25<br>125 |  | 0,995<br>0,927 | 1,21 <sup>(1)</sup><br>1,1 <sup>(1)</sup> | V  |
| Reverse leakage current | $I_R$ | $V_i = 1600$ V |  |  |    | 25        |  |                | 50  | μA |

##### Thermal

|  |               |                                       |  |  |  |  |  |      |  |     |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|
| Thermal resistance junction to sink <sup>(2)</sup> | $R_{th(j-s)}$ | $\lambda_{paste} = 3,4$ W/mK<br>(PSX) |  |  |  |  |  | 1,25 |  | K/W |
|--|---------------|---------------------------------------|--|--|--|--|--|------|--|-----|

#### Thermistor

##### Static

|                                |                |                    |  |  |  |     |    |      |   |      |
|--------------------------------|----------------|--------------------|--|--|--|-----|----|------|---|------|
| Rated resistance               | $R$            |                    |  |  |  | 25  |    | 22   |   | kΩ   |
| Deviation of $R_{100}$         | $\Delta_{R/R}$ | $R_{100} = 1484$ Ω |  |  |  | 100 | -5 |      | 5 | %    |
| Power dissipation              | $P$            |                    |  |  |  | 25  |    | 130  |   | mW   |
| Power dissipation constant     | $d$            |                    |  |  |  | 25  |    | 1,5  |   | mW/K |
| B-value                        | $B_{(25/50)}$  | Tol. ±1 %          |  |  |  |     |    | 3962 |   | K    |
| B-value                        | $B_{(25/100)}$ | Tol. ±1 %          |  |  |  |     |    | 4000 |   | K    |
| Vincotech Thermistor Reference |                |                    |  |  |  |     |    |      | I |      |

<sup>(1)</sup> Value at chip level

<sup>(2)</sup> Only valid with pre-applied Vincotech thermal interface material.






## Inverter Switch Characteristics

**figure 1.** IGBT


Typical output characteristics  
 $I_C = f(V_{CE})$



$t_p = 250 \mu s$   
 $V_{GE} = 15 V$   
 $T_j:$  — 25 °C  
— 125 °C

**figure 2.** IGBT


Typical output characteristics  
 $I_C = f(V_{CE})$



$t_p = 250 \mu s$   
 $T_j = 125 \text{ °C}$   
 $V_{GE}$  from 7 V to 17 V in steps of 1 V

**figure 3.** IGBT


Typical transfer characteristics  
 $I_C = f(V_{GE})$



$t_p = 250 \mu s$   
 $V_{CE} = 10 V$   
 $T_j:$  — 25 °C  
— 125 °C

**figure 4.** IGBT

Transient thermal impedance as a function of pulse width  
 $Z_{th(j-s)} = f(t_p)$



$D = t_p / T$   
 $R_{th(j-s)} = 1,059 \text{ K/W}$   
IGBT thermal model values  

| R (K/W)  | $\tau$ (s) |
|----------|------------|
| 1,11E-01 | 1,12E+00   |
| 3,60E-01 | 1,48E-01   |
| 3,77E-01 | 4,74E-02   |
| 1,24E-01 | 7,68E-03   |
| 4,58E-02 | 6,49E-04   |
| 4,19E-02 | 1,61E-04   |




### Inverter Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D =$  single pulse  
 $T_s = 80 \text{ } ^\circ\text{C}$   
 $V_{CE} = 15 \text{ V}$   
 $T_j = T_{jmax}$




## Inverter Diode Characteristics

figure 6. FWD

Typical forward characteristics

$$I_F = f(V_F)$$




$t_p = 250 \mu s$   
 $T_j$ : — 25 °C  
— 125 °C

figure 7. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$   
 $R_{th(j-s)} = 1,399 \text{ K/W}$   
FWD thermal model values

| $R$ (K/W) | $\tau$ (s) |
|-----------|------------|
| 6,76E-02  | 3,05E+00   |
| 1,79E-01  | 3,50E-01   |
| 6,70E-01  | 7,08E-02   |
| 2,72E-01  | 1,81E-02   |
| 1,35E-01  | 4,13E-03   |
| 7,56E-02  | 5,11E-04   |




## Brake Switch Characteristics

figure 8. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$   
 $V_{GE} = 15 V$   
 $T_j: 25^\circ C$  (blue line)  
 $125^\circ C$  (red line)

figure 9. IGBT

Typical output characteristics

$$I_C = f(V_{CE})$$




$t_p = 250 \mu s$   
 $T_j = 125^\circ C$   
 $V_{GE}$  from 7 V to 17 V in steps of 1 V

figure 10. IGBT

Typical transfer characteristics

$$I_C = f(V_{GE})$$




$t_p = 250 \mu s$   
 $V_{CE} = 10 V$   
 $T_j: 25^\circ C$  (blue line)  
 $125^\circ C$  (red line)

figure 11. IGBT

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$   
 $R_{th(j-s)} = 1,49 K/W$   
IGBT thermal model values

| R (K/W)  | $\tau$ (s) |
|----------|------------|
| 7,25E-02 | 2,15E+00   |
| 1,02E-01 | 4,82E-01   |
| 6,96E-01 | 9,49E-02   |
| 3,56E-01 | 3,40E-02   |
| 1,42E-01 | 5,95E-03   |
| 4,77E-02 | 1,04E-03   |
| 7,51E-02 | 2,72E-04   |




### Brake Switch Characteristics

figure 12. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D =$  single pulse  
 $T_s = 80$  °C  
 $V_{CE} = 15$  V  
 $T_j = T_{jmax}$



### Brake Diode Characteristics

figure 13. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 14. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$

$R_{th(j-s)} = 2,598 \text{ K/W}$

FWD thermal model values

| $R \text{ (K/W)}$ | $\tau \text{ (s)}$ |
|-------------------|--------------------|
| 6,56E-02          | 4,59E+00           |
| 1,58E-01          | 5,68E-01           |
| 8,97E-01          | 8,41E-02           |
| 1,05E+00          | 3,28E-02           |
| 2,75E-01          | 4,96E-03           |
| 1,51E-01          | 7,65E-04           |



## Rectifier Diode Characteristics

figure 15. Rectifier

Typical forward characteristics

$$I_F = f(V_F)$$





figure 16. Rectifier

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$

$R_{th(j-s)} = 1,254 \text{ K/W}$

Rectifier thermal model values

| $R \text{ (K/W)}$ | $\tau \text{ (s)}$ |
|-------------------|--------------------|
| 8,00E-02          | 5,22E+00           |
| 1,56E-01          | 4,18E-01           |
| 6,95E-01          | 8,82E-02           |
| 2,23E-01          | 3,07E-02           |
| 9,97E-02          | 5,99E-03           |




## Thermistor Characteristics

figure 17. Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$








## Inverter Switching Characteristics

**figure 18.** IGBT

Typical switching energy losses as a function of collector current  
 $E = f(I_c)$




With an inductive load at  
 $V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{g(on)} = 16 \ \Omega$   
 $R_{g(off)} = 16 \ \Omega$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 19.** IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor  
 $E = f(R_g)$




With an inductive load at  
 $V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 20.** FWD

Typical reverse recovered energy loss as a function of collector current  
 $E_{rec} = f(I_c)$




With an inductive load at  
 $V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{g(on)} = 16 \ \Omega$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 21.** FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor  
 $E_{rec} = f(R_g)$



With an inductive load at  
 $V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$


$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C



## Inverter Switching Characteristics

**figure 22.** IGBT


Typical switching times as a function of collector current  
 $t = f(I_c)$



With an inductive load at  
 $T_j = 150 \text{ }^\circ\text{C}$   
 $V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{gon} = 16 \text{ } \Omega$   
 $R_{goff} = 16 \text{ } \Omega$

**figure 23.** IGBT


Typical switching times as a function of IGBT turn on gate resistor  
 $t = f(R_g)$



With an inductive load at  
 $T_j = 150 \text{ }^\circ\text{C}$   
 $V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$

**figure 24.** FWD


Typical reverse recovery time as a function of collector current  
 $t_{rr} = f(I_c)$



With an inductive load at  
 $V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{gon} = 16 \text{ } \Omega$   
 $T_j:$  — 25 °C  
— 125 °C  
— 150 °C

**figure 25.** FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor  
 $t_{rr} = f(R_{gon})$



With an inductive load at  
 $V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$   
 $T_j:$  — 25 °C  
— 125 °C  
— 150 °C




## Inverter Switching Characteristics

**figure 26.** FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{gon} = 16 \ \Omega$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 27.** FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at


$V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 28.** FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $R_{gon} = 16 \ \Omega$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 29.** FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 350 \text{ V}$   
 $V_{GE} = \pm 15 \text{ V}$   
 $I_c = 50 \text{ A}$


$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C



## Inverter Switching Characteristics

**figure 30.** FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current  
 $di_i/dt, di_r/dt = f(I_c)$




With an inductive load at

|             |       |        |        |
|-------------|-------|--------|--------|
| $V_{CE} =$  | 350 V | $T_j:$ | 25 °C  |
| $V_{GE} =$  | ±15 V |        | 125 °C |
| $R_{gon} =$ | 16 Ω  |        | 150 °C |

**figure 31.** FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor  
 $di_i/dt, di_r/dt = f(R_{gon})$




With an inductive load at

|            |       |        |        |
|------------|-------|--------|--------|
| $V_{CE} =$ | 350 V | $T_j:$ | 25 °C  |
| $V_{GE} =$ | ±15 V |        | 125 °C |
| $I_c =$    | 50 A  |        | 150 °C |

**figure 32.** IGBT

Reverse bias safe operating area  
 $I_c = f(V_{CE})$




At  $T_j = 150$  °C  
 $R_{gon} = 16$  Ω  
 $R_{goff} = 16$  Ω



## Brake Switching Characteristics

**figure 33.** IGBT

Typical switching energy losses as a function of collector current  
 $E = f(I_c)$




With an inductive load at  
 $V_{CE} = 400$  V  
 $V_{GE} = 0/15$  V  
 $R_{gon} = 8$   $\Omega$   
 $R_{goff} = 8$   $\Omega$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 34.** IGBT

Typical switching energy losses as a function of IGBT turn on gate resistor  
 $E = f(R_g)$




With an inductive load at  
 $V_{CE} = 400$  V  
 $V_{GE} = 0/15$  V  
 $I_c = 30$  A

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 35.** FWD

Typical reverse recovered energy loss as a function of collector current  
 $E_{rec} = f(I_c)$




With an inductive load at  
 $V_{CE} = 400$  V  
 $V_{GE} = 0/15$  V  
 $R_{gon} = 8$   $\Omega$

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 36.** FWD

Typical reverse recovered energy loss as a function of IGBT turn on gate resistor  
 $E_{rec} = f(R_g)$



With an inductive load at  
 $V_{CE} = 400$  V  
 $V_{GE} = 0/15$  V  
 $I_c = 30$  A


$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C



## Brake Switching Characteristics

**figure 37.** IGBT


Typical switching times as a function of collector current  
 $t = f(I_c)$



With an inductive load at  
 $T_j = 150 \text{ }^\circ\text{C}$   
 $V_{CE} = 400 \text{ V}$   
 $V_{GE} = 0/15 \text{ V}$   
 $R_{gon} = 8 \text{ } \Omega$   
 $R_{goff} = 8 \text{ } \Omega$

**figure 38.** IGBT


Typical switching times as a function of IGBT turn on gate resistor  
 $t = f(R_g)$



With an inductive load at  
 $T_j = 150 \text{ }^\circ\text{C}$   
 $V_{CE} = 400 \text{ V}$   
 $V_{GE} = 0/15 \text{ V}$   
 $I_c = 30 \text{ A}$

**figure 39.** FWD


Typical reverse recovery time as a function of collector current  
 $t_{rr} = f(I_c)$



With an inductive load at  
 $V_{CE} = 400 \text{ V}$   
 $V_{GE} = 0/15 \text{ V}$   
 $R_{gon} = 8 \text{ } \Omega$   
 $T_j: \text{ } \text{---} 25 \text{ }^\circ\text{C}$   
 $\text{---} 125 \text{ }^\circ\text{C}$   
 $\text{---} 150 \text{ }^\circ\text{C}$

**figure 40.** FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor  
 $t_{rr} = f(R_{gon})$



With an inductive load at  
 $V_{CE} = 400 \text{ V}$   
 $V_{GE} = 0/15 \text{ V}$   
 $I_c = 30 \text{ A}$   
 $T_j: \text{ } \text{---} 25 \text{ }^\circ\text{C}$   
 $\text{---} 125 \text{ }^\circ\text{C}$   
 $\text{---} 150 \text{ }^\circ\text{C}$




## Brake Switching Characteristics

**figure 41.** FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 400$  V  
 $V_{GE} = 0/15$  V  
 $R_{gon} = 8$  Ω

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 42.** FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gon})$$



With an inductive load at


$V_{CE} = 400$  V  
 $V_{GE} = 0/15$  V  
 $I_c = 30$  A

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 43.** FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 400$  V  
 $V_{GE} = 0/15$  V  
 $R_{gon} = 8$  Ω

$T_j$ : — 25 °C  
— 125 °C  
— 150 °C

**figure 44.** FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gon})$$



With an inductive load at

$V_{CE} = 400$  V  
 $V_{GE} = 0/15$  V  
 $I_c = 30$  A


$T_j$ : — 25 °C  
— 125 °C  
— 150 °C



## Brake Switching Characteristics

**figure 45.** FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current  
 $di_f/dt, di_r/dt = f(I_c)$




With an inductive load at  
 $V_{CE} = 400$  V  
 $V_{GE} = 0/15$  V  
 $R_{gon} = 8$  Ω

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 46.** FWD

Typical rate of fall of forward and reverse recovery current as a function of turn on gate resistor  
 $di_f/dt, di_r/dt = f(R_{gon})$




With an inductive load at  
 $V_{CE} = 400$  V  
 $V_{GE} = 0/15$  V  
 $I_c = 30$  A

$T_j$ :  
— 25 °C  
— 125 °C  
— 150 °C

**figure 47.** IGBT

Reverse bias safe operating area

$I_c = f(V_{CE})$



At  $T_j = 150$  °C  
 $R_{gon} = 8$  Ω  
 $R_{goff} = 8$  Ω





## Switching Definitions

figure 48. IGBT

Turn-off Switching Waveforms & definition of  $t_{doff}$ ,  $t_{Eoff}$  ( $t_{Eoff}$  = integrating time for  $E_{off}$ )




figure 49. IGBT

Turn-on Switching Waveforms & definition of  $t_{don}$ ,  $t_{Eon}$  ( $t_{Eon}$  = integrating time for  $E_{on}$ )




figure 50. IGBT

Turn-off Switching Waveforms & definition of  $t_f$





figure 51. IGBT

Turn-on Switching Waveforms & definition of  $t_r$





### Switching Definitions

figure 52. FWD

Turn-off Switching Waveforms & definition of  $t_{rr}$





figure 53. FWD

Turn-on Switching Waveforms & definition of  $t_{Qr}$  ( $t_{Qr}$  = integrating time for  $Q_r$ )







Vincotech

**V23990-P586-A20-PM**  
datasheet

| Ordering Code                            |                        |
|--|------------------------|
| <b>Version</b>                           | <b>Ordering Code</b>   |
| Without thermal paste                    | V23990-P586-A20-PM     |
| With thermal paste (5,2 W/mK, PTM6000HV) | V23990-P586-A20-/7/-PM |
| With thermal paste (3,4 W/mK, PSX-P7)    | V23990-P586-A20-/3/-PM |

| Marking |                   |                     |                   |                     |                  |            |               |
|---------|-------------------|---------------------|-------------------|---------------------|------------------|------------|---------------|
|         | <b>Text</b>       | <b>VIN</b>          | <b>Date code</b>  | <b>Type&amp;Ver</b> | <b>UL</b>        | <b>Lot</b> | <b>Serial</b> |
|         |                   | VIN                 | WWYY              | TTTTTTVV            | UL               | LLLLL      | SSSS          |
|         | <b>Datamatrix</b> | <b>Type&amp;Ver</b> | <b>Lot number</b> | <b>Serial</b>       | <b>Date code</b> |            |               |
|         |                   | TTTTTTVV            | LLLLL             | SSSS                | WWYY             |            |               |


| Outline        |       |      |          |  |
|----------------|-------|------|----------|--|
| Pin table [mm] |       |      |          |  |
| Pin            | X     | Y    | Function |  |
| 1              | 52,55 | 0    | BrG      |  |
| 2              | 47,7  | 0    | DC-      |  |
| 3              | 44,8  | 0    | DC-      |  |
| 4              | 37,8  | 0    | DC+      |  |
| 5              | 37,8  | 2,8  | DC+      |  |
| 6              | 35    | 0    | Inv+     |  |
| 7              | 35    | 2,8  | Inv+     |  |
| 8              | 28    | 0    | R1       |  |
| 9              | 25,2  | 0    | R2       |  |
| 10             | 22,4  | 0    | N6       |  |
| 11             | 19,6  | 0    | G6       |  |
| 12             | 16,8  | 0    | S6       |  |
| 13             | 14    | 0    | N4       |  |
| 14             | 11,2  | 0    | G4       |  |
| 15             | 8,4   | 0    | S4       |  |
| 16             | 5,6   | 0    | N2       |  |
| 17             | 2,8   | 0    | G2       |  |
| 18             | 0     | 0    | S2       |  |
| 19             | 0     | 28,5 | U        |  |
| 20             | 2,8   | 28,5 | G1       |  |
| 21             | 7,5   | 28,5 | S1       |  |
| 22             | 14,5  | 28,5 | V        |  |
| 23             | 17,3  | 28,5 | G3       |  |
| 24             | 22    | 28,5 | S3       |  |
| 25             | 29    | 28,5 | W        |  |
| 26             | 31,8  | 28,5 | G5       |  |
| 27             | 36,5  | 28,5 | S5       |  |
| 28             | 43,5  | 28,5 | L1       |  |
| 29             | 52,55 | 25   | L2       |  |
| 30             | 52,55 | 16,9 | L3       |  |
| 31             | 52,55 | 8,6  | BrC      |  |
| 32             | 52,55 | 2,8  | BrE      |  |

Tolerance of pins position: +0.5mm at the end of pins  
Dimension of coordinate axis is only offset without tolerance



Vincotech



| Identification             |           |         |         |                 |         |
|----------------------------|-----------|---------|---------|-----------------|---------|
| ID                         | Component | Voltage | Current | Function        | Comment |
| T2, T1, T4, T3, T6, T5     | IGBT      | 600 V   | 50 A    | Inverter Switch |         |
| D1, D2, D3, D4, D5, D6     | FWD       | 600 V   | 50 A    | Inverter Diode  |         |
| T7                         | IGBT      | 600 V   | 30 A    | Brake Switch    |         |
| D7                         | FWD       | 600 V   | 20 A    | Brake Diode     |         |
| D8, D9, D10, D11, D12, D13 | Rectifier | 1600 V  | 35 A    | Rectifier Diode |         |
| NTC                        | NTC       |         |         | Thermistor      |         |




| Packaging instruction                 |      |          |      |        |
|---------------------------------------|------|----------|------|--------|
| Standard packaging quantity (SPQ) 100 | >SPQ | Standard | <SPQ | Sample |

| Handling instruction  |
|---|
| Handling instructions for <i>flow 1</i> packages see vincotech.com website. |

| Package data   |
|--|
| Package data for <i>flow 1</i> packages see vincotech.com website. |

| Vincotech thermistor reference                                     |
|--|
| See Vincotech thermistor reference table at vincotech.com website. |

| UL recognition and file number  |
|---|
| This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website.  |

| Document No.:            | Date:       | Modification:   | Pages |
|--------------------------|-------------|---|-------|
| V23990-P586-A20-PM-D6-14 | 5 May. 2022 | Separate datasheet for pressfit pin version & housing |       |

**DISCLAIMER**

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

**LIFE SUPPORT POLICY**

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Vincotech\(威科\)](#)