



<i>flow</i> MNPC 0	1200 V / 80 A
<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <p style="text-align: center; margin: 0;">Features</p> <ul style="list-style-type: none"> Mixed voltage component topology Neutral point clamped inverter Reactive power capability Low inductance layout </div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <p style="text-align: center; margin: 0;">Target applications</p> <ul style="list-style-type: none"> Solar inverter UPS </div> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; margin: 0;">Types</p> <ul style="list-style-type: none"> 10-FZ12NMA080NS03-M260F38 10-PZ12NMA080NS03-M260F38Y </div>	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <p style="text-align: center; margin: 0;"><i>flow</i> 0 12 mm housing</p> <div style="display: flex; justify-content: space-around; align-items: center;"> </div> <div style="display: flex; justify-content: space-around; margin-top: 5px;"> solder pins press-fit pins </div> </div> <div style="border: 1px solid black; padding: 5px;"> <p style="text-align: center; margin: 0;">Schematic</p> </div>

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Boost Switch				
Collector-emitter voltage	V_{CES}		600	V
Collector current	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	64	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	225	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	101	W
Gate-emitter voltage	V_{GES}		±20	V
Short circuit ratings	t_{SC} V_{CC}	$T_j \leq 150\text{ °C}$ $V_{GE} = 15\text{ V}$	6 360	µs V
Maximum Junction Temperature	T_{jmax}		175	°C



Vincotech

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Boost Diode				
Peak Repetitive Reverse Voltage	V_{RRM}		1200	V
Continuous (direct) forward current	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	61	A
Repetitive peak forward current	I_{FRM}		100	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	111	W
Maximum Junction Temperature	T_{jmax}		175	°C
Buck Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	80	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	400	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	181	W
Gate-emitter voltage	V_{GES}		±20	V
Short circuit ratings	t_{SC}	$T_j \leq 150\text{ °C}$	10	µs
	V_{CC}	$V_{GE} = 15\text{ V}$	500	V
Maximum junction temperature	T_{jmax}		175	°C
Buck Diode				
Peak repetitive reverse voltage	V_{RRM}		600	V
Continuous (direct) forward current	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	33	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	58	W
Maximum junction temperature	T_{jmax}		175	°C



Vincotech

10-FZ12NMA080NS03-M260F38
10-PZ12NMA080NS03-M260F38Y
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
-----------	--------	-----------	-------	------

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...(T _{jmax} - 25)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
		AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			>12,7	mm
Clearance		with press-fit pins / with solder pins	9 / 9,15	mm
Comparative Tracking Index	CTI		>200	

*100% tested in production



Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
		V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	I_D [A]	T_j [°C]	Min	Typ	Max	

Boost Switch

Static

Parameter	Symbol	Conditions	V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	I_D [A]	T_j [°C]	Min	Typ	Max	Unit
Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{GE} = V_{CE}$				0,0012	25	5	5,8	6,5	V
Collector-emitter saturation voltage	V_{CEsat}		15			75	25 125 150	1,05	1,45 1,59 1,64	1,85	V
Collector-emitter cut-off current	I_{CES}		0	600			25			100	μA
Gate-emitter leakage current	I_{GES}		20	0			25			600	nA
Internal gate resistance	r_g								none		Ω
Input capacitance	C_{ies}								4620		pF
Output capacitance	C_{oes}	$f=1$ MHz	0	25		25			288		
Reverse transfer capacitance	C_{res}								137		
Gate charge	Q_g		15	480	75		25		470		nC

Thermal

Parameter	Symbol	Conditions	V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	I_D [A]	T_j [°C]	Min	Typ	Max	Unit
Thermal resistance junction to sink	$R_{th(j-s)}$	phase-change material $\lambda = 3,4$ W/mK							0,94		K/W

Dynamic

Parameter	Symbol	Conditions	V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	I_D [A]	T_j [°C]	Min	Typ	Max	Unit
Turn-on delay time	$t_{d(on)}$	$R_{goff} = 4 \Omega$ $R_{gon} = 4 \Omega$					25 125		84 85		ns
Rise time	t_r						25 125		11 12		
Turn-off delay time	$t_{d(off)}$						25 125		177 205		
Fall time	t_f						25 125		87 105		
Turn-on energy (per pulse)	E_{on}	$Q_{FWD} = 5,3 \mu C$ $Q_{FWD} = 8,2 \mu C$					25 125		0,528 0,747		mWs
Turn-off energy (per pulse)	E_{off}						25 125		1,860 2,500		



Vincotech

10-FZ12NMA080NS03-M260F38
10-PZ12NMA080NS03-M260F38Y
 datasheet

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
		V_{GE} [V]	V_{CE} [V]	I_C [A]	T_j [°C]	Min	Typ	Max		

Boost Diode

Static

Parameter	Symbol	V_{GE} [V]	V_{CE} [V]	I_C [A]	T_j [°C]	Min	Typ	Max	Unit
Forward voltage	V_F			50	25 125 150		1,73 1,70 1,68	2,05	V
Reverse leakage current	I_r		1200		25			10	μA

Thermal

Parameter	Symbol	Conditions	Value	Unit
Thermal resistance junction to sink	$R_{th(j-s)}$	phase-change material $\lambda = 3,4$ W/mK	0,86	K/W

Dynamic

Parameter	Symbol	dI/dt	V_{CE}	I_C	T_j	Min	Typ	Max	Unit
Peak recovery current	I_{RRM}	$dI/dt = 6090$ A/μs $dI/dt = 5325$ A/μs	±15	350	55	25	106		A
Reverse recovery time	t_{rr}					125	118		
						25	102		
Recovered charge	Q_r					125	148		
						25	5,316		μC
Reverse recovered energy	E_{rec}					125	8,219		
		25	1,551		mWs				
Peak rate of fall of recovery current	$(di_{rf}/dt)_{max}$	125	2,418						
		25	6904		A/μs				
		125	4951						



Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
		V_{GE} [V]	V_{CE} [V]	I_C [A]	T_j [°C]	Min	Typ	Max		

Buck Switch

Static

Parameter	Symbol	$V_{GE} = V_{CE}$	V_{GS} [V]	V_{DS} [V]	I_D [A]	T_j [°C]	Min	Typ	Max	Unit
Gate-emitter threshold voltage	$V_{GE(th)}$				0,0008	25	4,5	5,5	6,5	V
Collector-emitter saturation voltage	V_{CESat}		15		80	25 125 150		2,08 2,19 2,22	2,4	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			800	μA
Gate-emitter leakage current	I_{GES}		20	0		25			400	nA
Internal gate resistance	r_g							none		Ω
Input capacitance	C_{ies}							14770		pF
Output capacitance	C_{oes}	$f = 1$ Mhz	0	20		25		460		
Reverse transfer capacitance	C_{res}							280		

Thermal

Parameter	Symbol	Material	λ [W/mK]	Unit
Thermal resistance junction to sink	$R_{th(j-s)}$	phase-change material	λ = 3,4 W/mK	K/W

Dynamic

Parameter	Symbol	R_{gon}	R_{goff}	I_C [A]	V_{CE} [V]	T_j [°C]	Min	Typ	Max	Unit
Turn-on delay time	$t_{d(on)}$	±15	350	56		25		113		ns
Rise time	t_r						25	15		
							125	17		
							150	18		
Turn-off delay time	$t_{d(off)}$						25	128		
Fall time	t_f						125	149		
		150	155							
		25	28							
Turn-on energy (per pulse)	E_{on}	125	45							
		150	46							
		25	0,412							
Turn-off energy (per pulse)	E_{off}	125	0,675							
		150	0,761							
		25	0,730							
		125	1,364							
		150	1,586							



Vincotech

10-FZ12NMA080NS03-M260F38
10-PZ12NMA080NS03-M260F38Y
 datasheet

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
		V_{GE} [V]	V_{CE} [V]	I_C [A]	T_j [°C]	Min	Typ	Max		

Buck Diode

Static

Forward voltage	V_F				50	25 125		1,99 2,16	2,7	V
-----------------	-------	--	--	--	----	-----------	--	--------------	-----	---

Thermal

Thermal resistance junction to sink	$R_{th(j-s)}$	phase-change material $\lambda = 3,4$ W/mK						1,65		K/W
-------------------------------------	---------------	---	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}					25 125 150		72 74 75		A
Reverse recovery time	t_{rr}					25 125 150		40 79 93		ns
Recovered charge	Q_r	$di/dt = 4594$ A/ μ s $di/dt = 4470$ A/ μ s $di/dt = 3885$ A/ μ s	± 15	350	56	25 125 150		1,458 2,329 2,776		μ C
Reverse recovered energy	E_{rec}					25 125 150		0,324 0,525 0,635		mWs
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$					25 125 150		5066 3825 3590		A/ μ s


Thermistor

Rated resistance	R					25		22		k Ω
Deviation of R_{100}	$\Delta_{R/R}$	$R_{100} = 1486 \Omega$				100	-12		+14	%
Power dissipation	P					25		200		mW
Power dissipation constant						25		2		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 3\%$				25		3950		K
B-value	$B_{(25/100)}$	Tol. $\pm 3\%$				25		3998		K
Vincotech NTC Reference									B	




Boost Switch Characteristics

figure 1. IGBT
Typical output characteristics




$t_p = 250 \mu\text{s}$
 $V_{GE} = 15 \text{ V}$
 $T_j: 25 \text{ }^\circ\text{C}$ (dotted blue)
 $125 \text{ }^\circ\text{C}$ (solid black)
 $150 \text{ }^\circ\text{C}$ (dashed red)

figure 2. IGBT
Typical output characteristics




$t_p = 250 \mu\text{s}$
 $T_j = 150 \text{ }^\circ\text{C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT
Typical transfer characteristics



$t_p = 100 \mu\text{s}$
 $V_{CE} = 10 \text{ V}$
 $T_j: 25 \text{ }^\circ\text{C}$ (dotted blue)
 $125 \text{ }^\circ\text{C}$ (solid black)
 $150 \text{ }^\circ\text{C}$ (dashed red)

figure 4. IGBT
Transient Thermal Impedance as function of Pulse duration



$D = t_p / T$
 $R_{th(j-s)} = 0,94 \text{ K/W}$
 IGBT thermal model values

R (K/W)	τ (s)
8,42E-02	4,56E+00
2,89E-01	4,19E-01
4,35E-01	7,20E-02
8,50E-02	2,19E-02
4,67E-02	1,33E-03




Boost Switch Characteristics

figure 5. IGBT

Gate voltage vs Gate charge

$V_{GE} = f(Q_G)$




At
 $I_C = 75 \text{ A}$

figure 6. IGBT

Safe operating area

$I_C = f(V_{CE})$




At
 $D =$ single pulse
 $T_s = 80 \text{ }^\circ\text{C}$
 $V_{GE} = \pm 15 \text{ V}$
 $T_j = T_{jmax}$

figure 7. IGBT

Short circuit duration as a function of

$t_{pSC} = f(V_{GE})$




At
 $V_{CE} = 600 \text{ V}$
 $T_j \leq 175 \text{ }^\circ\text{C}$

figure 8. IGBT

Typical short circuit current as a function of

$I_{SC} = f(V_{GE})$



At
 $V_{CE} \leq 600 \text{ V}$
 $T_j \leq 175 \text{ }^\circ\text{C}$




Boost Diode Characteristics

figure 1. FWD

Typical forward characteristics

$$I_F = f(V_F)$$




$t_p = 250 \mu s$

T_j : 25 °C (blue dotted line)
 125 °C (black solid line)
 150 °C (red dashed line)

figure 2. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$

$R_{th(j-s)} = 0,86 \text{ K/W}$

FWD thermal model values

R (K/W)	τ (s)
3,99E-02	4,72E+00
9,06E-02	7,70E-01
3,15E-01	1,07E-01
2,60E-01	3,37E-02
9,39E-02	5,79E-03
5,83E-02	4,95E-04



Buck Switch Characteristics

figure 1. IGBT




figure 2. IGBT




figure 3. IGBT





figure 4. IGBT






Buck Switch Characteristics

figure 6. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



- $D =$ single pulse
- $T_s =$ 80 °C
- $V_{GE} =$ ± 15 V
- $T_j =$ T_{jmax}




Buck Diode Characteristics

figure 1. FWD

Typical forward characteristics

$$I_F = f(V_F)$$




$t_p = 250 \mu s$
 T_j : 25 °C
 125 °C ———
 150 °C - - - -

figure 2. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 1,65 \text{ K/W}$
 FWD thermal model values

R (K/W)	τ (s)
1,38E-01	2,78E+00
3,51E-01	3,25E-01
7,90E-01	6,26E-02
1,62E-01	3,53E-02
2,07E-01	2,89E-03




Thermistor Characteristics

figure 1. Thermistor

**Typical NTC characteristic
as a function of temperature**

$$R = f(T)$$






Boost Switching Characteristics

figure 1. IGBT


Typical switching energy losses as a function of collector current



With an inductive load at
 $V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω
 $T_j: 25$ °C (dotted blue)
 125 °C (solid black)

figure 2. IGBT


Typical switching energy losses as a function of gate resistor



With an inductive load at
 $V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 55$ A
 $T_j: 25$ °C (dotted blue)
 125 °C (solid black)

figure 3. FWD


Typical reverse recovered energy loss as a function of collector current



With an inductive load at
 $V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω
 $T_j: 25$ °C (dotted blue)
 125 °C (solid black)

figure 4. FWD

Typical reverse recovered energy loss as a function of gate resistor



With an inductive load at
 $V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_C = 55$ A
 $T_j: 25$ °C (dotted blue)
 125 °C (solid black)




Vincotech

Boost Switching Characteristics

figure 5. IGBT

Typical switching times as a function of collector current

$$t = f(I_C)$$




With an inductive load at

$T_j =$	125	°C
$V_{CE} =$	350	V
$V_{GE} =$	±15	V
$R_{gon} =$	4	Ω
$R_{goff} =$	4	Ω

figure 6. IGBT

Typical switching times as a function of gate resistor

$$t = f(R_g)$$




With an inductive load at

$T_j =$	125	°C
$V_{CE} =$	350	V
$V_{GE} =$	±15	V
$I_C =$	55	A

figure 7. FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_C)$$




At	$V_{CE} =$	350	V	$T_j:$	25 °C
	$V_{GE} =$	±15	V		125 °C	————
	$R_{gon} =$	4	Ω			

figure 8. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor

$$t_{rr} = f(R_{gon})$$



At	$V_{CE} =$	350	V	$T_j:$	25 °C
	$V_{GE} =$	±15	V		125 °C	————
	$I_C =$	55	A			




Vincotech

Boost Switching Characteristics

figure 9. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$




At $V_{CE} = 350$ V $T_j: 25$ °C
 $V_{GE} = \pm 15$ V $T_j: 125$ °C ———
 $R_{gpn} = 4$ Ω

figure 10. FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gpn})$$




At $V_{CE} = 350$ V $T_j: 25$ °C
 $V_{GE} = \pm 15$ V $T_j: 125$ °C ———
 $I_c = 55$ A

figure 11. FWD

Typical peak reverse recovery current current as a function of collector current

$$I_{RM} = f(I_c)$$




At $V_{CE} = 350$ V $T_j: 25$ °C
 $V_{GE} = \pm 15$ V $T_j: 125$ °C ———
 $R_{gpn} = 4$ Ω

figure 12. FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gpn})$$




At $V_{CE} = 350$ V $T_j: 25$ °C
 $V_{GE} = \pm 15$ V $T_j: 125$ °C ———
 $I_c = 55$ A



Boost Switching Characteristics

figure 13. FWD


Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_{rr}/dt = f(I_c)$



At $V_{CE} = 350$ V $T_j = 25$ °C $R_{g(on)} = 4$ Ω

figure 14. FWD


Typical rate of fall of forward and reverse recovery current as a function of IGBT turn on gate resistor
 $di_f/dt, di_{rr}/dt = f(R_{g(on)})$



At $V_{CE} = 350$ V $V_{GE} = \pm 15$ V $I_c = 55$ A

figure 15. IGBT

Reverse bias safe operating area



At $T_j = 175$ °C $R_{g(on)} = 4$ Ω $R_{g(off)} = 4$ Ω




Boost Switching Definitions

General conditions


T_j	=	125 °C
R_{gon}	=	4 Ω
R_{goff}	=	4 Ω

figure 1. IGBT
 Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for Eoff)




$V_{CE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	350	V
$I_C(100\%) =$	56	A
$t_{doff} =$	0,205	μs
$t_{Eoff} =$	0,582	μs

figure 3. IGBT
 Turn-off Switching Waveforms & definition of t_f




$V_C(100\%) =$	350	V
$I_C(100\%) =$	56	A
$t_f =$	0,105	μs

figure 2. IGBT
 Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for Eon)



$V_{CE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	350	V
$I_C(100\%) =$	56	A
$t_{don} =$	0,085	μs
$t_{Eon} =$	0,157	μs

figure 4. IGBT
 Turn-on Switching Waveforms & definition of t_r



$V_C(100\%) =$	350	V
$I_C(100\%) =$	56	A
$t_r =$	0,012	μs




Vincotech

10-FZ12NMA080NS03-M260F38
10-PZ12NMA080NS03-M260F38Y
 datasheet


Boost Switching Characteristics

figure 5. IGBT




$P_{off}(100\%) = 19,56$ kW
 $E_{off}(100\%) = 2,50$ mJ
 $t_{Eoff} = 0,58$ μs

figure 6. IGBT



$P_{on}(100\%) = 19,56$ kW
 $E_{on}(100\%) = 0,75$ mJ
 $t_{Eon} = 0,16$ μs

figure 7. FWD




$V_d(100\%) = 350$ V
 $I_d(100\%) = 56$ A
 $I_{RRM}(100\%) = -118$ A
 $t_{tr} = 0,148$ μs



Vincotech


Boost Switching Characteristics

figure 8. FWD



I_d (100%) =	56	A
Q_{rr} (100%) =	8,22	μC
t_{Qrr} =	1,00	μs

figure 9. FWD




P_{rec} (100%) =	19,56	kW
E_{rec} (100%) =	2,42	mJ
t_{Erec} =	1,00	μs



Buck Switching Characteristics


figure 1. IGBT



With an inductive load at

$V_{CE} = 350$ V	$T_j: 25$ °C
$V_{GE} = \pm 15$ V	125 °C	————
$R_{gon} = 4$ Ω	150 °C	- - - -
$R_{goff} = 4$ Ω		


figure 2. IGBT



With an inductive load at

$V_{CE} = 350$ V	$T_j: 25$ °C
$V_{GE} = \pm 15$ V	125 °C	————
$I_c = 56$ A	150 °C	- - - -


figure 3. FWD



With an inductive load at

$V_{CE} = 350$ V	$T_j: 25$ °C
$V_{GE} = \pm 15$ V	125 °C	————
$R_{gon} = 4$ Ω	150 °C	- - - -

figure 4. FWD



With an inductive load at

$V_{CE} = 350$ V	$T_j: 25$ °C
$V_{GE} = \pm 15$ V	125 °C	————
$I_c = 56$ A	150 °C	- - - -




Vincotech

Buck Switching Characteristics

figure 5. IGBT

Typical switching times as a function of collector current

$$t = f(I_C)$$




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	350	V
$V_{GE} =$	±15	V
$R_{g(on)} =$	4	Ω
$R_{g(off)} =$	4	Ω

figure 6. IGBT

Typical switching times as a function of gate resistor

$$t = f(R_g)$$




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	350	V
$V_{GE} =$	±15	V
$I_C =$	56	A

figure 7. FWD

Typical reverse recovery time as a function of collector current

$$t_{rr} = f(I_C)$$




At	$V_{CE} =$	350	V	$T_j:$	25 °C
	$V_{GE} =$	±15	V		125 °C	————
	$R_{g(on)} =$	4	Ω		150 °C	- - - -

figure 8. FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor

$$t_{rr} = f(R_{g(on)})$$



At	$V_{CE} =$	350	V	$T_j:$	25 °C
	$V_{GE} =$	±15	V		125 °C	————
	$I_C =$	56	A		150 °C	- - - -




Vincotech

Buck Switching Characteristics

figure 9. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$




At $V_{CE} = 350$ V $T_j = 25$ °C
 $V_{GE} = \pm 15$ V $T_j = 125$ °C ———
 $R_{gpn} = 4$ Ω $T_j = 150$ °C - - - - -

figure 10. FWD

Typical recovered charge as a function of IGBT turn on gate resistor

$$Q_r = f(R_{gpn})$$




At $V_{CE} = 350$ V $T_j = 25$ °C
 $V_{GE} = \pm 15$ V $T_j = 125$ °C ———
 $I_c = 56$ A $T_j = 150$ °C - - - - -

figure 11. FWD

Typical peak reverse recovery current current as a function of collector current

$$I_{RM} = f(I_c)$$




At $V_{CE} = 350$ V $T_j = 25$ °C
 $V_{GE} = \pm 15$ V $T_j = 125$ °C ———
 $R_{gpn} = 4$ Ω $T_j = 150$ °C - - - - -

figure 12. FWD

Typical peak reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RM} = f(R_{gpn})$$



At $V_{CE} = 350$ V $T_j = 25$ °C
 $V_{GE} = \pm 15$ V $T_j = 125$ °C ———
 $I_c = 56$ A $T_j = 150$ °C - - - - -




Vincotech

Buck Switching Characteristics

figure 13. FWD


Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_{rr}/dt = f(I_c)$



At $V_{CE} = 350$ V $T_j = 25$ °C (blue dotted)
 $V_{GE} = \pm 15$ V $T_j = 125$ °C (black solid)
 $R_{gon} = 4$ Ω $T_j = 150$ °C (red dashed)

figure 14. FWD


Typical rate of fall of forward and reverse recovery current as a function of IGBT turn on gate resistor
 $di_f/dt, di_{rr}/dt = f(R_{gon})$



At $V_{CE} = 350$ V $T_j = 25$ °C (blue dotted)
 $V_{GE} = \pm 15$ V $T_j = 125$ °C (black solid)
 $I_c = 56$ A $T_j = 150$ °C (red dashed)

figure 15. IGBT

Reverse bias safe operating area
 $I_c = f(V_{CE})$



At $T_j = 175$ °C
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω



Vincotech


10-FZ12NMA080NS03-M260F38
10-PZ12NMA080NS03-M260F38Y
 datasheet

Buck Switching Definitions

General conditions


T_j	=	125 °C
R_{gon}	=	4 Ω
R_{goff}	=	4 Ω

figure 1. IGBT
 Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




$V_{CE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	350	V
$I_C(100\%) =$	56	A
$t_{doff} =$	0,149	μs
$t_{Eoff} =$	0,510	μs

figure 2. IGBT
 Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




$V_{CE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	350	V
$I_C(100\%) =$	56	A
$t_{don} =$	0,113	μs
$t_{Eon} =$	0,262	μs

figure 3. IGBT
 Turn-off Switching Waveforms & definition of t_f



$V_C(100\%) =$	350	V
$I_C(100\%) =$	56	A
$t_f =$	0,045	μs

figure 4. IGBT
 Turn-on Switching Waveforms & definition of t_r



$V_C(100\%) =$	350	V
$I_C(100\%) =$	56	A
$t_r =$	0,017	μs




Vincotech

10-FZ12NMA080NS03-M260F38
10-PZ12NMA080NS03-M260F38Y
 datasheet


Buck Switching Characteristics

figure 5. IGBT




$P_{off}(100\%) =$	19,59	kW
$E_{off}(100\%) =$	1,36	mJ
$t_{Eoff} =$	0,51	μs

figure 6. IGBT



$P_{on}(100\%) =$	19,59	kW
$E_{on}(100\%) =$	0,68	mJ
$t_{Eon} =$	0,26	μs

figure 7. FWD




$V_F(100\%) =$	350	V
$I_F(100\%) =$	56	A
$I_{RRM}(100\%) =$	-74	A
$t_{tr} =$	0,079	μs



Vincotech


Buck Switching Characteristics

figure 8. FWD



I_F (100%) =	56	A
Q_r (100%) =	2,33	μC
t_{Qr} =	0,16	μs

figure 9. FWD



P_{rec} (100%) =	19,59	kW
E_{rec} (100%) =	0,53	mJ
t_{Erec} =	0,16	μs



10-FZ12NMA080NS03-M260F38
10-PZ12NMA080NS03-M260F38Y
 datasheet

Vincotech

Ordering Code & Marking						
Version			Ordering Code			
without thermal paste 12 mm housing with solder pins			10-FZ12NMA080NS03-M260F38			
without thermal paste 12 mm housing with press-fit pins			10-PZ12NMA080NS03-M260F38Y			
Text	Name		Date code	UL & VIN	Lot	Serial
	NN-NNNNNNNNNNNNNN-TTTTTTVV		WWYY	UL VIN	LLLLL	SSSS
Datamatrix	Type&Ver	Lot number	Serial	Date code		
	TTTTTTVV	LLLLL	SSSS	WWYY		

Pin table			
Pin	X	Y	Function
1	33,6	0	S2
2	30,8	0	G2
3	22	0	-DC
4	19,2	0	-DC
5	10,1	0	GND
6	2,8	0	S4
7	0	0	G4
8	0	7,1	Line
9	0	9,9	Line
10	0	12,7	Line
11	0	15,5	Line
12	0	22,6	G3
13	2,8	22,6	S3
14	10,1	22,6	GND
15	19,2	22,6	+DC
16	22	22,6	+DC
17	30,8	22,6	G1
18	33,6	22,6	S1
19	33,6	14,8	NTC1
20	33,6	8,2	NTC2
21	Not assembled		
22	Not assembled		

Outline

center of press-fit pinhead
for connection parameter see the handling instruction

12,93 ±0,1
16,2 ±0,5


113
y
16,8
X

113
y
16,8
X

Tolerance of pinpositions ±0,5mm at the end of pins
Dimension of coordinate axis is only offset without tolerance



Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
T3, T4	IGBT	600 V	75 A	Boost Switch	
D1, D2	FWD	1200 V	50 A	Boost Diode	
T1, T2	IGBT	1200 V	80 A	Buck Switch	
D3, D4	FWD	600 V	50 A	Buck Diode	
NTC	Thermistor			Thermistor	



Vincotech

Packaging instruction			
Standard packaging quantity (SPQ) 135	>SPQ	Standard	<SPQ Sample

Handling instruction
Handling instructions for <i>flow 0</i> packages see vincotech.com website.

Package data
Package data for <i>flow 0</i> packages see vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
10-xZ12NMA080NS03-M260F38x-D1-14	29 Jun. 2017		

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Vincotech\(威科\)](#)