





flowMNPC 0		1200 V / 80 A	
Features <ul style="list-style-type: none">• mixed voltage component topology• neutral point clamped inverter• reactive power capability• low inductance layout		flow 0 12 mm housing 	
Target applications <ul style="list-style-type: none">• solar inverter• UPS		Schematic 	
Types <ul style="list-style-type: none">• 10-FZ12NMA080SH01-M260F			



Vincotech

10-FZ12NMA080SH01-M260F
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Buck Switch				
Collector-emitter voltage	V_{CES}		1200	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	76	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	240	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	186	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 800\text{ V}$ $T_j = 150\text{ °C}$	10	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Buck Diode

Peak repetitive reverse voltage	V_{RRM}		600	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	51	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	69	W
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$

Boost Switch

Collector-emitter voltage	V_{CES}		600	V
Collector current (DC current)	I_C	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	65	A
Repetitive peak collector current	I_{CRM}	t_p limited by T_{jmax}	225	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	101	W
Gate-emitter voltage	V_{GES}		± 20	V
Short circuit ratings	t_{SC}	$V_{GE} = 15\text{ V}$, $V_{CC} = 360\text{ V}$ $T_j = 150\text{ °C}$	6	μs
Maximum junction temperature	T_{jmax}		175	$^{\circ}\text{C}$



Vincotech

10-FZ12NMA080SH01-M260F
datasheet

Maximum Ratings

$T_j = 25\text{ °C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Boost Diode				
Peak repetitive reverse voltage	V_{RRM}		1200	V
Forward current (DC current)	I_F	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	53	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	100	A
Total power dissipation	P_{tot}	$T_j = T_{jmax}$ $T_s = 80\text{ °C}$	90	W
Maximum junction temperature	T_{jmax}		175	°C

Module Properties

Thermal Properties

Storage temperature	T_{stg}		-40...+125	°C
Operation temperature under switching condition	T_{jop}		-40...+($T_{jmax} - 25$)	°C

Isolation Properties

Isolation voltage	V_{isol}	DC Test Voltage* $t_p = 2\text{ s}$	6000	V
Isolation voltage	V_{isol}	AC Voltage $t_p = 1\text{ min}$	2500	V
Creepage distance			min. 12,7	mm
Clearance			9,15	mm
Comparative Tracking Index	CTI		> 200	

*100 % tested in production



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Buck Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,003	25	5,3	5,8	6,3	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		80	25 125	1,78	1,99 2,33	2,42 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	1200		25			10	μA
Gate-emitter leakage current	I_{GES}		20	0		25			240	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}							4660		pF
Output capacitance	C_{oes}	$f = 1$ Mhz	0	25		25		300		pF
Reverse transfer capacitance	C_{res}							260		pF
Gate charge	Q_g	$V_{CC} = 960$ V	15		80	25		370		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,51		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4$ Ω $R_{goff} = 4$ Ω	±15	350	56	25		77,6		ns
						125		78,8		
Rise time	t_r					25		13		
						125		15,4		
Turn-off delay time	$t_{d(off)}$					25		170,4		
						125		220,8		
Fall time	t_f					25		43,2		ns
						125		68,24		
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD} = 1,01$ μC $Q_{tFWD} = 2,74$ μC				25		0,473		mWs
						125		0,972		
Turn-off energy (per pulse)	E_{off}					25		1,28		mWs
						125		2,17		



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	V_{CE} [V]	T_j [°C]	Min	Typ	Max	

Buck Diode

Static

Forward voltage	V_F				60	25 125 150		2,27 1,68 1,58	2,8 ⁽¹⁾	V
Reverse leakage current	I_R	$V_r = 600$ V				25			10	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						1,38		K/W
--	---------------	------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt=4710$ A/μs $di/dt=4651$ A/μs	±15	350	56	25		64,27		A
						125		83,05		
Reverse recovery time	t_{rr}					25		28,7		
						125		73,13		
Recovered charge	Q_r					25		1,01		
		125		2,74						
Reverse recovered energy	E_{rec}	25		0,172						
		125		0,521						
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$	25		9597						
		125		3522						



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit
		V_{GE} [V] V_{GS} [V]	V_{CE} [V] V_{DS} [V] V_F [V]	I_C [A] I_D [A] I_F [A]	T_j [°C]	Min	Typ	Max		

Boost Switch

Static

Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$			0,0012	25	5	5,8	6,5	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		75	25 125	1,05	1,44 1,59	1,85 ⁽¹⁾	V
Collector-emitter cut-off current	I_{CES}		0	600		25			3,8	µA
Gate-emitter leakage current	I_{GES}		20	0		25			600	nA
Internal gate resistance	r_g							None		Ω
Input capacitance	C_{ies}							4620		pF
Output capacitance	C_{oes}	$f = 1$ Mhz	0	25		25		288		pF
Reverse transfer capacitance	C_{res}							137		pF
Gate charge	Q_g	$V_{CC} = 480$ V	15		75	25		470		nC

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						0,94		K/W
--	---------------	---------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Turn-on delay time	$t_{d(on)}$	$R_{gon} = 4$ Ω $R_{goff} = 4$ Ω	±15	350	56	25		83,6		ns
						125		84,8		
Rise time	t_r					25		11		
						125		12,2		
Turn-off delay time	$t_{d(off)}$					25		177		
						125		204,6		
Fall time	t_f					25		86,45		ns
						125		105,19		
Turn-on energy (per pulse)	E_{on}	$Q_{tFWD} = 5,32$ µC $Q_{tFWD} = 8,22$ µC				25		0,528		mWs
						125		0,747		
Turn-off energy (per pulse)	E_{off}					25		1,86		mWs
						125		2,5		



Vincotech

Characteristic Values

Parameter	Symbol	Conditions						Values			Unit
		V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	V_{CE} [V]	I_D [A]	I_C [A]	T_j [°C]	Min	Typ	

Boost Diode

Static

Forward voltage	V_F				50	25 125 150	1,35	1,73 1,7 1,68	2,05 ⁽¹⁾	V
Reverse leakage current	I_R	$V_T = 1200$ V				25			10	μA

Thermal

Thermal resistance junction to sink ⁽²⁾	$R_{th(j-s)}$	$\lambda_{paste} = 3,4$ W/mK (PSX)						1,06		K/W
--	---------------	------------------------------------	--	--	--	--	--	------	--	-----

Dynamic

Peak recovery current	I_{RRM}	$di/dt=6090$ A/μs $di/dt=5325$ A/μs	±15	350	56	25		106,49		A
						125		117,83		
Reverse recovery time	t_{rr}					25		102,06		ns
						125		148,06		
Recovered charge	Q_r					25		5,32		μC
						125		8,22		
Reverse recovered energy	E_{rec}	25		1,55		mWs				
		125		2,42						
Peak rate of fall of recovery current	$(di_{rr}/dt)_{max}$	25		6904		A/μs				
		125		4951						



Vincotech

Characteristic Values

Parameter	Symbol	Conditions					Values			Unit	
		V_{GS} [V]	V_{GE} [V]	V_{DS} [V]	V_{CE} [V]	V_F [V]	I_D [A]	I_C [A]	I_F [A]		T_j [°C]

Thermistor

Static

Rated resistance	R					25		22		kΩ
Deviation of R_{100}	$A_{R/R}$	$R_{100} = 1486 \Omega$				100	-12		14	%
Power dissipation	P							200		mW
Power dissipation constant	d					25		2		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 3 \%$						3950		K
B-value	$B_{(25/100)}$	Tol. $\pm 3 \%$						3998		K
Vincotech Thermistor Reference									B	

⁽¹⁾ Value at chip level

⁽²⁾ Only valid with pre-applied Vincotech thermal interface material.




Buck Switch Characteristics

figure 1. IGBT

Typical output characteristics

$I_C = f(V_{CE})$




$t_p = 250 \mu s$
 $V_{GE} = 15 V$
 $T_j: 25^\circ C$ (blue), $125^\circ C$ (red)

figure 2. IGBT

Typical output characteristics

$I_C = f(V_{CE})$




$t_p = 250 \mu s$
 $T_j = 125^\circ C$
 V_{GE} from 7 V to 17 V in steps of 1 V

figure 3. IGBT

Typical transfer characteristics

$I_C = f(V_{GE})$




$t_p = 250 \mu s$
 $V_{CE} = 10 V$
 $T_j: 25^\circ C$ (blue), $125^\circ C$ (red)

figure 4. IGBT

Transient thermal impedance as a function of pulse width

$Z_{th(j-s)} = f(t_p)$



$D = t_p / T$
 $R_{th(j-s)} = 0,512 K/W$
IGBT thermal model values

R (K/W)	τ (s)
9,50E-02	1,05E+00
1,84E-01	1,66E-01
1,81E-01	6,37E-02
3,37E-02	7,18E-03
1,79E-02	6,47E-04




Vincotech

Buck Switch Characteristics

figure 5. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D =$ single pulse
 $T_s = 80$ °C
 $V_{CE} = 15$ V
 $T_j = T_{jmax}$



Buck Diode Characteristics

figure 6. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 7. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = \frac{t_p}{T}$
 $R_{th(j-s)} = 1,379 \text{ K/W}$
 FWD thermal model values

R (K/W)	τ (s)
8,16E-02	3,99E+00
2,02E-01	6,32E-01
7,09E-01	1,11E-01
2,16E-01	3,68E-02
9,74E-02	5,31E-03
7,28E-02	1,31E-03



Boost Switch Characteristics

figure 8. IGBT

Typical output characteristics
 $I_C = f(V_{CE})$




figure 9. IGBT

Typical output characteristics
 $I_C = f(V_{CE})$




figure 10. IGBT

Typical transfer characteristics
 $I_C = f(V_{GE})$





figure 11. IGBT

Transient thermal impedance as a function of pulse width
 $Z_{th(j-s)} = f(t_p)$



IGBT thermal model values

R (K/W)	τ (s)
8,42E-02	4,56E+00
2,89E-01	4,19E-01
4,35E-01	7,20E-02
8,50E-02	2,19E-02
4,67E-02	1,33E-03




Vincotech

Boost Switch Characteristics

figure 12. IGBT

Safe operating area

$$I_C = f(V_{CE})$$



$D =$ single pulse
 $T_s = 80 \text{ } ^\circ\text{C}$
 $V_{GE} = 15 \text{ V}$
 $T_j = T_{jmax}$



Boost Diode Characteristics

figure 13. FWD

Typical forward characteristics

$$I_F = f(V_F)$$





figure 14. FWD

Transient thermal impedance as a function of pulse width

$$Z_{th(j-s)} = f(t_p)$$



$D = t_p / T$
 $R_{th(j-s)} = 1,061 \text{ K/W}$
 FWD thermal model values

R (K/W)	τ (s)
4,19E-02	4,68E+00
8,50E-02	8,80E-01
4,99E-01	1,21E-01
2,83E-01	4,12E-02
9,28E-02	6,53E-03
5,92E-02	6,76E-04




Thermistor Characteristics

figure 15. Thermistor

Typical NTC characteristic as function of temperature

$$R_T = f(T)$$






Buck Switching Characteristics

figure 16. IGBT

Typical switching energy losses as a function of collector current
 $E = f(I_c)$




With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω
 $R_{goff} = 4$ Ω

T_j : — 25 °C
— 125 °C

figure 17. IGBT

Typical switching energy losses as a function of gate resistor
 $E = f(R_g)$




With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 56$ A

T_j : — 25 °C
— 125 °C

figure 18. FWD

Typical reverse recovered energy loss as a function of collector current
 $E_{rec} = f(I_c)$




With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 4$ Ω

T_j : — 25 °C
— 125 °C

figure 19. FWD

Typical reverse recovered energy loss as a function of gate resistor
 $E_{rec} = f(R_g)$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 56$ A


T_j : — 25 °C
— 125 °C



Buck Switching Characteristics

figure 20. IGBT


Typical switching times as a function of collector current
 $t = f(I_c)$



With an inductive load at
 $T_j = 125 \text{ } ^\circ\text{C}$
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{g(on)} = 4 \text{ } \Omega$
 $R_{g(off)} = 4 \text{ } \Omega$

figure 21. IGBT


Typical switching times as a function of gate resistor
 $t = f(R_g)$



With an inductive load at
 $T_j = 125 \text{ } ^\circ\text{C}$
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 56 \text{ A}$

figure 22. FWD


Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{g(on)} = 4 \text{ } \Omega$
 $T_j: \text{ — } 25 \text{ } ^\circ\text{C}$
 $\text{ — } 125 \text{ } ^\circ\text{C}$

figure 23. FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor
 $t_{rr} = f(R_{g(off)})$



With an inductive load at
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 56 \text{ A}$
 $T_j: \text{ — } 25 \text{ } ^\circ\text{C}$
 $\text{ — } 125 \text{ } ^\circ\text{C}$




Buck Switching Characteristics

figure 24. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 4$ Ω

T_j : — 25 °C
— 125 °C

figure 25. FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 56$ A

T_j : — 25 °C
— 125 °C

figure 26. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 4$ Ω

T_j : — 25 °C
— 125 °C

figure 27. FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 56$ A


T_j : — 25 °C
— 125 °C



Buck Switching Characteristics

figure 28. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_f/dt, di_{rr}/dt = f(I_C)$




With an inductive load at
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{goff} = 4 \text{ } \Omega$

T_j : — 25 °C
 — 125 °C

figure 29. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_f/dt, di_{rr}/dt = f(R_{goff})$




With an inductive load at
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_C = 56 \text{ A}$

T_j : — 25 °C
 — 125 °C

figure 30. IGBT

Reverse bias safe operating area
 $I_C = f(V_{CE})$




At $T_j = 125 \text{ } ^\circ\text{C}$
 $R_{goff} = 4 \text{ } \Omega$
 $R_{goff} = 4 \text{ } \Omega$



Boost Switching Characteristics

figure 31. IGBT

Typical switching energy losses as a function of collector current
 $E = f(I_c)$




With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \ \Omega$
 $R_{goff} = 4 \ \Omega$

T_j : — 25 °C
 — 125 °C

figure 32. IGBT

Typical switching energy losses as a function of gate resistor
 $E = f(R_g)$




With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 56 \text{ A}$

T_j : — 25 °C
 — 125 °C

figure 33. FWD

Typical reverse recovered energy loss as a function of collector current
 $E_{rec} = f(I_c)$




With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 4 \ \Omega$

T_j : — 25 °C
 — 125 °C

figure 34. FWD

Typical reverse recovered energy loss as a function of gate resistor
 $E_{rec} = f(R_g)$



With an inductive load at

$V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 56 \text{ A}$


T_j : — 25 °C
 — 125 °C



Boost Switching Characteristics

figure 35. IGBT


Typical switching times as a function of collector current
 $t = f(I_c)$



With an inductive load at
 $T_j = 125 \text{ } ^\circ\text{C}$
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{g(on)} = 4 \text{ } \Omega$
 $R_{g(off)} = 4 \text{ } \Omega$

figure 36. IGBT


Typical switching times as a function of gate resistor
 $t = f(R_g)$



With an inductive load at
 $T_j = 125 \text{ } ^\circ\text{C}$
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 56 \text{ A}$

figure 37. FWD


Typical reverse recovery time as a function of collector current
 $t_{rr} = f(I_c)$



With an inductive load at
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{g(on)} = 4 \text{ } \Omega$
 $T_j: \text{ — } 25 \text{ } ^\circ\text{C}$
 $\text{ — } 125 \text{ } ^\circ\text{C}$

figure 38. FWD

Typical reverse recovery time as a function of IGBT turn off gate resistor
 $t_{rr} = f(R_{g(off)})$



With an inductive load at
 $V_{CE} = 350 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $I_c = 56 \text{ A}$
 $T_j: \text{ — } 25 \text{ } ^\circ\text{C}$
 $\text{ — } 125 \text{ } ^\circ\text{C}$




Boost Switching Characteristics

figure 39. FWD

Typical recovered charge as a function of collector current

$$Q_r = f(I_c)$$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 4$ Ω

T_j : — 25 °C
— 125 °C

figure 40. FWD

Typical recovered charge as a function of turn off gate resistor

$$Q_r = f(R_{goff})$$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 56$ A

T_j : — 25 °C
— 125 °C

figure 41. FWD

Typical peak reverse recovery current as a function of collector current

$$I_{RM} = f(I_c)$$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 4$ Ω

T_j : — 25 °C
— 125 °C

figure 42. FWD

Typical peak reverse recovery current as a function of turn off gate resistor

$$I_{RM} = f(R_{goff})$$



With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 56$ A


T_j : — 25 °C
— 125 °C



Boost Switching Characteristics

figure 43. FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current
 $di_i/dt, di_r/dt = f(I_c)$




With an inductive load at

$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $R_{goff} = 4$ Ω

T_j : — 25 °C
 — 125 °C

figure 44. FWD

Typical rate of fall of forward and reverse recovery current as a function of turn off gate resistor
 $di_i/dt, di_r/dt = f(R_{goff})$



With an inductive load at


$V_{CE} = 350$ V
 $V_{GE} = \pm 15$ V
 $I_c = 56$ A

T_j : — 25 °C
 — 125 °C

figure 45. IGBT

Reverse bias safe operating area

$I_c = f(V_{CE})$



At $T_j = 125$ °C
 $R_{goff} = 4$ Ω
 $R_{goff} = 4$ Ω



Switching Definitions

figure 46. IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff} (t_{Eoff} = integrating time for E_{off})




figure 47. IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon} (t_{Eon} = integrating time for E_{on})




figure 48. IGBT

Turn-off Switching Waveforms & definition of t_f





figure 49. IGBT

Turn-on Switching Waveforms & definition of t_r





Switching Definitions

figure 50. FWD

Turn-off Switching Waveforms & definition of t_{rr}





figure 51. FWD

Turn-on Switching Waveforms & definition of t_{Qr} (t_{Qr} = integrating time for Q_r)





Vincotech


10-FZ12NMA080SH01-M260F
datasheet

Ordering Code	
Version	Ordering Code
Without thermal paste	10-FZ12NMA080SH01-M260F
With thermal paste (5,2 W/mK, PTM6000HV)	10-FZ12NMA080SH01-M260F-/7/
With thermal paste (3,4 W/mK, PSX-P7)	10-FZ12NMA080SH01-M260F-/3/

Marking						
	Text	Name NN-NNNNNNNNNNNNNN- TTTTTVV	Date code WWYY	UL & VIN UL VIN	Lot LLLLL	Serial SSSS
	Datamatrix	Type&Ver TTTTTVV	Lot number LLLLL	Serial SSSS	Date code WWYY	

Outline


Pin table [mm]			
Pin	X	Y	Function
1	33,6	0	S2
2	30,8	0	G2
3	22	0	-DC
4	19,2	0	-DC
5	10,1	0	GND
6	2,8	0	S4
7	0	0	G4
8	0	7,1	Line
9	0	9,9	Line
10	0	12,7	Line
11	0	15,5	Line
12	0	22,6	G3
13	2,8	22,6	S3
14	10,1	22,6	GND
15	19,2	22,6	+DC
16	22	22,6	+DC
17	30,8	22,6	G1
18	33,6	22,6	S1
19	33,6	14,8	NTC1
20	33,6	8,2	NTC2
21	not assembled		
22	not assembled		



Tolerance of pinpositions: ±0,5mm at the end of pins
Dimension of coordinate axis is only offset without tolerance



Vincotech



Identification					
ID	Component	Voltage	Current	Function	Comment
T1, T2	IGBT	1200 V	80 A	Buck Switch	
D3, D4	FWD	600 V	60 A	Buck Diode	
T3, T4	IGBT	600 V	75 A	Boost Switch	
D1, D2	FWD	1200 V	50 A	Boost Diode	
NTC	Thermistor			Thermistor	




Packaging instruction				
Standard packaging quantity (SPQ) 135	>SPQ	Standard	<SPQ	Sample

Handling instruction
Handling instructions for <i>flow 0</i> packages see vincotech.com website.

Package data
Package data for <i>flow 0</i> packages see vincotech.com website.

Vincotech thermistor reference
See Vincotech thermistor reference table at vincotech.com website.

UL recognition and file number
This device is certified according to UL 1557 standard, UL file number E192116. For more information see vincotech.com website. 

Document No.:	Date:	Modification:	Pages
10-FZ12NMA080SH01-M260F-D11-14	11 Sep. 2021	New Datasheet format, module is unchanged Introduce Rth values with PSX-P7 TIM Separate datasheet for pressfit pin version	

DISCLAIMER

The information, specifications, procedures, methods and recommendations herein (together "information") are presented by Vincotech to reader in good faith, are believed to be accurate and reliable, but may well be incomplete and/or not applicable to all conditions or situations that may exist or occur. Vincotech reserves the right to make any changes without further notice to any products to improve reliability, function or design. No representation, guarantee or warranty is made to reader as to the accuracy, reliability or completeness of said information or that the application or use of any of the same will avoid hazards, accidents, losses, damages or injury of any kind to persons or property or that the same will not infringe third parties rights or give desired results. It is reader's sole responsibility to test and determine the suitability of the information and the product for reader's intended use.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Vincotech\(威科\)](#)