

## Aluminum Electrolytic Capacitors Axial Standard, High Voltage




Fig. 1

### QUICK REFERENCE DATA

| DESCRIPTION                                        | VALUE                                         |                                                         |
|----------------------------------------------------|-----------------------------------------------|---------------------------------------------------------|
| Nominal case sizes<br>( $\varnothing$ D x L in mm) | 8 x 18<br>to 10 x 25                          | 10 x 30<br>to 21 x 38                                   |
| Rated capacitance range, $C_R$                     | 6.8 $\mu$ F to 220 $\mu$ F                    |                                                         |
| Tolerance on $C_R$                                 | -10 % to +50 %                                |                                                         |
| Rated voltage range, $U_R$                         | 160 V to 450 V                                |                                                         |
| Category temperature range                         | -40 °C to +85 °C<br>(450 V: -25 °C to +85 °C) |                                                         |
| Endurance test at 85 °C                            | 2000 h                                        | 8000 h<br>(450 V: 5000 h)                               |
| Useful life at 85 °C                               | 5000 h                                        | 15 000 h<br>(450 V: 10 000 h)                           |
| Useful life at 40 °C                               | 1.4 x $I_R$<br>applied:<br>120 000 h          | 1.8 x $I_R$ applied:<br>240 000 h<br>(450 V: 160 000 h) |
| Shelf life at 0 V, 85 °C                           | 500 h                                         |                                                         |
| Based on sectional<br>specification                | IEC 60384-4 / EN130300                        |                                                         |
| Climatic category IEC 60068                        | 40 / 085 / 56 (450 V: 25 / 085 / 56)          |                                                         |

### FEATURES

- Useful life: 5000 h to 15 000 h at 85 °C
- High rated voltage: up to 450 V
- Taped versions up to case  $\varnothing$  15 mm x 30 mm available for automatic insertion
- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Axial leads, cylindrical aluminum case, insulated with a blue sleeve
- Mounting ring version not available in insulated form
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS  
COMPLIANT**

### APPLICATIONS

- General purpose, industrial, power supply, audio-video
- Smoothing, filtering, buffering at high voltages
- Boards with restricted mounting height, vibration, and shock resistant


### MARKING

The capacitors are marked (where possible) with the following information:

- Rated capacitance (in  $\mu$ F)
- Tolerance on rated capacitance, code letter in accordance with IEC 60062 (T for -10 % to +50 %)
- Rated voltage (in V)
- Upper category temperature (85 °C)
- Date code, in accordance with IEC 60062
- Code indicating factory of origin
- Name of manufacturer
- Negative terminal identification
- Series number (041, 042 or 043)


### SELECTION CHART FOR $C_R$ , $U_R$ , AND RELEVANT NOMINAL CASE SIZES ( $\varnothing$ D x L in mm)

| $C_R$<br>( $\mu$ F) | $U_R$ (V) |           |           |           |           |           |
|---------------------|-----------|-----------|-----------|-----------|-----------|-----------|
|                     | 160       | 250       | 350       | 385       | 400       | 450       |
| 6.8                 | -         | -         | 10 x 30   | 10 x 30   | 10 x 30   | 10 x 30   |
| 10                  | 8 x 18    | -         | 12.5 x 30 | 12.5 x 30 | 12.5 x 30 | 12.5 x 30 |
|                     | -         | 10 x 30   | -         | -         | -         | -         |
| 15                  | -         | 12.5 x 30 | 12.5 x 30 | 15 x 30   | 15 x 30   | 12.5 x 30 |
| 22                  | 10 x 25   | 12.5 x 30 | 15 x 30   | 18 x 30   | 18 x 30   | 15 x 30   |
|                     | 10 x 30   | -         | -         | -         | -         | -         |
| 33                  | 12.5 x 30 | 15 x 30   | 18 x 30   | 18 x 38   | 18 x 38   | 18 x 30   |
| 47                  | 15 x 30   | 18 x 30   | 18 x 38   | 18 x 38   | 18 x 38   | 18 x 38   |
| 68                  | 15 x 30   | 18 x 38   | 21 x 38   | 21 x 38   | 21 x 38   | 21 x 38   |
| 100                 | 18 x 30   | 21 x 38   | -         | -         | -         | -         |
| 150                 | 18 x 38   | -         | -         | -         | -         | -         |
| 220                 | 21 x 38   | -         | -         | -         | -         | -         |

**DIMENSIONS in millimeters AND AVAILABLE FORMS**


**Form BR:** Taped on reel  
Case  $\varnothing D \times L = 8 \text{ mm} \times 18 \text{ mm}$  to  $15 \text{ mm} \times 30 \text{ mm}$   
**Form BA:** Taped in box (ammopack)  
Case  $\varnothing D \times L = 8 \text{ mm} \times 18 \text{ mm}$  to  $10 \text{ mm} \times 25 \text{ mm}$

Fig. 2 - Forms BA and BR



**Form AA:** Axial in box  
Case  $\varnothing D \times L = 10 \text{ mm} \times 30 \text{ mm}$  to  $21 \text{ mm} \times 38 \text{ mm}$


Fig. 3 - Form AA

Table 1

| <b>AXIAL; DIMENSIONS in millimeters, MASS AND PACKAGING QUANTITIES</b> |              |                            |        |                               |                   |                   |             |                      |            |            |
|------------------------------------------------------------------------|--------------|----------------------------|--------|-------------------------------|-------------------|-------------------|-------------|----------------------|------------|------------|
| NOMINAL<br>CASE SIZE<br>$\varnothing D \times L$                       | CASE<br>CODE | AXIAL: FORM AA, BA, AND BR |        |                               |                   |                   | MASS<br>(g) | PACKAGING QUANTITIES |            |            |
|                                                                        |              | $\varnothing d$            | L      | $\varnothing D_{\text{max.}}$ | $L_{\text{max.}}$ | $F_{\text{min.}}$ |             | FORM<br>AA           | FORM<br>BA | FORM<br>BR |
| 8 x 18                                                                 | 5            | 0.8                        | -      | 8.5                           | 18.5              | 25                | ≈ 1.7       | -                    | 500        | 500        |
| 10 x 18                                                                | 6            | 0.8                        | -      | 10.5                          | 18.5              | 25                | ≈ 2.5       | -                    | 500        | 500        |
| 10 x 25                                                                | 7            | 0.8                        | -      | 10.5                          | 25.5              | 30                | ≈ 3.3       | -                    | 500        | 500        |
| 10 x 30                                                                | 00           | 0.8                        | 55 ± 1 | 10.5                          | 30.5              | 35                | ≈ 4.8       | 340                  | -          | 500        |
| 12.5 x 30                                                              | 01           | 0.8                        | 55 ± 1 | 13.0                          | 30.5              | 35                | ≈ 7.4       | 260                  | -          | 400        |
| 15 x 30                                                                | 02           | 0.8                        | 55 ± 1 | 15.5                          | 30.5              | 35                | ≈ 11.7      | 200                  | -          | 250        |
| 18 x 30                                                                | 03           | 0.8                        | 55 ± 1 | 18.5                          | 30.5              | 35                | ≈ 12.9      | 120                  | -          | -          |
| 18 x 38                                                                | 04           | 0.8                        | 34 ± 1 | 18.5                          | 39.5              | 44                | ≈ 19.0      | 125                  | -          | -          |
| 21 x 38                                                                | 05           | 0.8                        | 34 ± 1 | 21.5                          | 39.5              | 44                | ≈ 24.0      | 100                  | -          | -          |

**Note**

- For detailed tape dimensions please refer to packaging information: [www.vishay.com/doc?28361](http://www.vishay.com/doc?28361)



**Form MR:**  
Case  $\varnothing D \times L = 15 \text{ mm} \times 30 \text{ mm}$  to  $21 \text{ mm} \times 38 \text{ mm}$   
Especially for applications with severe shocks and vibrations




Fig. 4 - Mounting hole diagram and outline. **Form MR:** With mounting ring and pins

Table 2

| <b>MOUNTING RING; DIMENSIONS in millimeters, MASS AND PACKAGING QUANTITIES</b> |              |                        |                  |                               |                                |            |                   |             |                         |
|--------------------------------------------------------------------------------|--------------|------------------------|------------------|-------------------------------|--------------------------------|------------|-------------------|-------------|-------------------------|
| NOMINAL<br>CASE SIZE<br>$\varnothing D \times L$                               | CASE<br>CODE | MOUNTING RING: FORM MR |                  |                               |                                |            |                   | MASS<br>(g) | PACKAGING<br>QUANTITIES |
|                                                                                |              | $\varnothing d1$       | $\varnothing d2$ | $\varnothing D_{\text{max.}}$ | $\varnothing D2_{\text{max.}}$ | D3         | $L_{\text{max.}}$ |             |                         |
| 15 x 30                                                                        | 02           | 0.8                    | 1.0 + 0.4        | 15.5                          | 17.5                           | 16.5 ± 0.2 | 33                | ≈ 11.7      | 200                     |
| 18 x 30                                                                        | 03           | 0.8                    | 1.0 + 0.4        | 18.5                          | 19.5                           | 18.5 ± 0.2 | 33                | ≈ 12.9      | 240                     |
| 18 x 38                                                                        | 04           | 0.8                    | 1.0 + 0.4        | 18.5                          | 19.5                           | 18.5 ± 0.2 | 42                | ≈ 19.0      | 100                     |
| 21 x 38                                                                        | 05           | 0.8                    | 1.0 + 0.4        | 21.5                          | 22.5                           | 21.5 ± 0.2 | 42                | ≈ 24.0      | 100                     |



| ELECTRICAL DATA |                                                                                          |
|-----------------|------------------------------------------------------------------------------------------|
| SYMBOL          | DESCRIPTION                                                                              |
| $C_R$           | Rated capacitance at 100 Hz, tolerance -10 % to +50 %                                    |
| $I_R$           | Rated RMS ripple current at 100 Hz, 85 °C                                                |
| $I_{L1}$        | Max. leakage current after 1 min at $U_R$                                                |
| $I_{L5}$        | Max. leakage current after 5 min at $U_R$                                                |
| $\tan \delta$   | Max. dissipation factor at 100 Hz                                                        |
| ESR             | Equivalent series resistance at 100 Hz (calculated from $\tan \delta_{\max}$ and $C_R$ ) |
| Z               | Max. impedance at 10 kHz                                                                 |

**Note**

- Unless otherwise specified, all electrical values in Table 3 apply at  $T_{\text{amb}} = 20\text{ °C}$ ,  $P = 86\text{ kPa}$  to  $106\text{ kPa}$ ,  $RH = 45\text{ %}$  to  $75\text{ %}$ .

**ORDERING EXAMPLE**

Electrolytic capacitor 041 series

10  $\mu\text{F}$  / 250 V; -10 % / +50 %Nominal case size:  $\varnothing 10\text{ mm} \times 25\text{ mm}$ ; Form BA

Ordering code: MAL204133109E3

Former 12NC: 2222 041 33109

| ELECTRICAL DATA AND ORDERING INFORMATION |                                  |                                            |              |                                           |                                  |                                  |                 |                      |                    |                             |                         |                             |                            |                             |
|------------------------------------------|----------------------------------|--------------------------------------------|--------------|-------------------------------------------|----------------------------------|----------------------------------|-----------------|----------------------|--------------------|-----------------------------|-------------------------|-----------------------------|----------------------------|-----------------------------|
| U <sub>R</sub><br>(V)                    | C <sub>R</sub><br>100 Hz<br>(μF) | NOMINAL<br>CASE<br>SIZE<br>Ø D x L<br>(mm) | CASE<br>CODE | I <sub>R</sub><br>100 Hz<br>85 °C<br>(mA) | I <sub>L1</sub><br>1 min<br>(μA) | I <sub>L5</sub><br>5 min<br>(μA) | tan δ<br>100 Hz | ESR<br>100 Hz<br>(Ω) | Z<br>10 kHz<br>(Ω) | LIFE<br>CODE <sup>(1)</sup> | ORDERING CODE MAL2..... |                             |                            |                             |
|                                          |                                  |                                            |              |                                           |                                  |                                  |                 |                      |                    |                             | IN BOX<br>FORM AA       | TAPED<br>ON REEL<br>FORM BR | TAPED<br>IN BOX<br>FORM BA | MOUNTING<br>RING<br>FORM MR |
| 160                                      | 10                               | 8 x 18                                     | 5            | 70                                        | 68                               | 14                               | 0.15            | 24                   | 12                 | L1                          | -                       | 04121109E3                  | 04131109E3                 | -                           |
|                                          | 22                               | 10 x 25                                    | 7            | 150                                       | 130                              | 25                               | 0.15            | 11                   | 5.5                | L1                          | -                       | 04121229E3                  | 04131229E3                 | -                           |
|                                          | 22                               | 10 x 30                                    | 00           | 190                                       | 42                               | 25                               | 0.10            | 6.8                  | 5.5                | L2                          | 04211229E3              | 04221229E3                  | -                          | -                           |
|                                          | 33                               | 12.5 x 30                                  | 01           | 270                                       | 58                               | 36                               | 0.10            | 4.5                  | 3.1                | L2                          | 04211339E3              | 04221339E3                  | -                          | -                           |
|                                          | 47                               | 15 x 30                                    | 02           | 350                                       | 78                               | 49                               | 0.10            | 3.2                  | 2.1                | L2                          | 04211479E3              | 04221479E3                  | -                          | 04241479E3                  |
|                                          | 68                               | 15 x 30                                    | 02           | 420                                       | 110                              | 69                               | 0.10            | 2.2                  | 1.4                | L2                          | 04211689E3              | 04221689E3                  | -                          | 04241689E3                  |
|                                          | 100                              | 18 x 30                                    | 03           | 580                                       | 150                              | 100                              | 0.10            | 1.5                  | 1.0                | L2                          | 04211101E3              | -                           | -                          | 04241101E3                  |
|                                          | 150                              | 18 x 38                                    | 04           | 760                                       | 230                              | 150                              | 0.10            | 1.0                  | 0.7                | L2                          | 04311151E3              | -                           | -                          | 04341151E3                  |
|                                          | 220                              | 21 x 38                                    | 05           | 940                                       | 330                              | 220                              | 0.10            | 0.7                  | 0.5                | L2                          | 04311221E3              | -                           | -                          | 04341221E3                  |
| 250                                      | 10                               | 10 x 30                                    | 00           | 130                                       | 33                               | 19                               | 0.10            | 15                   | 11                 | L2                          | 04213109E3              | 04223109E3                  | -                          | -                           |
|                                          | 15                               | 12.5 x 30                                  | 01           | 180                                       | 44                               | 27                               | 0.10            | 10                   | 7.4                | L2                          | 04213159E3              | 04223159E3                  | -                          | -                           |
|                                          | 22                               | 12.5 x 30                                  | 01           | 220                                       | 60                               | 37                               | 0.10            | 6.8                  | 5.0                | L2                          | 04213229E3              | 04223229E3                  | -                          | -                           |
|                                          | 33                               | 15 x 30                                    | 02           | 290                                       | 84                               | 54                               | 0.10            | 4.5                  | 3.4                | L2                          | 04213339E3              | 04223339E3                  | -                          | 04243339E3                  |
|                                          | 47                               | 18 x 30                                    | 03           | 400                                       | 120                              | 75                               | 0.10            | 3.2                  | 2.3                | L2                          | 04213479E3              | -                           | -                          | 04243479E3                  |
|                                          | 68                               | 18 x 38                                    | 04           | 520                                       | 160                              | 110                              | 0.10            | 2.2                  | 1.7                | L2                          | 04313689E3              | -                           | -                          | 04343689E3                  |
|                                          | 100                              | 21 x 38                                    | 05           | 650                                       | 240                              | 150                              | 0.10            | 1.5                  | 1.1                | L2                          | 04313101E3              | -                           | -                          | 04343101E3                  |
| 350                                      | 6.8                              | 10 x 30                                    | 00           | 110                                       | 32                               | 18                               | 0.10            | 22                   | 14                 | L2                          | 04215688E3              | 04225688E3                  | -                          | -                           |
|                                          | 10                               | 12.5 x 30                                  | 01           | 150                                       | 42                               | 25                               | 0.10            | 15                   | 10                 | L2                          | 04215109E3              | 04225109E3                  | -                          | -                           |
|                                          | 15                               | 12.5 x 30                                  | 01           | 180                                       | 57                               | 36                               | 0.10            | 10                   | 6.7                | L2                          | 04215159E3              | 04225159E3                  | -                          | -                           |
|                                          | 22                               | 15 x 30                                    | 02           | 250                                       | 79                               | 50                               | 0.10            | 6.8                  | 4.5                | L2                          | 04215229E3              | 04225229E3                  | -                          | 04245229E3                  |
|                                          | 33                               | 18 x 30                                    | 03           | 350                                       | 110                              | 73                               | 0.10            | 4.5                  | 3.1                | L2                          | 04215339E3              | -                           | -                          | 04245339E3                  |
|                                          | 47                               | 18 x 38                                    | 04           | 450                                       | 160                              | 100                              | 0.10            | 3.2                  | 2.1                | L2                          | 04315479E3              | -                           | -                          | 04345479E3                  |
|                                          | 68                               | 21 x 38                                    | 05           | 560                                       | 220                              | 150                              | 0.10            | 2.2                  | 1.4                | L2                          | 04315689E3              | -                           | -                          | 04345689E3                  |
| 385                                      | 6.8                              | 10 x 30                                    | 00           | 110                                       | 34                               | 20                               | 0.10            | 22                   | 14                 | L2                          | 04218688E3              | 04228688E3                  | -                          | -                           |
|                                          | 10                               | 12.5 x 30                                  | 01           | 150                                       | 45                               | 27                               | 0.10            | 15                   | 10                 | L2                          | 04218109E3              | 04228109E3                  | -                          | -                           |
|                                          | 15                               | 15 x 30                                    | 02           | 210                                       | 62                               | 39                               | 0.10            | 10                   | 6.0                | L2                          | 04218159E3              | 04228159E3                  | -                          | 04248159E3                  |
|                                          | 22                               | 18 x 30                                    | 03           | 290                                       | 86                               | 55                               | 0.10            | 6.8                  | 4.1                | L2                          | 04218229E3              | -                           | -                          | 04248229E3                  |
|                                          | 33                               | 18 x 38                                    | 04           | 380                                       | 120                              | 80                               | 0.10            | 4.5                  | 2.7                | L2                          | 04318339E3              | -                           | -                          | 04348339E3                  |
|                                          | 47                               | 18 x 38                                    | 04           | 450                                       | 170                              | 110                              | 0.10            | 3.2                  | 2.1                | L2                          | 04318479E3              | -                           | -                          | 04348479E3                  |
|                                          | 68                               | 21 x 38                                    | 05           | 570                                       | 250                              | 160                              | 0.10            | 2.2                  | 1.4                | L2                          | 04318689E3              | -                           | -                          | 04348689E3                  |

**ELECTRICAL DATA AND ORDERING INFORMATION**

| U <sub>R</sub><br>(V) | C <sub>R</sub><br>100 Hz<br>(μF) | NOMINAL<br>CASE<br>SIZE<br>Ø D x L<br>(mm) | CASE<br>CODE | I <sub>R</sub><br>100 Hz<br>85 °C<br>(mA) | I <sub>L1</sub><br>1 min<br>(μA) | I <sub>L5</sub><br>5 min<br>(μA) | tan δ<br>100 Hz | ESR<br>100 Hz<br>(Ω) | Z<br>10 kHz<br>(Ω) | LIFE<br>CODE <sup>(1)</sup> | ORDERING CODE MAL2..... |                             |                            |                             |
|-----------------------|----------------------------------|--------------------------------------------|--------------|-------------------------------------------|----------------------------------|----------------------------------|-----------------|----------------------|--------------------|-----------------------------|-------------------------|-----------------------------|----------------------------|-----------------------------|
|                       |                                  |                                            |              |                                           |                                  |                                  |                 |                      |                    |                             | IN BOX<br>FORM AA       | TAPED<br>ON REEL<br>FORM BR | TAPED<br>IN BOX<br>FORM BA | MOUNTING<br>RING<br>FORM MR |
| 400                   | 6.8                              | 10 x 30                                    | 00           | 110                                       | 220                              | 110                              | 0.055           | 11.5                 | 7.3                | L2                          | 04216688E3              | 04226688E3                  | -                          | -                           |
|                       | 10                               | 12.5 x 30                                  | 01           | 150                                       | 240                              | 110                              | 0.055           | 7.5                  | 4.6                | L2                          | 04216109E3              | 04226109E3                  | -                          | -                           |
|                       | 15                               | 15 x 30                                    | 02           | 210                                       | 250                              | 110                              | 0.055           | 5.0                  | 3.1                | L2                          | 04216159E3              | 04226159E3                  | -                          | 04246159E3                  |
|                       | 22                               | 18 x 30                                    | 03           | 290                                       | 280                              | 120                              | 0.055           | 3.5                  | 2.1                | L2                          | 04216229E3              | -                           | -                          | 04246229E3                  |
|                       | 33                               | 18 x 38                                    | 04           | 380                                       | 320                              | 130                              | 0.055           | 2.3                  | 1.4                | L2                          | 04316339E3              | -                           | -                          | 04346339E3                  |
|                       | 47                               | 18 x 38                                    | 04           | 450                                       | 370                              | 140                              | 0.055           | 1.7                  | 1.1                | L2                          | 04316479E3              | -                           | -                          | 04346479E3                  |
|                       | 68                               | 21 x 38                                    | 05           | 560                                       | 440                              | 150                              | 0.055           | 1.2                  | 0.7                | L2                          | 04316689E3              | -                           | -                          | 04346689E3                  |
| 450                   | 6.8                              | 10 x 30                                    | 00           | 110                                       | 230                              | 110                              | 0.10            | 22                   | 14                 | L3                          | 04217688E3              | 04227688E3                  | -                          | -                           |
|                       | 10                               | 12.5 x 30                                  | 01           | 150                                       | 240                              | 110                              | 0.10            | 15                   | 10                 | L3                          | 04217109E3              | 04227109E3                  | -                          | -                           |
|                       | 15                               | 12.5 x 30                                  | 01           | 180                                       | 260                              | 110                              | 0.10            | 10                   | 6.0                | L3                          | 04217159E3              | 04227159E3                  | -                          | -                           |
|                       | 22                               | 15 x 30                                    | 02           | 240                                       | 290                              | 120                              | 0.10            | 6.8                  | 4.1                | L3                          | 04217229E3              | 04227229E3                  | -                          | 04247229E3                  |
|                       | 33                               | 18 x 30                                    | 03           | 350                                       | 330                              | 130                              | 0.10            | 4.5                  | 2.7                | L3                          | 04217339E3              | -                           | -                          | 04247339E3                  |
|                       | 47                               | 18 x 38                                    | 04           | 440                                       | 390                              | 140                              | 0.10            | 3.2                  | 2.1                | L3                          | 04317479E3              | -                           | -                          | 04347479E3                  |
|                       | 68                               | 21 x 38                                    | 05           | 550                                       | 460                              | 160                              | 0.10            | 2.2                  | 1.4                | L3                          | 04317689E3              | -                           | -                          | 04347689E3                  |

**Note**

(1) Determines the applicable row in the table "Endurance Test Duration and Useful Life"

**ADDITIONAL ELECTRICAL DATA**

| PARAMETER                          | CONDITIONS                                                                                                                                                                                                                                                                                                                                                                              | VALUE                                                                                                                                                                                                                                                                                   |               |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
|                                    |                                                                                                                                                                                                                                                                                                                                                                                         | AXIAL                                                                                                                                                                                                                                                                                   | MOUNTING RING |
| Voltage                            |                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                         |               |
| Surge voltage                      | $U_R = 160\text{ V to }250\text{ V}$                                                                                                                                                                                                                                                                                                                                                    | $U_s \leq 1.15 \times U_R$                                                                                                                                                                                                                                                              |               |
|                                    | $U_R = 350\text{ V to }450\text{ V}$                                                                                                                                                                                                                                                                                                                                                    | $U_s \leq 1.1 \times U_R$                                                                                                                                                                                                                                                               |               |
| Reverse voltage                    |                                                                                                                                                                                                                                                                                                                                                                                         | $U_{rev} \leq 1\text{ V}$                                                                                                                                                                                                                                                               |               |
| Current                            |                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                         |               |
| Leakage current                    | After 1 min:<br>case $\varnothing D \times L = 8\text{ mm} \times 18\text{ mm to }10\text{ mm} \times 25\text{ mm}$ :<br>$CV \leq 1000\text{ }\mu\text{C}$<br>$CV > 1000\text{ }\mu\text{C}$<br>case $\varnothing D \times L = 10\text{ mm} \times 30\text{ mm to }21\text{ mm} \times 38\text{ mm}$ :<br>$U_R = 160\text{ V to }385\text{ V}$<br>$U_R = 400\text{ V and }450\text{ V}$ | $I_{L1} \leq 0.05 C_R \times U_R \text{ or } 5\text{ }\mu\text{A}$ , whichever is greater<br>$I_{L1} \leq 0.03 C_R \times U_R + 20\text{ }\mu\text{A}$<br><br>$I_{L1} \leq 0.009 C_R \times U_R + 10\text{ }\mu\text{A}$<br>$I_{L1} \leq 0.009 C_R \times U_R + 200\text{ }\mu\text{A}$ |               |
|                                    | After 5 min:<br>$U_R = 160\text{ V to }385\text{ V}$ :<br>$CV \leq 1000\text{ }\mu\text{C}$<br>$CV > 1000\text{ }\mu\text{C}$<br>$U_R = 400\text{ V and }450\text{ V}$                                                                                                                                                                                                                  | $I_{L5} \leq 0.01 C_R \times U_R \text{ or } 1\text{ }\mu\text{A}$ , whichever is greater<br>$I_{L5} \leq 0.006 C_R \times U_R + 4\text{ }\mu\text{A}$<br>$I_{L5} \leq 0.002 C_R \times U_R + 100\text{ }\mu\text{A}$                                                                   |               |
| Inductance                         |                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                         |               |
| Equivalent series inductance (ESL) | Case $\varnothing D \times L\text{ mm}$ :                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                         |               |
|                                    | 8 x 18                                                                                                                                                                                                                                                                                                                                                                                  | Typ. 35 nH                                                                                                                                                                                                                                                                              | -             |
|                                    | 10 x 18                                                                                                                                                                                                                                                                                                                                                                                 | Typ. 69 nH                                                                                                                                                                                                                                                                              | -             |
|                                    | 10 x 25                                                                                                                                                                                                                                                                                                                                                                                 | Typ. 38 nH                                                                                                                                                                                                                                                                              | -             |
|                                    | 10 x 30                                                                                                                                                                                                                                                                                                                                                                                 | Typ. 38 nH                                                                                                                                                                                                                                                                              | -             |
|                                    | 12.5 x 30                                                                                                                                                                                                                                                                                                                                                                               | Typ. 46 nH                                                                                                                                                                                                                                                                              | -             |
|                                    | 15 x 30                                                                                                                                                                                                                                                                                                                                                                                 | Typ. 48 nH                                                                                                                                                                                                                                                                              | Typ. 39 nH    |
|                                    | 18 x 30                                                                                                                                                                                                                                                                                                                                                                                 | Typ. 50 nH                                                                                                                                                                                                                                                                              | Typ. 39 nH    |
|                                    | 18 x 38                                                                                                                                                                                                                                                                                                                                                                                 | Typ. 54 nH                                                                                                                                                                                                                                                                              | Typ. 39 nH    |
| 21 x 38                            | Typ. 59 nH                                                                                                                                                                                                                                                                                                                                                                              | Typ. 39 nH                                                                                                                                                                                                                                                                              |               |

## CAPACITANCE (C)




Fig. 5 - Typical multiplier of capacitance as a function of ambient temperature

## EQUIVALENT SERIES RESISTANCE (ESR)




Fig. 6 - Typical multiplier of ESR as a function of ambient temperature




Fig. 7 - Typical multiplier of ESR as a function of frequency


**IMPEDANCE (Z)**


Fig. 8 - Typical impedance of capacitance as a function of ambient temperature




Fig. 9 - Typical impedance as a function of frequency



Fig. 10 - Typical impedance as a function of frequency



Fig. 11 - Typical impedance as a function of frequency at different ambient temperatures

Curve 1: 10 μF, 350 V and 385 V; -40 °C  
Curve 2: 15 μF, 250 V; -40 °C  
Curve 3: 33 μF, 160 V; -40 °C  
Curve 4: 10 μF, 350 V and 385 V; 20 °C  
Curve 5: 15 μF, 250 V; 20 °C  
Curve 6: 33 μF, 160 V; 20 °C  
Curve 7: 10 μF, 350 V and 385 V; 85 °C  
Curve 8: 15 μF, 250 V; 85 °C  
Curve 9: 33 μF, 160 V; 85 °C

**RIPPLE CURRENT AND USEFUL LIFE**

Table 3

| ENDURANCE TEST DURATION AND USEFUL LIFE |                        |                          |
|-----------------------------------------|------------------------|--------------------------|
| LIFE CODE                               | ENDURANCE AT 85 °C (h) | USEFUL LIFE AT 85 °C (h) |
| L1                                      | 2000                   | 5000                     |
| L2                                      | 8000                   | 15 000                   |
| L3                                      | 5000                   | 10 000                   |

**Note**

- Multiplier of useful life code: CCC205




Fig. 12 - Multiplier of useful life as a function of ambient temperature and ripple current load

Table 4

| MULTIPLIER OF RIPPLE CURRENT ( $I_R$ ) AS A FUNCTION OF FREQUENCY |      |      |      |      |          |
|-------------------------------------------------------------------|------|------|------|------|----------|
| FREQUENCY (Hz)                                                    |      |      |      |      |          |
| 50                                                                | 100  | 300  | 1000 | 3000 | ≥ 10 000 |
| $I_R$ MULTIPLIER                                                  |      |      |      |      |          |
| 0.75                                                              | 1.00 | 1.15 | 1.30 | 1.40 | 1.50     |



Table 5

| TEST PROCEDURE REQUIREMENTS                    |                                             |                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                |
|------------------------------------------------|---------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TEST                                           |                                             | PROCEDURE<br>(quick reference)                                                                                                                                                                                     | REQUIREMENTS                                                                                                                                                                                                                                                                                                   |
| NAME OF TEST                                   | REFERENCE                                   |                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                |
| Endurance                                      | IEC 60384-4 /<br>EN130300<br>subclause 4.13 | $T_{amb} = 85\text{ }^{\circ}\text{C}$ ; $U_R$ applied;<br>Case $\varnothing D \times L$ :<br>8 mm x 18 mm to 10 mm x 25 mm:<br>2000 h;<br>10 mm x 30 mm to 21 mm x 38 mm:<br>8000 h (450 V: 5000 h)               | $U_R = 160\text{ V}$ ; $\Delta C/C$ : $\pm 15\%$<br>$U_R = 250\text{ V}$ to 450 V; $\Delta C/C$ : $\pm 10\%$<br>$\tan \delta \leq 1.3 \times \text{spec. limit}$<br>$Z \leq 2 \times \text{spec. limit}$<br>$I_{L5} \leq \text{spec. limit}$                                                                   |
| Useful life                                    | CECC 30301<br>subclause 1.8.1               | $T_{amb} = 85\text{ }^{\circ}\text{C}$ ; $U_R$ and $I_R$ applied;<br>Case $\varnothing D \times L$ :<br>8 mm x 18 mm to 10 mm x 25 mm:<br>5000 h;<br>10 mm x 30 mm to 21 mm x 38 mm:<br>15 000 h (450 V: 10 000 h) | $U_R = 160\text{ V}$ ; $\Delta C/C$ : $\pm 45\%$<br>$U_R = 250\text{ V}$ to 450 V; $\Delta C/C$ : $\pm 30\%$<br>$\tan \delta \leq 3 \times \text{spec. limit}$<br>$Z \leq 3 \times \text{spec. limit}$<br>$I_{L5} \leq \text{spec. limit}$<br>No short or open circuit<br>Total failure percentage: $\leq 3\%$ |
| Shelf life<br>(storage at high<br>temperature) | IEC 60384-4 /<br>EN130300<br>subclause 4.17 | $T_{amb} = 85\text{ }^{\circ}\text{C}$ ; no voltage applied;<br>500 h<br>After test: $U_R$ to be applied for 30 min,<br>24 h to 48 h before measurement                                                            | $\Delta C/C$ , $\tan \delta$ , $Z$ :<br>for requirements<br>see "Endurance test" above<br>$I_{L5} \leq 2 \times \text{spec. limit}$                                                                                                                                                                            |

Statements about product lifetime are based on calculations and internal testing. They should only be interpreted as estimations. Also due to external factors, the lifetime in the field application may deviate from the calculated lifetime. In general, nothing stated herein shall be construed as a guarantee of durability.



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Vishay\(威世\)](#)