





N- and P-Channel 12 V (D-S) MOSFET

| PRODUCT SUMMARY | | |
|---|---------------|-----------|
| | N-CHANNEL | P-CHANNEL |
| V_{DS} (V) | 12 | - 12 |
| $R_{DS(on)}$ (Ω) at $V_{GS} = \pm 4.5$ V | 0.040 | 0.070 |
| $R_{DS(on)}$ (Ω) at $V_{GS} = \pm 2.5$ V | 0.048 | 0.100 |
| $R_{DS(on)}$ (Ω) at $V_{GS} = \pm 1.8$ V | 0.063 | 0.140 |
| I_D (A) ^a | 4.5 | - 4.5 |
| Configuration | N- and P-Pair | |



FEATURES

- High Quality Manufacturing Process Using SMM Process Flow
- Halogen-free According to IEC 61249-2-21 Definition
- TrenchFET® Power MOSFETs
- New Thermally Enhanced PowerPAK® SC-70 Package
 - Small Footprint Area
 - Low On-Resistance
- Compliant to RoHS Directive 2002/95/EC
- Find out more about Vishay's Medical Products at: www.vishay.com/medical-mosfets



RoHS
COMPLIANT
HALOGEN
FREE

APPLICATION EXAMPLES

- Medical Implantable Applications Including
 - Drug Delivery Systems
 - Defibrillators
 - Pacemakers
 - Hearing Aids
 - Other Implantable Devices
- Load Switch for Portable Devices

ORDERING INFORMATION

| | |
|---------------------------------|------------------|
| Package | PowerPAK SC-70 |
| Lead (Pb)-free and Halogen-free | SMMA511DJ-T1-GE3 |

ABSOLUTE MAXIMUM RATINGS $T_A = 25$ °C, unless otherwise noted

| PARAMETER | SYMBOL | N-CHANNEL | P-CHANNEL | UNIT |
|--|----------------|----------------------------------|-----------|------|
| Drain-Source Voltage | V_{DS} | 12 | - 12 | V |
| Gate-Source Voltage | V_{GS} | ± 8 | ± 8 | |
| Continuous Drain Current ($T_J = 150$ °C) | I_D | $T_C = 25$ °C ^a | - 4.5 | A |
| | | $T_C = 70$ °C ^a | - 4.5 | |
| | | $T_A = 25$ °C ^{a, b, c} | - 4.3 | |
| | | $T_A = 70$ °C ^{a, b, c} | - 3.4 | |
| Pulsed Drain Current | I_{DM} | 20 | - 10 | |
| Continuous Source-Drain Diode Current | I_S | $T_C = 25$ °C ^a | - 4.5 | |
| | | $T_A = 25$ °C ^{b, c} | - 1.6 | |
| Maximum Power Dissipation | P_D | $T_C = 25$ °C | 6.5 | W |
| | | $T_C = 70$ °C | 5 | |
| | | $T_A = 25$ °C ^{a, c} | 1.9 | |
| | | $T_A = 70$ °C ^{a, c} | 1.2 | |
| Operating Junction and Storage Temperature Range | T_J, T_{stg} | - 55 to + 150 | | °C |
| Soldering Recommendations (Peak Temperature) ^{d, e} | | 260 | | |

THERMAL RESISTANCE RATINGS

| PARAMETER | SYMBOL | N-CHANNEL | | P-CHANNEL | | UNIT | |
|---|--------------|------------|------|-----------|------|------|------|
| | | TYP. | MAX. | TYP. | MAX. | | |
| Maximum Junction-to-Ambient ^{b, f} | $t \leq 5$ s | R_{thJA} | 52 | 65 | 52 | 65 | °C/W |
| Maximum Junction-to-Case (Drain) | Steady State | R_{thJC} | 12.5 | 16 | 12.5 | 16 | |

Notes

- Surface mounted on 1" x 1" FR4 board.
- Package limit is ± 4.5 A.
- $t = 5$ s.
- See Solder Profile (www.vishay.com/ppg?73257). The PowerPAK SC-70 is a leadless package. The end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solder interconnection.
- Rework conditions: manual soldering with a soldering iron is not recommended for leadless components.
- Maximum under steady state conditions is 110 °C/W.

SPECIFICATIONS $T_J = 25$ °C, unless otherwise noted

| PARAMETER | SYMBOL | TEST CONDITIONS | | MIN. | TYP. | MAX. | UNIT | |
|---|-------------------------|--|--|------|------|-------|-----------|----------|
| Static | | | | | | | | |
| Drain-Source Breakdown Voltage | V_{DS} | $V_{GS} = 0$ V, $I_D = 250$ μ A | | N-Ch | 12 | - | - | V |
| | | $V_{GS} = 0$ V, $I_D = -250$ μ A | | P-Ch | -12 | - | - | |
| V_{DS} Temperature Coefficient | $\Delta V_{DS}/T_J$ | $I_D = 250$ μ A | | N-Ch | - | 12 | - | mV/°C |
| | | $I_D = -250$ μ A | | P-Ch | - | -7 | - | |
| $V_{GS(th)}$ Temperature Coefficient | $\Delta V_{GS(th)}/T_J$ | $I_D = 250$ μ A | | N-Ch | - | -2.8 | - | mV/°C |
| | | $I_D = -250$ μ A | | P-Ch | - | 2.1 | - | |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{DS} = V_{GS}$, $I_D = 250$ μ A | | N-Ch | 0.4 | - | 1 | V |
| | | $V_{DS} = V_{GS}$, $I_D = -250$ μ A | | P-Ch | -0.4 | - | -1 | |
| Gate-Body Leakage | I_{GSS} | $V_{DS} = 0$ V, $V_{GS} = \pm 8$ V | | N-Ch | - | - | ± 100 | nA |
| | | | | P-Ch | - | - | ± 100 | |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{GS} = 0$ V | $V_{DS} = 12$ V | N-Ch | - | - | 1 | μ A |
| | | $V_{GS} = 0$ V | $V_{DS} = -12$ V | P-Ch | - | - | -1 | |
| | | $V_{GS} = 0$ V | $V_{DS} = 12$ V, $T_J = 55$ °C | N-Ch | - | - | 10 | |
| | | $V_{GS} = 0$ V | $V_{DS} = -12$ V, $T_J = 55$ °C | P-Ch | - | - | -10 | |
| On-State Drain Current ^a | $I_{D(on)}$ | $V_{GS} = 4.5$ V | $V_{DS} \geq 5$ V | N-Ch | 15 | - | - | A |
| | | $V_{GS} = -4.5$ V | $V_{DS} \leq -5$ V | P-Ch | -8 | - | - | |
| Drain-Source On-State Resistance ^a | $R_{DS(on)}$ | $V_{GS} = 4.5$ V | $I_D = 4.2$ A | N-Ch | - | 0.033 | 0.040 | Ω |
| | | $V_{GS} = -4.5$ V | $I_D = -3.3$ A | P-Ch | - | 0.058 | 0.070 | |
| | | $V_{GS} = 2.5$ V | $I_D = 3.8$ A | N-Ch | - | 0.039 | 0.048 | |
| | | $V_{GS} = -2.5$ V | $I_D = -2.8$ A | P-Ch | - | 0.082 | 0.100 | |
| | | $V_{GS} = 1.8$ V | $I_D = 1.6$ A | N-Ch | - | 0.051 | 0.063 | |
| | | $V_{GS} = -1.8$ V | $I_D = -0.7$ A | P-Ch | - | 0.111 | 0.140 | |
| Forward Transconductance ^a | g_{fs} | $V_{DS} = 10$ V, $I_D = 4.2$ A | | N-Ch | - | 13 | - | S |
| | | $V_{DS} = -10$ V, $I_D = -3.3$ A | | P-Ch | - | 9 | - | |
| Dynamic^b | | | | | | | | |
| Input Capacitance | C_{iss} | $V_{GS} = 0$ V | N-Channel $V_{DS} = 6$ V, $f = 1$ MHz | N-Ch | - | 400 | - | μ F |
| Output Capacitance | C_{oss} | | | P-Ch | - | 400 | - | |
| | | | | N-Ch | - | 120 | - | |
| Reverse Transfer Capacitance | C_{rss} | | | P-Ch | - | 140 | - | |
| | | | | N-Ch | - | 70 | - | |
| | | | | P-Ch | - | 100 | - | |









| SPECIFICATIONS $T_J = 25\text{ }^\circ\text{C}$, unless otherwise noted | | | | | | | |
|--|--------------|---|---|------|------|------|------|
| PARAMETER | SYMBOL | TEST CONDITIONS | | MIN. | TYP. | MAX. | UNIT |
| Dynamic^b | | | | | | | |
| Total Gate Charge | Q_g | $V_{GS} = 8\text{ V}$ | $V_{DS} = 6\text{ V}, I_D = 5.5\text{ A}$ | N-Ch | - | 7.5 | 12 |
| | | $V_{GS} = -8\text{ V}$ | $V_{DS} = -6\text{ V}, I_D = -4.3\text{ A}$ | P-Ch | - | 8 | 12 |
| | | $V_{GS} = 4.5\text{ V}$ | $V_{DS} = 6\text{ V}, I_D = 5.5\text{ A}$ | N-Ch | - | 4.5 | 6.8 |
| | | $V_{GS} = -4.5\text{ V}$ | | P-Ch | - | 5 | 7.5 |
| Gate-Source Charge | Q_{gs} | $V_{GS} = 4.5\text{ V}$ | $V_{DS} = 6\text{ V}, I_D = 5.5\text{ A}$ | N-Ch | - | 0.6 | - |
| | | $V_{GS} = -4.5\text{ V}$ | | P-Ch | - | 0.8 | - |
| Gate-Drain Charge | Q_{gd} | $V_{GS} = 4.5\text{ V}$ | $V_{DS} = -6\text{ V}, I_D = -4.3\text{ A}$ | N-Ch | - | 0.8 | - |
| | | $V_{GS} = -4.5\text{ V}$ | | P-Ch | - | 1.4 | - |
| Gate Resistance | R_g | $f = 1\text{ MHz}$ | | N-Ch | - | 2.5 | - |
| | | | | P-Ch | - | 7 | - |
| Turn-On Delay Time | $t_{d(on)}$ | N-Channel $V_{DD} = 6\text{ V}, R_L = 1.4\text{ }\Omega$ $I_D \cong 4.4\text{ A}, V_{GEN} = 4.5\text{ V}, R_g = 1\text{ }\Omega$ | | N-Ch | - | 5 | 10 |
| Rise Time | t_r | | | P-Ch | - | 15 | 25 |
| Turn-Off Delay Time | $t_{d(off)}$ | P-Channel $V_{DD} = -6\text{ V}, R_L = 1.8\text{ }\Omega$ $I_D \cong -3.4\text{ A}, V_{GEN} = -4.5\text{ V}, R_g = 1\text{ }\Omega$ | | N-Ch | - | 15 | 25 |
| | | | | P-Ch | - | 35 | 55 |
| Fall Time | t_f | | | N-Ch | - | 20 | 30 |
| | | | | P-Ch | - | 15 | 25 |
| Turn-On Delay Time | $t_{d(on)}$ | N-Channel $V_{DD} = 6\text{ V}, R_L = 1.4\text{ }\Omega$ $I_D \cong 4.4\text{ A}, V_{GEN} = 10\text{ V}, R_g = 1\text{ }\Omega$ | | N-Ch | - | 5 | 10 |
| | | | | P-Ch | - | 5 | 10 |
| Rise Time | t_r | | | N-Ch | - | 10 | 15 |
| | | | | P-Ch | - | 12 | 20 |
| Turn-Off Delay Time | $t_{d(off)}$ | P-Channel $V_{DD} = -6\text{ V}, R_L = 1.8\text{ }\Omega$ $I_D \cong -3.4\text{ A}, V_{GEN} = -10\text{ V}, R_g = 1\text{ }\Omega$ | | N-Ch | - | 15 | 25 |
| | | | | P-Ch | - | 20 | 30 |
| Fall Time | t_f | | | N-Ch | - | 10 | 15 |
| | | | | P-Ch | - | 10 | 15 |
| Source-Drain Body Diode Characteristics | | | | | | | |
| Continuous Source-Drain Diode Current | I_S | $T_C = 25\text{ }^\circ\text{C}$ | | N-Ch | - | - | 4.5 |
| | | | | P-Ch | - | - | -4.5 |
| Pulse Diode Forward Current | I_{SM} | | | N-Ch | - | - | 20 |
| | | | | P-Ch | - | - | -10 |
| Body Diode Voltage | V_{SD} | $V_{GS} = 0\text{ V}$ | $I_S = 4.4\text{ A}$ | N-Ch | - | 0.8 | 1.2 |
| | | | $I_S = -3.4\text{ A}$ | P-Ch | - | -0.8 | -1.2 |
| Body Diode Reverse Recovery Time | t_{rr} | | | N-Ch | - | 15 | 30 |
| | | | | P-Ch | - | 30 | 60 |
| Body Diode Reverse Recovery Charge | Q_{rr} | N-Channel $I_F = 4.4\text{ A}, di/dt = 100\text{ A}/\mu\text{s}, T_J = 25\text{ }^\circ\text{C}$ | | N-Ch | - | 8 | 20 |
| | | | | P-Ch | - | 12 | 24 |
| Reverse Recovery Fall Time | t_a | P-Channel $I_F = -3.4\text{ A}, di/dt = -100\text{ A}/\mu\text{s}, T_J = 25\text{ }^\circ\text{C}$ | | N-Ch | - | 8.5 | - |
| | | | | P-Ch | - | 14 | - |
| Reverse Recovery Rise Time | t_b | | | N-Ch | - | 8.5 | - |
| | | | | P-Ch | - | 16 | - |

Notes

- a. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.
b. Guaranteed by design, not subject to production testing.


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

N-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted







N-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage




Single Pulse Power, Junction-to-Ambient




* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified

Safe Operating Area, Junction-to-Ambient

N-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted



Current Derating*




Power Derating


* The power dissipation P_D is based on $T_{J(max.)} = 150\text{ }^\circ\text{C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.



N-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted




Normalized Thermal Transient Impedance, Junction-to-Ambient




Normalized Thermal Transient Impedance, Junction-to-Case




P-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current and Gate Voltage



Capacitance




Gate Charge




On-Resistance vs. Junction Temperature




P-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage




Single Pulse Power, Junction-to-Ambient




* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified

Safe Operating Area, Junction-to-Ambient

P-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted



Current Derating*




Power Derating


* The power dissipation P_D is based on $T_{J(max.)} = 150\text{ }^\circ\text{C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.



P-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted




Normalized Thermal Transient Impedance, Junction-to-Ambient



Normalized Thermal Transient Impedance, Junction-to-Case


Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?65281.

PowerPAK® SC70-6L



BACKSIDE VIEW OF SINGLE

BACKSIDE VIEW OF DUAL




Notes:

1. All dimensions are in millimeters
2. Package outline exclusive of mold flash and metal burr
3. Package outline inclusive of plating

| DIM | SINGLE PAD | | | | | | DUAL PAD | | | | | |
|-----|-------------|-------|-------|-----------|-------|-------|-------------|-------|-------|-----------|-------|-------|
| | MILLIMETERS | | | INCHES | | | MILLIMETERS | | | INCHES | | |
| | Min | Nom | Max | Min | Nom | Max | Min | Nom | Max | Min | Nom | Max |
| A | 0.675 | 0.75 | 0.80 | 0.027 | 0.030 | 0.032 | 0.675 | 0.75 | 0.80 | 0.027 | 0.030 | 0.032 |
| A1 | 0 | - | 0.05 | 0 | - | 0.002 | 0 | - | 0.05 | 0 | - | 0.002 |
| b | 0.23 | 0.30 | 0.38 | 0.009 | 0.012 | 0.015 | 0.23 | 0.30 | 0.38 | 0.009 | 0.012 | 0.015 |
| C | 0.15 | 0.20 | 0.25 | 0.006 | 0.008 | 0.010 | 0.15 | 0.20 | 0.25 | 0.006 | 0.008 | 0.010 |
| D | 1.98 | 2.05 | 2.15 | 0.078 | 0.081 | 0.085 | 1.98 | 2.05 | 2.15 | 0.078 | 0.081 | 0.085 |
| D1 | 0.85 | 0.95 | 1.05 | 0.033 | 0.037 | 0.041 | 0.513 | 0.613 | 0.713 | 0.020 | 0.024 | 0.028 |
| D2 | 0.135 | 0.235 | 0.335 | 0.005 | 0.009 | 0.013 | | | | | | |
| E | 1.98 | 2.05 | 2.15 | 0.078 | 0.081 | 0.085 | 1.98 | 2.05 | 2.15 | 0.078 | 0.081 | 0.085 |
| E1 | 1.40 | 1.50 | 1.60 | 0.055 | 0.059 | 0.063 | 0.85 | 0.95 | 1.05 | 0.033 | 0.037 | 0.041 |
| E2 | 0.345 | 0.395 | 0.445 | 0.014 | 0.016 | 0.018 | | | | | | |
| E3 | 0.425 | 0.475 | 0.525 | 0.017 | 0.019 | 0.021 | | | | | | |
| e | 0.65 BSC | | | 0.026 BSC | | | 0.65 BSC | | | 0.026 BSC | | |
| K | 0.275 TYP | | | 0.011 TYP | | | 0.275 TYP | | | 0.011 TYP | | |
| K1 | 0.400 TYP | | | 0.016 TYP | | | 0.320 TYP | | | 0.013 TYP | | |
| K2 | 0.240 TYP | | | 0.009 TYP | | | 0.252 TYP | | | 0.010 TYP | | |
| K3 | 0.225 TYP | | | 0.009 TYP | | | | | | | | |
| K4 | 0.355 TYP | | | 0.014 TYP | | | | | | | | |
| L | 0.175 | 0.275 | 0.375 | 0.007 | 0.011 | 0.015 | 0.175 | 0.275 | 0.375 | 0.007 | 0.011 | 0.015 |
| T | | | | | | | 0.05 | 0.10 | 0.15 | 0.002 | 0.004 | 0.006 |

ECN: C-07431 – Rev. C, 06-Aug-07
DWG: 5934

RECOMMENDED PAD LAYOUT FOR PowerPAK® SC70-6L Dual



Dimensions in mm (inches)

Return to Index

APPLICATION NOTE



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Vishay\(威世\)](#)