


**INPUT RECTIFIER DIODE**

	$V_F < 1.1V @ 40A$ $I_{FSM} = 475A$ $V_{RRM} = 800 - 1200V$
---	---


**Description/Features**

The 40EPS.. rectifier **SAFEIR** series has been optimized for very low forward voltage drop, with moderate leakage. The glass passivation technology used has reliable operation up to 150° C junction temperature. Typical applications are in input rectification and these products are designed to be used with International Rectifier Switches and Output Rectifiers which are available in identical package outlines.

**Major Ratings and Characteristics**

Characteristics	Values	Units
$I_{F(AV)}$ Sinusoidal waveform	40	A
$V_{RRM}$ Range (*)	800- 1200	V
$I_{FSM}$	475	A
$V_F$ @40A, $T_J=25^\circ C$	1.1	V
$T_J$	-40 to 150	°C

**Package Outline**



(\*) for higher voltage up to 1600V contact factory

## Voltage Ratings

Part Number	$V_{RRM}$ , maximum peak reverse voltage V	$V_{RSM}$ , maximum non repetitive peak reverse voltage V	$I_{RRM}$ 150°C mA
40EPS08	800	900	1
40EPS12	1200	1300	

## Absolute Maximum Ratings

Parameters	40EPS..	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current	40	A	@ $T_C = 105^\circ\text{C}$ , 180° conduction half sine wave
$I_{FSM}$ Max. Peak One Cycle Non-Repetitive Surge Current	400	A	10ms Sine pulse, rated $V_{RRM}$ applied
	475		10ms Sine pulse, no voltage reapplied
$I^2t$ Max. $I^2t$ for fusing	800	$A^2s$	10ms Sine pulse, rated $V_{RRM}$ applied
	1131		10ms Sine pulse, no voltage reapplied
$I^2vt$ Max. $I^2vt$ for fusing	11310	$A^2vs$	t = 0.1 to 10ms, no voltage reapplied

## Electrical Specifications

Parameters	40EPS..	Units	Conditions
$V_{FM}$ Max. Forward Voltage Drop	1.1	V	@ 40A, $T_J = 25^\circ\text{C}$
$r_t$ Forward slope resistance	7.16	$m\Omega$	$T_J = 150^\circ\text{C}$
$V_{F(TO)}$ Threshold voltage	0.74	V	
$I_{RM}$ Max. Reverse Leakage Current	0.1	mA	$T_J = 25^\circ\text{C}$
	1.0		$T_J = 150^\circ\text{C}$

$V_R = \text{rated } V_{RRM}$

## Thermal-Mechanical Specifications

Parameters	40EPS..	Units	Conditions
$T_J$ Max. Junction Temperature Range	-40 to 150	$^\circ\text{C}$	
$T_{stg}$ Max. Storage Temperature Range	-40 to 150	$^\circ\text{C}$	
$R_{thJC}$ Max. Thermal Resistance Junction to Case	0.6	$^\circ\text{C/W}$	DC operation
$R_{thJA}$ Max. Thermal Resistance Junction to Ambient	40	$^\circ\text{C/W}$	
$R_{thCS}$ Typical Thermal Resistance, Case to Heatsink	0.2	$^\circ\text{C/W}$	Mounting surface, smooth and greased
wt Approximate Weight	6(0.21)	g(oz.)	
T Mounting Torque	Min.	6(5)	$\text{Kg-cm}$ $(\text{lbf-in})$
	Max.	12(10)	
Case Style	TO-247AC		JEDEC (Modified)




Fig. 1 - Current Rating Characteristics




Fig. 2 - Current Rating Characteristics




Fig. 3 - Forward Power Loss Characteristics




Fig. 4 - Forward Power Loss Characteristics




Fig. 5 - Forward Voltage Drop Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current






Fig. 7 - Thermal Impedance  $Z_{thJC}$  Characteristics

Outline Table



Marking Information

EXAMPLE: THIS IS A 40EPS12 WITH ASSEMBLY LOT CODE 5657 ASSEMBLED ON WW 35, 2000 IN THE ASSEMBLY LINE "H"




INTERNATIONAL RECTIFIER LOGO  
 ASSEMBLY LOT CODE  
 PART NUMBER  
 DATE CODE  
 YEAR 0 = 2000  
 WEEK 35  
 LINE H

Ordering Information Table

**Device Code**

40	E	P	S	12
①	②	③	④	⑤

- 1** - Current Rating (40 = 40A)
- 2** - Circuit Configuration  
E = Single Diode
- 3** - Package  
P = TO-247AC (Modified)
- 4** - Type of Silicon  
S = Standard Recovery Rectifier
- 5** - Voltage code: Code x 100 =  $V_{RRM}$



BASE CATHODE  
 CATHODE ANODE

08 = 800V
12 = 1200V

Data and specifications subject to change without notice.  
 This product has been designed and qualified for Industrial Level.  
 Qualification Standards can be found on IR's Web site.



## Notice

The products described herein were acquired by Vishay Intertechnology, Inc., as part of its acquisition of International Rectifier's Power Control Systems (PCS) business, which closed in April 2007. Specifications of the products displayed herein are pending review by Vishay and are subject to the terms and conditions shown below.

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

International Rectifier®, IR®, the IR logo, HEXFET®, HEXSense®, HEXDIP®, DOL®, INTERO®, and POWIRTRAIN® are registered trademarks of International Rectifier Corporation in the U.S. and other countries. All other product names noted herein may be trademarks of their respective owners.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Vishay\(威世\)](#)