



P-Channel 60-V (D-S) MOSFET




PRODUCT SUMMARY			
$V_{(BR)DSS(min)}$ (V)	$r_{DS(on)}$ (Ω)	$V_{GS(th)}$ (V)	I_D (A)
-60	6 @ $V_{GS} = -10$ V	-1 to -3.0	-0.27
	10 @ $V_{GS} = -4.5$ V		-0.21

FEATURES

- TrenchFET® Power MOSFET
- ESD Protected: 2000 V

APPLICATIONS

- Drivers: Relays, Solenoids, Lamps, Hammers, Displays, Memories, Transistors, etc.
- Battery Operated Systems
- Power Supply, Converter Circuits
- Motor Control



Ordering Information: TP0610KL-TR1

Ordering Information: BS250KL-TR1

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)				
Parameter	Symbol	Limit	Unit	
Drain-Source Voltage	V_{DS}	-60	V	
Gate-Source Voltage	V_{GS}	± 20		
Continuous Drain Current	I_D	$T_A = 25^\circ\text{C}$	-0.27	A
		$T_A = 70^\circ\text{C}$	-0.22	
Pulse Drain Current ^a	I_{DM}	-1.0		
Power Dissipation	P_D	$T_A = 25^\circ\text{C}$	0.8	W
		$T_A = 70^\circ\text{C}$	0.51	
Maximum Junction-to-Ambient	R_{thJA}	156	$^\circ\text{C}/\text{W}$	
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 150	$^\circ\text{C}$	

Notes

a. Pulse width limited by maximum junction temperature.



SPECIFICATIONS (T _A = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = -10 μA	-60			V
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250 μA	-1	-2.1	-3.0	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±10	μA
		V _{DS} = 0 V, V _{GS} = ±10 V			±200	
		V _{DS} = 0 V, V _{GS} = ±10 V, T _J = 85 °C			±500	nA
		V _{DS} = 0 V, V _{GS} = ±5 V			±100	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -60 V, V _{GS} = 0 V			-1	μA
		V _{DS} = -60 V, V _{GS} = 0 V, T _J = 55 °C			-10	
On-State Drain Current ^a	I _{D(on)}	V _{DS} = -10 V, V _{GS} = -4.5 V	-50			mA
		V _{DS} = -10 V, V _{GS} = -10 V	-600			
Drain-Source On-Resistance ^a	r _{DS(on)}	V _{GS} = -4.5 V, I _D = -25 mA		5.5	10	Ω
		V _{GS} = -10 V, I _D = -500 mA		3.1	6	
		V _{GS} = -10 V, I _D = -500 mA, T _J = 125 °C		4.7	9	
Forward Transconductance ^a	g _{fs}	V _{DS} = -10 V, I _D = -100 mA		180		mS
Diode Forward Voltage ^a	V _{SD}	I _S = -200 mA, V _{GS} = 0 V		-0.9	-1.4	V
Dynamic^b						
Total Gate Charge	Q _g	V _{DS} = -30 V, V _{GS} = -15 V, I _D ≅ -500 mA		1.7	3	nC
Gate-Source Charge	Q _{gs}			0.26		
Gate-Drain Charge	Q _{gd}			0.46		
Gate Resistance	R _g			285		Ω
Turn-On Time	t _{d(on)}	V _{DD} = -25 V, R _L = 150 Ω I _D ≅ -150 mA, V _{GEN} = -10 V R _g = 10 Ω		2.4	5	ns
	t _r			15.5	25	
Turn-Off Time	t _{d(off)}			21	35	
	t _f			12.5	20	

Notes

- a. Pulse test: PW ≤ 300 ms duty cycle ≤ 2%.
- b. Guaranteed by design, not subject to production testing.

TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)







For the following graphs, p-channel negative polarities for all voltage and current values are represented as positive values.









TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

For the following graphs, p-channel negative polarities for all voltage and current values are represented as positive values.



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

For the following graphs, p-channel negative polarities for all voltage and current values are represented as positive values.





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Vishay\(威世\)](#)