

International IOR Rectifier

MBR10.. Series MBRB10.. Series

SCHOTTKY RECTIFIER

10 Amp

$$I_{F(AV)} = 10\text{Amp}$$

$$V_R = 35 - 45\text{V}$$

Major Ratings and Characteristics


Characteristics	Values	Units
$I_{F(AV)}$ Rectangular waveform	10	A
V_{RRM} range	35-45	V
I_{FSM} @tp=5µs sine	1060	A
V_F @10Apk, $T_J = 125^\circ\text{C}$	0.57	V
T_J range	-55 to 150	$^\circ\text{C}$

Description/ Features

This Schottky rectifier has been optimized for low reverse leakage at high temperature. The proprietary barrier technology allows for reliable operation up to 150° C junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- 150° C T_J operation
- TO-220 and D²Pak packages
- Low forward voltage drop
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability

Case Styles



Voltage Ratings

Partnumber	MBR1035/MBRB1035	MBR1045/MBRB1045
V_R Max. DC Reverse Voltage (V)	35	45
V_{RWM} Max. Working Peak Reverse Voltage (V)		

Absolute Maximum Ratings

Parameters	Values	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current	10	A	@ $T_C = 135^\circ\text{C}$ (Rated V_R)
I_{FRM} Peak Repetitive Forward Current	20	A	Rated V_R , square wave, 20kHz $T_C = 135^\circ\text{C}$
I_{FSM} Non Repetitive Peak Surge Current	1060	A	5 μs Sine or 3 μs Rect. pulse Following any rated load condition and with rated V_{RWM} applied
	150		Surge applied at rated load conditions halfwave, single phase, 60Hz
E_{AS} Non-Repetitive Avalanche Energy	8	mJ	$T_J = 25^\circ\text{C}$, $I_{AS} = 2\text{Amps}$, $L = 4\text{mH}$
I_{AR} Repetitive Avalanche Current	2	A	Current decaying linearly to zero in 1 μsec Frequency limited by T_J max. $V_A = 1.5 \times V_R$ typical

Electrical Specifications

Parameters	Values	Units	Conditions	
V_{FM} Max. Forward Voltage Drop (1)	0.84	V	@ 20A	$T_J = 25^\circ\text{C}$
	0.57	V	@ 10A	$T_J = 125^\circ\text{C}$
	0.72	V	@ 20A	
I_{RM} Max. Instantaneous Reverse Current (1)	0.1	mA	$T_J = 25^\circ\text{C}$	Rated DC voltage
	15	mA	$T_J = 125^\circ\text{C}$	
$V_{F(TO)}$ Threshold Voltage	0.354	V	$T_J = T_J$ max.	
r_f Forward Slope Resistance	17.6	m Ω		
C_T Max. Junction Capacitance	600	pF	$V_R = 5V_{DC}$ (test signal range 100Khz to 1Mhz) 25°C	
L_S Typical Series Inductance	8.0	nH	Measured from top of terminal to mounting plane	
dv/dt Max. Voltage Rate of Change	10000	V/ μs	(Rated V_R)	

(1) Pulse Width < 300 μs , Duty Cycle <2%

Thermal-Mechanical Specifications

Parameters	Values	Units	Conditions
T_J Max. Junction Temperature Range	-65 to 150	$^\circ\text{C}$	
T_{stg} Max. Storage Temperature Range	-65 to 175	$^\circ\text{C}$	
R_{thJC} Max. Thermal Resistance Junction to Case	2.0	$^\circ\text{C/W}$	DC operation
R_{thCS} Typical Thermal Resistance Case to Heatsink	0.50	$^\circ\text{C/W}$	Mounting surface, smooth and greased Only for TO-220
wt Approximate Weight	2 (0.07)	g (oz.)	
T Mounting Torque	Min. 6 (5)	Kg-cm (lbf-in)	
	Max. 12 (10)		
Marking Device	MBR1045	CaseStyle TO-220	
	MBRB1045	CaseStyle D ² Pak	




Fig. 1 - Max. Forward Voltage Drop Characteristics




Fig. 2 - Typical Values Of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Max. Thermal Impedance Z_{thJC} Characteristics




Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics







Fig. 7 - Max. Non-Repetitive Surge Current

- (2) Formula used: $T_C = T_J - (P_d + P_{d_{REV}}) \times R_{thJC}$;
 $P_d = \text{Forward Power Loss} = I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$ (see Fig. 6);
 $P_{d_{REV}} = \text{Inverse Power Loss} = V_{R1} \times I_R (1 - D)$; $I_R @ V_{R1} = \text{rated } V_R$


Outline Table



Part Marking Information



Tape & Reel Information



Ordering Information Table

Device Code													
	<table border="1" style="margin: auto;"> <tr> <td style="padding: 5px;">MBR</td> <td style="padding: 5px;">B</td> <td style="padding: 5px;">10</td> <td style="padding: 5px;">45</td> <td style="padding: 5px;">TRL</td> <td style="padding: 5px;">-</td> </tr> <tr> <td style="text-align: center;">①</td> <td style="text-align: center;">②</td> <td style="text-align: center;">③</td> <td style="text-align: center;">④</td> <td style="text-align: center;">⑤</td> <td style="text-align: center;">⑥</td> </tr> </table>	MBR	B	10	45	TRL	-	①	②	③	④	⑤	⑥
MBR	B	10	45	TRL	-								
①	②	③	④	⑤	⑥								
1	- Schottky MBR Series												
2	- Package Style: <ul style="list-style-type: none"> • none = TO-220 • B = D²PAK 												
3	- Current Rating (10 = 10A)												
4	- Voltage Ratings												
5	- <ul style="list-style-type: none"> • none = Tube • TRR = Tape & Reel (Right Oriented) • TRL = Tape & Reel (Left Oriented) 												
6	- <ul style="list-style-type: none"> • none = Standard Production • PbF = Lead-Free 												

35 = 35V
45 = 45V

```

MBR1045
*****
* This model has been developed by *
* Wizard SPICE MODEL GENERATOR (1999) *
* (International Rectifier Corporation) *
* Contains Proprietary Information *
*****
* SPICE Model Diode is composed by a *
* simple diode plus paralld VCG2T *
*****
.SUBCKT MBR1045 ANO,CAT
D1 ANO 1 DMOD (0.04688)
*Define diode model
.MODEL DMODD (IS=2.14849701885607E-04A,N=1.50833541375759,BV=52V,
+IBV=0.431942180477539A,RS=0.000618816,CJO=1.90645706123736E-08,
+VJ=2.31227489200037,XTI=2,EG=0.684712841282824)
*****
*Implementation of VCG2T
VX 1 2 DC 0V
R1 2 CAT TRES 1E-6
.MODEL TRES RES (R=1,TC1=-29.9118224426661)
GP1 ANO,CAT VALUE={-ABS(I(VX))*(EXP((( -6.195028E-06 / -29.91182) * ((V(2,CAT) * 1E6) / (I(VX) + 1E-6) - 1)) + 1) * 4.475503E-02 * ABS(V(ANO,CAT))) - 1)}
*****
.ENDS MBR1045

Thermal Model Subcircuit
.SUBCKT MBR1045 5 1

CTHERM1 5 4 1.40E+00
CTHERM2 4 3 1.46E+01
CTHERM3 3 2 9.30E+01
CTHERM4 2 1 1.69E+03

RTHERM1 5 4 5.79E-01
RTHERM2 4 3 7.72E-01
RTHERM1 3 2 4.45E-01
RTHERM1 2 1 1.93E-01

.ENDS MBR1045
    
```

Data and specifications subject to change without notice.
 This product has been designed and qualified for Industrial Level.
 Qualification Standards can be found on IR's Web site.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Vishay\(威世\)](#)