



## 5-Line ESD-Protection Diode Array in LLP75-6A


### Features

- Ultra compact LLP75-6A package
- 5-line ESD-protection
- Low leakage current  $I_R < 0.1 \mu A$
- Low load capacitance of typ. 43 pF at  $V_R = 0 V$
- ESD-immunity acc. IEC 61000-4-2  $\pm 30 kV$  contact discharge  $\pm 30 kV$  air discharge
- Working voltage range  $V_{RWM} = 5 V$
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



19956

### Marking (example only)



Dot = Pin 1 marking

XX = Date code

YY = Type code (see table below)

### Ordering Information

| Device name | Ordering code    | Taped units per reel<br>(8 mm tape on 7" reel) | Minimum order quantity |
|-------------|------------------|--|------------------------|
| GMF05LC-HS3 | GMF05LC-HS3-GS08 | 3000   | 15000                  |

### Package Data

| Device name | Package name | Type code | Weight | Molding compound flammability rating | Moisture sensitivity level        | Soldering conditions     |
|-------------|--------------|-----------|--------|--------------------------------------|-----------------------------------|--------------------------|
| GMF05LC-HS3 | LLP75-6A     | F6        | 5.1 mg | UL 94 V-0                            | MSL level 1 (according J-STD-020) | 260 °C/10 s at terminals |

### Absolute Maximum Ratings

| Rating                | Test condition  | Symbol            | Value         | Unit     |    |
|-----------------------|---|-------------------|---------------|----------|----|
| Peak pulse current    | BiAs-mode: each input (pin 1; 3 - pin 6) to ground (pin 2);<br>acc. IEC 61000-4-5; $t_p = 8/20 \mu s$ ; single shot | $I_{PPM}$         | 5             | A        |    |
| Peak pulse power      | BiAs-mode: each input (pin 1; 3 - pin 6) to ground (pin 2);<br>acc. IEC 61000-4-5; $t_p = 8/20 \mu s$ ; single shot | $P_{PP}$          | 70            | W        |    |
| ESD-immunity          | acc. IEC61000-4-2; 10 pulses<br>BiAs-mode: each input (pin 1; 3 - pin 6) to ground (pin 2)                          | contact discharge | $V_{ESD}$     | $\pm 30$ | kV |
|                       |   | air discharge     | $V_{ESD}$     | $\pm 30$ | kV |
| Operating temperature | Junction temperature  | $T_J$             | - 55 to + 125 | °C       |    |
| Storage temperature   |   | $T_{STG}$         | - 55 to + 150 | °C       |    |

\* Please see document "Vishay Green and Halogen-Free Definitions (5-2008)" <http://www.vishay.com/doc?99902>



## BiAs-Mode (5-line Bidirectional Asymmetrical protection mode)

With the **GMF05LC-HS3** up to 5 signal- or data-lines (L1 - L5) can be protected against voltage transients. With pin 2 connected to ground and pin 1; 3 up to pin 6 connected to a signal- or data-line which has to be protected. As long as the voltage level on the data- or signal-line is between 0 V (ground level) and the specified **Maximum Reverse Working Voltage ( $V_{RWM}$ )** the protection diode between data line and ground offer a high isolation to the ground line. The protection device behaves like an open switch.

As soon as any positive transient voltage signal exceeds the break through voltage level of the protection diode, the diode becomes conductive and shorts the transient current to ground. Now the protection device behaves like a closed switch. The **Clamping Voltage ( $V_C$ )** is defined by the **Breakthrough Voltage ( $V_{BR}$ )** level plus the voltage drop at the series impedance (resistance and inductance) of the protection device.

Any negative transient signal will be clamped accordingly. The negative transient current is flowing in the forward direction of the protection diode. The low **Forward Voltage ( $V_F$ )** clamps the negative transient close to the ground level.

Due to the different clamping levels in forward and reverse direction the **GMF05LC-HS3** clamping behaviour is **Bidirectional** and **Asymmetrical (BiAs)**.



20739

## Electrical Characteristics

Ratings at 25 °C ambient temperature, unless otherwise specified

### GMF05LC-HS3


**BiAs mode: each input (pin 1, 3, 4, 5, 6) to ground (pin 2)**

| Parameter                 | Test conditions/remarks                          | Symbol    | Min. | Typ. | Max. | Unit    |
|---------------------------|--|-----------|------|------|------|---------|
| Protection paths          | number of line which can be protected            | N lines   |      |      | 5    | lines   |
| Reverse stand-off voltage | at $I_R = 1 \mu A$                               | $V_{RWM}$ | 5    |      |      | V       |
| Reverse current           | at $V_R = V_{RWM} = 5 V$                         | $I_R$     |      | 0.01 | 0.1  | $\mu A$ |
| Reverse breakdown voltage | at $I_R = 1 mA$                                  | $V_{BR}$  | 6    |      | 8    | V       |
| Reverse clamping voltage  | at $I_{PP} = 1 A$ ; acc. IEC 61000-4-5           | $V_C$     |      | 8    | 9.5  | V       |
|                           | at $I_{PP} = I_{PPM} = 5 A$ ; acc. IEC 61000-4-5 | $V_C$     |      | 11.5 | 12.5 | V       |
| Forward clamping voltage  | at $I_F = 1 A$ ; acc. IEC 61000-4-5              | $V_F$     |      | 1.5  | 2    | V       |
|                           | at $I_{PP} = I_{PPM} = 5 A$ ; acc. IEC 61000-4-5 | $V_F$     |      | 3.1  | 4    | V       |
| Line capacitance          | at $V_R = 0 V$ ; $f = 1 MHz$                     | $C_D$     |      | 43   | 50   | pF      |
|                           | at $V_R = 2.5 V$ ; $f = 1 MHz$                   | $C_D$     |      | 25   |      | pF      |

If a higher surge current or **Peak Pulse current ( $I_{PP}$ )** is needed, some protection diodes in the **GMF05LC-HS3** can also be used in parallel in order to "multiply" the performance.

If two diodes are switched in parallel you get


- double surge power = double peak pulse current ( $2 \times I_{PPM}$ )
- half of the line inductance = reduced clamping voltage
- half of the line resistance = reduced clamping voltage
- double line **Capacitance** ( $2 \times C_D$ )
- double **Reverse leakage current** ( $2 \times I_R$ )



20740


## Typical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified




20557

Figure 1. ESD Discharge Current Wave Form acc. IEC 61000-4-2 (330  $\Omega$ /150 pF)




20281

Figure 3. Typical Capacitance  $C_D$  vs. Reverse Voltage  $V_R$



20548

Figure 2. 8/20  $\mu\text{s}$  Peak Pulse Current Wave Form acc. IEC 61000-4-5



20282

Figure 4. Typical Forward Current  $I_F$  vs. Forward Voltage  $V_F$




Figure 5. Typical Reverse Voltage  $V_R$  vs. Reverse Current  $I_R$




Figure 8. Typical Clamping performance at -8 kV Contact Discharge (acc. IEC 61000-4-2)




Figure 6. Typical Peak Clamping Voltage  $V_C$  vs. Peak Pulse Current  $I_{PP}$




Figure 9. Typical Peak Clamping Voltage at ESD Contact Discharge (acc. IEC 61000-4-2)






Figure 7. Typical Clamping Performance at +8 kV Contact Discharge (acc. IEC 61000-4-2)

**Package Dimensions** in millimeters (inches): **LLP75-6A**



foot print recommendation:



Document no.: S8-V-3906.02-001 (4)  
 Created - Date: 20.December 2004  
 Rev. b - Date: 12.January 2006  
 18058

### Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively.
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA.
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.


We reserve the right to make changes to improve technical design  
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany

## LLP75-6A


### Package Dimensions in mm (Inches)



Document no.: S8-V-3906.02-001 (4)  
 Created - Date: 20.December 2004  
 Rev. b - Date: 12.January 2006  
 18058

## LLP75-6A

### Package Dimensions in mm (Inches)



Document no.: S8-V-3906.02-001 (4)  
 Created - Date: 20.December 2004  
 Rev. b - Date: 12.January 2006  
 18058



### Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design  
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

单击下面可查看定价，库存，交付和生命周期等信息

[>>Vishay\(威世\)](#)