

APPROVAL SHEET

RF Switch Series – RoHS Compliance

DPDT GPIO Switch

Halogens Free Product

Any 2G/3G/4G Band for TRx System

P/N: RFASWB643ATF09

*Contents in this sheet are subject to change without prior notice.

Approval Sheet

FEATURES

- Low Insertion Loss : 0.45dB typ. @ 2.7GHz
- High Isolation : 27dB typ. @ 2.7GHz
- Low control voltage : 1.3 to 2.7 V
- Miniature footprint : 2.0 x 2.0 x 0.55 mm³
- **M**oisture **S**ensitive **L**evel 3 (MSL3)
- High ESD tolerance of 2kV HBM at all pins


Description

- The RFASWB643ATF09 is a SOI (Silicon On Insulator) double pole double throw (DPDT) switch in a low cost miniature QFN (2.0x2.0 x0.55mm³) package. Typical applications are for SV-LTE ,LTE-A and diversity antenna switching.
- The RFASWB643ATF09 is ideally suited for applications where high power, high linearity, low insertion loss, and small size are required.
- The RFASWB643ATF09 has ESD protection devices to achieve excellent ESD performances.

Application

- 2G/3G/4G multimode cellular handsets (LTE, UMTS, CDMA2000, EDGE, GSM, TDD-LTE, TD-SCDMA)

Block Diagram and Pin Out (Top View)




Pin Names and Descriptions

Pin	Name	Description	Pin	Name	Description
1	VDD	DC power supply	7	RF1	RF path 1
2	N/C	No connected	8	N/C	No connected
3	V _{c1}	Control voltage 1	9	RF4	RF path 4
4	GND	Ground	10	GND	Ground
5	RF2	RF path 2	11	path3	RF path 3
6	GND	Ground	12	GND	Ground

Approval Sheet

Application Circuit



Parts List

Parts No.	Value
C1-C2	1000 pF

Absolute Maximum Ratings

Parameter	Symbol	Minimum	Maximum	Units
Max Input Power	Pin		+36	dBm
DC Supply Voltage	VDD	+2.6	+5.0	V
DC Control Voltage	Vc1	0	+2.7	V
Operating temperature	T _{OP}	-30	+85	°C
Storage temperature	T _{ST}	-65	+105	°C
HBM ESD Voltage, All Pins	V _{ESD} ¹	-	+2000	V

Exceeding absolute maximum ratings may cause permanent damage. Operation between operating range maximum and absolute maximum for extended periods may reduce reliability.

Approval Sheet
Electrical Specifications at 25°C with VDD=2.8V, V_{C1}=0/1.8V, Characteristic Impedance Z₀=50Ω, Pin=0dBm

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Units
RF Specifications						
Operating frequency	f		0.7		3.0	GHz
Insertion loss (Port1/2 to Port3/4)	IL	0.7 ~ 1.0 GHz	-	0.30	0.40	dB
		1.0 ~ 2.0 GHz		0.35	0.50	dB
		2.0 ~ 2.7 GHz		0.45	0.60	dB
Isolation (Port1/2 to Port3/4)	Iso	0.7 ~ 1.0 GHz	32	40	-	dB
		1.0 ~ 2.0 GHz	26	32	-	dB
		2.0 ~ 2.7 GHz	22	27	-	dB
On state match (Port1/2)	VSWR	0.7 ~ 2.7 GHz	-	1.12	1.5	-
RFx Harmonics	2f ₀	PIN = +36 dBm, f = 900 MHz	-	-72	-70	dBc
	3f ₀	PIN = +36 dBm, f = 900 MHz	-	-73	-60	dBc
3 rd Order Intermodulation Distortion	IMD3	F _{cw1} =1.85 GHz, P _{cw1} = +20dBm F _{cw2} =1.74 GHz, P _{cw2} = -15dBm	-	-115	-	dBm
2 nd Order Input Intercept Point	IIP2	F _{cw1} =0.9 GHz, P _{cw1} = +20dBm F _{cw1} =1.85 GHz, P _{cw2} = 0dBm	-	+115	-	dBm
DC Specification (Decoder)						
Supply Voltage	VDD		2.6	2.8	4.5	V
Supply Current	IDD	VDD= 2.8V	-	70	-	μA
Control Voltage(High)	V _{C1(H)}		1.3	1.8	2.7	V
Control Voltage(Low)	V _{C1(L)}		0	-	0.45	V
Control Current	I _{C1}	V _{C1} = 1.8V	-	0.1	5	μA
Switching Specification						
Switching speed	T _{SW}	50% V _{CTL} to 90/10% RF	-	-	5	μs


Note : All measurements made in a 50Ω system with 0/+1.8V control voltages, unless otherwise specified.

Logic Table for Switch On-Path


VC1	State
1	PORT3 to PORT1, PORT4 to PORT2
0	PORT3 to PORT2, PORT4 to PORT1

State 1=1.3V to 2.7V ; State 0= 0V to 0.45V

Approval Sheet
Package Dimensions



Solder Land Pattern



Approval Sheet

Reliability test

TEST	PROCEDURE / TEST METHOD	REQUIREMENT
Solderability JIS C 0050-4.6 JESD22-B102D	*Solder bath temperature : 255 ± 5°C *Immersion time : 5 ± 0.5 sec Solder : Sn3Ag0.5Cu for lead-free	At least 95% of a surface of each terminal electrode must be covered by fresh solder.
High temperature JIS C 0021	*Temperature : 90°C±2°C *Test duration : 1000+24/-0 hours Measurement to be made after keeping at room temperature for 24±2 hrs	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics under the operational temperature range within -30 ~ 90°C.
Low temperature JIS C 0020	*Temperature : -30°C±2°C *Test duration : 1000+24/-0 hours Measurement to be made after keeping at room temperature for 24±2 hrs	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics under the operational temperature range within -30 ~ 90°C.
Temperature cycle JIS C 0025	1. 30±3 minutes at -30±3°C, 2. 10~15 minutes at room temperature, 3. 30±3 minutes at +90±3°C, 4. 10~15 minutes at room temperature, Total 100 continuous cycles Measurement to be made after keeping at room temperature for 24±2 hrs	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics under the operational temperature range within -30 ~ 90°C.
High temperature operation life (HTOL)	*Temperature : 90°C *VDD = 4.8V *Time : 1000+24/-0 hrs. Measurement to be made after keeping at room temperature for 24±2 hrs	No mechanical damage. Electrical specification shall satisfy the descriptions in electrical characteristics under the operational temperature range within -30 ~ 90°C.

Soldering condition

Typical examples of soldering processes that provide reliable joints without any damage are given in Figure 11.




Figure 11. Infrared soldering profile


Approval Sheet

Ordering code

RF	ASW	B	643A	T
RF module RF: Walsin RF Switch Device	Module type ASW: Antenna Switch	Application B: DPDT	Design Code	Packing T: Taping

Minimum Ordering Quantity: 3000 pcs per reel.


Packaging



Plastic Tape specifications (unit :mm)

Index	Ao	Bo	øD	T	W
Dimension (mm)	2.25 ± 0.10	2.25 ± 0.10	1.55 ± 0.05	0.75 ± 0.10	8.00 ± 0.3
Index	E	F	Po	P1	P2
Dimension (mm)	1.75 ± 0.10	3.50 ± 0.10	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05

Reel dimensions



Index	A	B	C
Dimension (mm)	Φ180	Φ62.5	Φ13.0

Taping Quantity : 3000 pieces per 7" reel

Approval Sheet

Caution of handling

Limitation of Applications

Please contact us before using our products for the applications listed below which require especially high reliability for the prevention of defects, which might directly cause damage to the third party's life, body or property.

- (1) Aircraft equipment
- (2) Aerospace equipment
- (3) Undersea equipment
- (4) Medical equipment
- (5) Disaster prevention / crime prevention equipment
- (6) Traffic signal equipment
- (7) Transportation equipment (vehicles, trains, ships, etc.)
- (8) Applications of similar complexity and /or reliability requirements to the applications listed in the above.

Storage condition

- (1) Products should be used in 6 months from the day of WALSIN outgoing inspection, which can be confirmed.
- (2) Storage environment condition.
 - Products should be storage in the warehouse on the following conditions.
 - Temperature : -10 to +40°C
 - Humidity : 30 to 70% relative humidity
 - Don't keep products in corrosive gases such as sulfur. Chlorine gas or acid or it may cause oxidization of electrode, resulting in poor solderability.
 - Products should be storage on the palette for the prevention of the influence from humidity, dust and son on.
 - Products should be storage in the warehouse without heat shock, vibration, direct sunlight and so on.
 - Products should be storage under the airtight packaged condition.

单击下面可查看定价，库存，交付和生命周期等信息

[>>Walsin Technology\(华新科技\(华科\)\)](#)