

APPROVAL SHEET

**WF25Z_Q, WF20Z_Q, WF10Z_Q,
WF12Z_Q, WF08Z_Q, WF06Z_Q,
WF04Z_Q.**

**$\pm 1\%$, $\pm 0.5\%$, $\pm 0.25\%$, $\pm 0.1\%$, $\pm 0.05\%$, $\pm 0.02\%$,
 $\pm 0.01\%$**

TC 5

High Precision Thin Film Chip Resistor

Size 2512, 2010, 1210, 1206, 0805, 0603, 0402

AEC-Q200 Compliant

RoHS Exemption free and Lead free products

Halogen free



*Contents in this sheet are subject to change without prior notice.

FEATURE

1. SMD metal film resistor
2. High reliability and stability of 0.5% and below per customer request
3. High performance of TCR: 5 ppm/°C and below per customer request
4. Low current noise
5. RoHS compliant and lead free
6. AEC-Q200 compliant

APPLICATION

- Automotive
- Medical equipment
- Measuring instrument
- Communication device
- Electronic Devices

DESCRIPTION

The resistors are constructed in a high grade ceramic body (aluminum oxide). Internal metal electrodes are added at each end and connected by a resistive layer that is applied to the top surface of the substrate. The composition of the resistive layer is adjusted to give the approximate resistance required and the value is trimmed to nominated value within tolerance which controlled by laser trimming of this resistive layer.

The resistive layer is covered with a protective coat. Finally, the two external end terminations are added. For environmental soldering issue, the outer layer of these end terminations is a Lead-free solder .




Fig 1. Construction of Chip-R WFxxZ_Q

QUICK REFERENCE DATA

| Item | General Specification | | | | | | |
|---|---|----------------|----------------|-----------------|-----------------|----------------|----------------|
| Series No. | WF25Z_Q | WF20Z_Q | WF10Z_Q | WF12Z_Q | WF08Z_Q | WF06Z_Q | WF04Z_Q |
| Size Code | 2512 (6432) | 2010 (5025) | 1210 (3225) | 1206 (3216) | 0805 (2012) | 0603 (1608) | 0402 (1005) |
| Resistance Tolerance | ±1.0%, ±0.5%, ±0.25%, ±0.1%, ±0.05%, ±0.02%, ±0.01% | | | | | | |
| Resistance Range | 10Ω ~ 600KΩ | 10Ω ~ 360KΩ | 10Ω ~ 150KΩ | 4.7Ω ~ 150KΩ | 4.7Ω ~ 100KΩ | 4.7Ω ~ 50KΩ | 10Ω ~ 10KΩ |
| TCR | ±5 ppm/°C | | | | | | |
| Max. Dissipation at T _{amb} =70°C | 1W | 3/4W | 2/5W | 1/4W | 1/8W | 1/10W | 1/10W |
| Max. Operation Voltage | 200V | 200V | 200V | 200V | 150V | 75V | 50V |
| Max. Overload Voltage | 400V | 400V | 400V | 400V | 300V | 150V | 100V |
| Operating Temperature | - 55~ +155°C | | | | | | |


Note :

- This is the maximum voltage that may be continuously supplied to the resistor element, see "IEC publication 60115-8"
- Max. Operation Voltage : So called RCWV (Rated Continuous Working Voltage) is determined by

$$RCWV = \sqrt{\text{Rated Power} \times \text{Resistance Value}} \text{ or Max. RCWV listed above, whichever is lower.}$$

DIMENSIONS:(unit:mm)

| Type | WF25Z_Q | WF20Z_Q | WF10Z_Q | WF12Z_Q | WF08Z_Q | WF06Z_Q | WF04Z_Q |
|------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| L | 6.35 ± 0.10 | 5.00 ± 0.10 | 3.10 ± 0.10 | 3.05 ± 0.15 | 2.00 ± 0.10 | 1.55 ± 0.10 | 1.00 ± 0.10 |
| W | 3.20 ± 0.15 | 2.50 ± 0.15 | 2.60 ± 0.15 | 1.55 ± 0.15 | 1.25 ± 0.10 | 0.80 ± 0.10 | 0.50 ± 0.05 |
| A | 0.60 ± 0.20 | 0.60 ± 0.20 | 0.50 ± 0.20 | 0.40 ± 0.20 | 0.25 ± 0.20 | 0.25 ± 0.15 | 0.3 ± 0.15 |
| B | 0.90 ± 0.25 | 0.60 ± 0.25 | 0.50 ± 0.20 | 0.40 ± 0.20 | 0.40 ± 0.20 | 0.30 ± 0.15 | 0.3 ± 0.15 |
| t | 0.55 ± 0.10 | 0.55 ± 0.10 | 0.55 ± 0.10 | 0.55 ± 0.15 | 0.50 ± 0.15 | 0.45 ± 0.15 | 0.35 ± 0.05 |



MARKING

- **3-digit marking for 0603 size**

WFxxZ has same marking rule as WRxx ±1%.

| Nominal resistance | | Description | | | | | | | | | | | | | |
|--------------------|---------|---|---------|------|---------|------|---------|------|---------|------|---------|------|---------|------|---------|
| 1.E-24 series | | As 0603 WR06X ±5%. | | | | | | | | | | | | | |
| 2.E-96 series | | The 1st two digit codes are referring to the CODE on the table, the 3rd code is the index of resistance value : Y=10 ⁻² , X=10 ⁻¹ , A=10 ⁰ , B=10 ¹ , C=10 ² , D=10 ³ , E=10 ⁴ , F=10 ⁵ EX: 17.8Ω=25X, 178Ω=25A, 1K78=25B 17K8=25C, 178K=25D, 1M78=25E | | | | | | | | | | | | | |
| 3. Remark | | There is no marking for the items are not under E-24 and E-96 series | | | | | | | | | | | | | |
| CODE | R_value | CODE | R_value | CODE | R_value | CODE | R_value | CODE | R_value | CODE | R_value | CODE | R_value | CODE | R_value |
| 01 | 100 | 13 | 133 | 25 | 178 | 37 | 237 | 49 | 316 | 61 | 422 | 73 | 562 | 85 | 750 |
| 02 | 102 | 14 | 137 | 26 | 182 | 38 | 243 | 50 | 324 | 62 | 432 | 74 | 576 | 86 | 768 |
| 03 | 105 | 15 | 140 | 27 | 187 | 39 | 249 | 51 | 332 | 63 | 442 | 75 | 590 | 87 | 787 |
| 04 | 107 | 16 | 143 | 28 | 191 | 40 | 255 | 52 | 340 | 64 | 453 | 76 | 604 | 88 | 806 |
| 05 | 110 | 17 | 147 | 29 | 196 | 41 | 261 | 53 | 348 | 65 | 464 | 77 | 619 | 89 | 825 |
| 06 | 113 | 18 | 150 | 30 | 200 | 42 | 267 | 54 | 357 | 66 | 475 | 78 | 634 | 90 | 845 |
| 07 | 115 | 19 | 154 | 31 | 205 | 43 | 274 | 55 | 365 | 67 | 487 | 79 | 649 | 91 | 866 |
| 08 | 118 | 20 | 158 | 32 | 210 | 44 | 280 | 56 | 374 | 68 | 499 | 80 | 665 | 92 | 887 |
| 09 | 121 | 21 | 162 | 33 | 215 | 45 | 287 | 57 | 383 | 69 | 511 | 81 | 681 | 93 | 909 |
| 10 | 124 | 22 | 165 | 34 | 221 | 46 | 294 | 58 | 392 | 70 | 523 | 82 | 698 | 94 | 931 |
| 11 | 127 | 23 | 169 | 35 | 226 | 47 | 301 | 59 | 402 | 71 | 536 | 83 | 715 | 95 | 953 |
| 12 | 130 | 24 | 174 | 36 | 232 | 48 | 309 | 60 | 412 | 72 | 549 | 84 | 732 | 96 | 976 |

- **4-digit marking for 2512, 2010, 1210, 1206, 0805 size**

For E24+E96 series, each resistor is marked with a four digits code on the protective coating to designate the nominal resistance value. For values below 970Ω the R is used as a digit. For values of 100Ω or greater, the first 3 digits are significant, the fourth digit indicates the number of multiple to follow.

No marking for E192 series

Example

| | | | |
|-----------------|------|-------|--------|
| RESISTANCE | 100Ω | 6800Ω | 47000Ω |
| 4-digit marking | 1000 | 6801 | 4702 |

- **No marking code for 0402 size**

FUNCTIONAL DESCRIPTION

Product characterization

Standard values of nominal resistance are taken from the E192 & E24 series for resistors with a tolerance of ±1.0%, ±0.5%, ±0.25%, ±0.1%, ±0.05%. The values of the E24/E192 series are in accordance with "IEC publication 60063".

DERATING:

The power that the resistor can dissipate depends on the operating temperature; see Fig.2




Fig.2 Maximum dissipation in percentage of rated power
As a function of the ambient temperature


MOUNTING

Due to their rectangular shapes and small tolerances, Surface Mountable Resistors are suitable for handling by automatic placement systems.

Chip placement can be on ceramic substrates and printed-circuit boards (PCBs).

Electrical connection to the circuit is by individual soldering condition.

The end terminations guarantee a reliable contact.



SOLDERING CONDITION

The robust construction of chip resistors allows them to be completely immersed in a solder bath of 260°C for 10 seconds. Therefore, it is possible to mount Surface Mount Resistors on one side of a PCB and other discrete components on the reverse (mixed PCBs).

Surface Mount Resistors are tested for solderability at 235°C during 2 seconds within lead-free solder bath. The test condition for no leaching is 260°C for 30 seconds. Typical examples of soldering profile and condition that provide reliable joints without any damage are given in Fig 3. and Table 1.




Fig. 3 Infrared soldering profile for Chip Resistors

Table 1. Infrared soldering condition for Chip Resistors

| Temperature Condition | Exposure Time |
|---------------------------------------|-----------------------------|
| Average ramp-up rate (217°C to 260°C) | Less than 3°C/second |
| Between 150 and 200°C | Between 60-120 seconds |
| > 217°C | Between 60-150 seconds |
| Peak Temperature | 260°C +0/-5°C |
| Time within 245°C | Min. 30 seconds |
| Ramp-down rate (Peak to 217°C) | Less than 6°C/second |
| Time from 25°C to Peak | No greater than 480 seconds |

CATALOGUE NUMBERS

The resistors have a catalogue number starting with .

| WF06 | Z | xxxx | B | T | L | Q |
|--|------------------|---|--|---|-------------------------|--------------------------|
| Size code | Type code | Resistance code | Tolerance | Packaging code | Termination code | Special code |
| WF25: 2512 WF20: 2010 WF10: 1210 WF12: 1206 WF08: 0805 WF06: 0603 WF04: 0402 | Z: TCR = 5 ppm | E24+E192: 3 significant digits followed by no. of zeros 82Ω =82R0 102Ω =1020 37.4KΩ =3742 | T : ±0.01% U : ±0.02% A : ±0.05% B : ±0.10% C : ±0.25% D : ±0.50% F : ±1.00% | T : 7" Reel & Taped V: 7" Reel & Taped 1Kpcs Z: 7" Reel & Taped 3Kpcs M: 7" Reel & Taped 5Kpcs A :7" reel 15Kpcs only for 0402 D :7" reel 20Kpcs only for 0402 Q :10" Reeled taping G :13" Reeled taping H :13" reel 50Kpcs only for 0402 | L : lead free | Q: AEC-Q200 Compliant |

Standard packaging quantity/units (pcs) :


| Size | Reel(Taping code) Tape specifications | 7" reel | 7" reel | 7" reel | 7" reel | 7" reel | 7" reel | 10" reel | 13" reel | 13" reel |
|------|--|---------|---------|---------|---------|---------|---------|----------|----------|----------|
| | | V | Z | M | T | A | D | Q | H | G |
| 2512 | 12mm width plastic tape | - | - | - | 4,000 | - | - | 8,000 | - | 16,000 |
| 2010 | 12mm width plastic tape | - | - | - | 4,000 | - | - | 8,000 | - | 16,000 |
| 1210 | 8mm width paper tape | - | - | - | 5,000 | - | - | 10,000 | - | 20,000 |
| 1206 | 8mm width paper tape | 1,000 | - | - | 5,000 | - | - | 10,000 | - | 20,000 |
| 0805 | 8mm width paper tape | 1,000 | - | - | 5,000 | - | - | 10,000 | - | 20,000 |
| 0603 | 8mm width paper tape | 1,000 | - | - | 5,000 | - | - | 10,000 | - | 20,000 |
| 0402 | 8mm width paper tape | 1,000 | 3,000 | 5,000 | 10,000 | 15,000 | 20,000 | - | 50,000 | 70,000 |

TEST AND REQUIREMENTS

| TEST | PROCEDURE | REQUIREMENT |
|--|---|--|
| | | Resistor |
| Electrical Characteristics IEC 60115-1 4.8 | - DC resistance values measurement - Temperature Coefficient of Resistance (T.C.R) Natural resistance change per change in degree centigrade. $\frac{R_2 - R_1}{R_1(t_2 - t_1)} \times 10^6 \text{ (ppm/ } ^\circ\text{C)}$ $t_1 : 20^\circ\text{C}+5^\circ\text{C}-1^\circ\text{C}$ $R_1 : \text{Resistance at reference temperature (20}^\circ\text{C}+5^\circ\text{C}-1^\circ\text{C)}$ $R_2 : \text{Resistance at test temperature (-55}^\circ\text{C or +125}^\circ\text{C)}$ | Within the specified tolerance |
| Short time overload (S.T.O.L) IEC60115-1 4.13 | Permanent resistance change after a 5second application of a voltage 2.5 times RCWV or the maximum overload voltage specified in the above list, whichever is less. | $\Delta R/R \text{ max. } \pm(0.1\%+0.05\Omega)$ |
| Resistance to soldering heat(R.S.H) MIL-STD-202 Method 210 | Un-mounted chips completely immersed for 10 ± 1 second in a SAC solder bath at $260^\circ\text{C} \pm 5^\circ\text{C}$ | no visible damage $\Delta R/R \text{ max. } \pm(0.25\%+0.05\Omega)$ |
| Solderability IEC 60068-2-58 | Un-mounted chips completely immersed for 2 ± 0.5 second in a SAC solder bath at $235^\circ\text{C} \pm 5^\circ\text{C}$ | good tinning (>95% covered) no visible damage |
| Temperature cycling MIL-STD-202 Method 107 | Test – 55 to 125°C / dwell time 30min/ Max transfer time 20sec 1000 cycles | no visible damage $\Delta R/R \text{ max. } \pm(0.3\%+0.05\Omega)$ |
| Biased Humidity MIL-STD-202 Method 103 | Test 1000 hours/ at $85^\circ\text{C}/85\% \text{ RH.}/ 10\%$ of operation power. Measurement at 24 ± 4 hours after test conclusion | $\Delta R/R \text{ max. } \pm(0.5\%+0.05\Omega)$ |
| Operational Life MIL-STD-202 -108 | 1,000 hours at $125 \pm 2^\circ\text{C}$, loaded with rated power continuously | $\Delta R/R \text{ max. } \pm(0.5\%+0.05\Omega)$ |
| High Temperature Exposure MIL-STD-202 -108 | 1,000 hours at 155°C , un-powered | $\Delta R/R \text{ max. } \pm(0.3\%+0.05\Omega)$ |
| Mechanical Shock MIL-STD-202 Method 213 | 1/2 Sine Pulse / 100g Peak / Velocity 12.3ft/sec | $\Delta R/R \text{ max. } \pm(0.25\%+0.05\Omega)$ |
| Vibration MIL-STD-202 Method 204 | 5 g's for 20 min , 12 cycles each of 3 orientations | $\Delta R/R \text{ max. } \pm(0.1\%+0.05\Omega)$ |
| Terminal strength AEC-Q200-006 | 1 kg for 60 s | No broken |
| Board flex AEC-Q200-005 | Bending 2mm for 60 sec | $\Delta R/R \text{ max. } \pm(0.1\%+0.05\Omega)$ |

PACKAGING


Tape specifications (unit :mm)



| Series No. | Tape | A | B | W | F | E |
|------------|---------|-----------|-----------|------------|-----------|-----------|
| WF25 | Plastic | 6.90±0.20 | 3.60±0.20 | 12.00±0.30 | 5.50±0.10 | 1.75±0.10 |
| WF20 | Plastic | 5.50±0.20 | 2.80±0.20 | 12.00±0.30 | 5.50±0.10 | 1.75±0.10 |
| WF10 | Paper | 3.60±0.20 | 3.00±0.20 | 8.00±0.30 | 3.50±0.20 | 1.75±0.10 |
| WF12 | Paper | 3.60±0.20 | 2.00±0.20 | 8.00±0.30 | 3.50±0.20 | 1.75±0.10 |
| WF08 | Paper | 2.40±0.20 | 1.65±0.20 | 8.00±0.30 | 3.50±0.20 | 1.75±0.10 |
| WF06 | Paper | 1.90±0.20 | 1.10±0.20 | 8.00±0.30 | 3.50±0.20 | 1.75±0.10 |
| WF04 | Paper | 1.20±0.10 | 0.7±0.10 | 8.00±0.30 | 3.50±0.05 | 1.75±0.10 |

| Series No. | P1 | P0 | P2 | ΦD | T |
|------------|-----------|-----------|-----------|---------------------------------------|-----------|
| WF25 | 4.00±0.10 | 4.00±0.10 | 2.00±0.10 | Φ1.50 ^{+0.1} _{-0.0} | Max 1.2 |
| WF20 | 4.00±0.10 | 4.00±0.10 | 2.00±0.10 | Φ1.50 ^{+0.1} _{-0.0} | Max 1.2 |
| WF10 | 4.00±0.10 | 4.00±0.10 | 2.00±0.10 | Φ1.50 ^{+0.1} _{-0.0} | Max. 1.0 |
| WF12 | 4.00±0.10 | 4.00±0.10 | 2.00±0.10 | Φ1.50 ^{+0.1} _{-0.0} | Max. 1.0 |
| WF08 | 4.00±0.10 | 4.00±0.10 | 2.00±0.10 | Φ1.50 ^{+0.1} _{-0.0} | Max. 1.0 |
| WF06 | 4.00±0.10 | 4.00±0.10 | 2.00±0.10 | Φ1.50 ^{+0.1} _{-0.0} | 0.65±0.05 |
| WF04 | 2.00±0.10 | 4.00±0.10 | 2.00±0.10 | Φ1.50 ^{+0.1} _{-0.0} | 0.40±0.05 |

Reel dimensions



WF25 , WF20

| Symbol | A | B | C | D |
|----------|----------------------|----------------------|----------------|----------------|
| 7" reel | $\Phi 178.0 \pm 2.0$ | $\Phi 60.0 \pm 1.0$ | 13.0 ± 0.2 | 14.0 ± 0.5 |
| 10" reel | $\Phi 254.0 \pm 2.0$ | $\Phi 100.0 \pm 1.0$ | 13.0 ± 0.2 | 14.0 ± 0.5 |
| 13" reel | $\Phi 330.0 \pm 2.0$ | $\Phi 100.0 \pm 1.0$ | 13.0 ± 0.2 | 14.0 ± 0.5 |

WF12 , WF10 , WF08 , WF06 , WF04

| Symbol | A | B | C | D |
|----------|----------------------|----------------------|----------------|---------------|
| 7" reel | $\Phi 178.0 \pm 2.0$ | $\Phi 60.0 \pm 1.0$ | 13.0 ± 0.2 | 9.0 ± 0.5 |
| 10" reel | $\Phi 254.0 \pm 2.0$ | $\Phi 100.0 \pm 1.0$ | 13.0 ± 0.2 | 9.0 ± 0.5 |
| 13" reel | $\Phi 330.0 \pm 2.0$ | $\Phi 100.0 \pm 1.0$ | 13.0 ± 0.2 | 9.0 ± 0.5 |

(unit : mm)

单击下面可查看定价，库存，交付和生命周期等信息

[>>Walsin Technology\(华新科技\)](#)