

I-T Characteristics / 時間-電流特性

| Ampere Rating<br>額定電流 | % of Ampere Rating<br>額定電流% | Opening Time<br>熔斷時間 |
|-----------------------|-----------------------------|----------------------|
| 15A~30A               | 200%                        | 5 min Max. / 最長5分鐘   |
|                       | 300%                        | 10s Max. / 最長10秒     |




Product Features / 產品特性


|  |   |
|--|---|
| <b>Operating Temperature<br/>操作溫度</b>                | <p>Operating temperature / 操作溫度範圍: -55°C~125°C</p> <p>When choosing the fuses specification, if the operating environmental temperature beyond the scope from 20~30°C, you should consider the environmental temperature's affection to fuses.</p> <p>若貴司操作環境溫度超出25±5°C範圍，在選用保險絲規格時，需考慮操作環境溫度對保險絲的影響。</p> |
| <b>Storage Conditions<br/>儲存條件</b>                   | <p>Under airtight in temperature +10°C~60°C、relative humidity ≤75% can store 3 years.</p> <p>在溫度+10°C~60°C、相對濕度≤75%的密閉條件下可存放3年。</p> <p>Without dew in temperature+10°C~60°C、relative humidity be 95% maximum value for 30 days.</p> <p>在溫度+10°C~60°C、相對濕度為95%的非露天下最多可存放30天。</p>                           |
| <b>Installation Way &amp; Parameters<br/>安裝方式及條件</b> | <p>Wave soldering parameters / 波峰焊</p> <p>Solder pot temperature / 錫爐溫度: 260±3°C Max</p> <p>Solder dwell time / 焊接時間: 10s Max</p>   |
|  | <p>Hand welding parameters / 手工焊</p> <p>Solder iron temperature / 烙鐵溫度: 350±5°C</p> <p>Heating time / 焊接時間: 5s Max</p>  |

Dimensions / 尺寸圖 (Unit / 單位:mm)


WM40-XXX




WM40-XXX-P



WM40-XXX-P-L



WM40-XXX-P-SXL



Electrical Characteristics / 電氣特性

| Type<br>品名 | Ordering P / N<br>料號 |                            | Rated Current<br>額定電流 | Breaking Capacity<br>分斷能力        | Safety Approvals<br>安全認證 |
|------------|----------------------|----------------------------|-----------------------|----------------------------------|--------------------------|
| WM40       | WM40-XXX             | WM40-XXX-P (-P-L / -P-SXL) |                       |                                  |                          |
|            | WM40-15              | WM40-15-P (-P-L / -P-SXL)  | 15A                   | 660VAC / 1000A<br>660VDC / 1000A | ●                        |
|            | WM40-16              | WM40-16-P (-P-L / -P-SXL)  | 16A                   |                                  | ●                        |
|            | WM40-20              | WM40-20-P (-P-L / -P-SXL)  | 20A                   |                                  | ●                        |
|            | WM40-25              | WM40-25-P (-P-L / -P-SXL)  | 25A                   |                                  | ●                        |
|            | WM40-30              | WM40-30-P (-P-L / -P-SXL)  | 30A                   |                                  | ●                        |

单击下面可查看定价，库存，交付和生命周期等信息

[>>Walter\(华德\)](#)