Document: W04010017, Rev: A

Gas Discharge Tube

GDTA2RD8-3300

WAY ON

Features

- 2-electrode arrester
- Very small size
- Extremely fast response time
- Stable performance over life
- Extremely low capacitance (<1.5pF)
- High insulation resistance



Application

- Modem
- Splitter
- Base stations

Electrical specifications

Part number	DC Spark-over Voltage	Maximum Impulse Spark-over Voltage	Service Life ³⁾	Insulation resistance	Capacitance
	100V/s	1kv/µs	8/20µs 10times	@ 100V _{DC}	@ 1 MHz
	(V)	(V)	(KA)	(GΩ)	(pF)
GDTA2RD8-3300	3300±20%	4800	5	> 1	< 1.5

1) At delivery AQL 0.65 level II, DIN ISO 2859.

2) In ionized mode.


3) Tests according to ITU-T Rec. K. 12 , IEC61643-311 and UL 497B.

Thermal Resistances

Parameter	Value	Unit
Storage&Operating temperature range	-40 to +85	°C

Gas Discharge Tube


Dimensional drawing



Cautions and warnings

- Gas Discharge Tubes must not be operated directly in power supply networks.
- Gas Discharge Tubes may become hot in case of longer periods of current stress (danger of burning).
- Gas Discharge Tubes may be used only within their specified values. In case of overload, the head contacts may fail
 or the component may be destroyed.
- Damaged Gas Discharge Tubes must not be re-used.

Part Numbering System



Package Information

Quantity:100PCS(Plastic box)

Contact Information

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201207 Tel: 86-21-68969993 Fax: 86-21-50757680 Email: market@way-on.com WAYON website: http://www.way-on.com

For additional information, please contact your local Sales Representative.

WRYAN ® are registered trademarks of Wayon Corporation.

Specifications are subject to change without notice. The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time. Users should verify actual device performance in their specific applications. 单击下面可查看定价,库存,交付和生命周期等信息

>>WAY-ON(维安)