



80V N-Channel Enhancement Mode Power MOSFET

Description

WMB060N08LG2 uses Wayon's 2nd generation power trench MOSFET technology that has been especially tailored to minimize the on-state resistance and yet maintain superior switching performance. This device is well suited for high efficiency fast switching applications.

Features

- $V_{DS} = 80V$, $I_D = 100A$ (Silicon Limited)
 $R_{DS(on)} < 6.0m\Omega @ V_{GS} = 10V$
 $R_{DS(on)} < 8.0m\Omega @ V_{GS} = 4.5V$
- Green Device Available
- 100% EAS Guaranteed
- Low $R_{DS(ON)}$
- High Speed Power Switching, Logic Level



Applications

- Hard Switching and High Speed Circuit
- DC/DC Conversion
- Power Tools
- UPS
- SSR

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-Source voltage	V_{DS}	80	V
Gate-Source voltage	V_{GS}	± 20	V
Continuous Drain Current ¹ (Silicon Limited)	I_D	$T_C=25^\circ C$	100
		$T_C=100^\circ C$	63
Continuous Drain Current ¹ (Package Limited)	I_D	60	A
Pulsed Drain Current ²	I_{DM}	350	A
Single Pulse Avalanche Energy ³	EAS	211	mJ
Avalanche Current	I_{AS}	65	A
Total Power Dissipation ⁴	P_D	105	W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	$^\circ C$

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance from Junction-to-Ambient ¹	$R_{\theta JA}$	49.5	$^\circ C/W$
Thermal Resistance from Junction-to-Case ¹	$R_{\theta JC}$	1.2	$^\circ C/W$

Electrical Characteristics $T_c = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	
Static Characteristics							
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	80	-	-	V	
Gate-body Leakage Current	I_{GSS}	$V_{DS} = 0V, V_{GS} = \pm 20V$	-	-	± 100	nA	
Zero Gate Voltage Drain Current	$T_J=25^\circ\text{C}$	I_{DSS}	$V_{DS} = 80V, V_{GS} = 0V$	-	-	1	μA
	$T_J=100^\circ\text{C}$			-	-	100	
Gate-Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250\mu A$	1.0	1.7	2.4	V	
Drain-Source On-Resistance ²	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 20A$	-	4.3	6.0	m Ω	
		$V_{GS} = 4.5V, I_D = 20A$	-	5.9	8.0		
Forward Transconductance	g_{fs}	$V_{DS} = 5V, I_D = 20A$	-	64	-	S	
Dynamic Characteristics							
Input Capacitance	C_{iss}	$V_{DS} = 40V, V_{GS} = 0V, f = 1\text{MHz}$	-	3100	-	pF	
Output Capacitance	C_{oss}		-	368	-		
Reverse Transfer Capacitance	C_{rss}		-	17	-		
Switching Characteristics							
Gate Resistance	R_g	$V_{DS}=0V, V_{GS}=0V, f=1\text{MHz}$	-	1.4	-	Ω	
Total Gate Charge	Q_g	$V_{GS} = 4.5V, V_{DD} = 40V, I_D = 20A$	-	21.3	-	nC	
Total Gate Charge	Q_g	$V_{GS} = 10V, V_{DD} = 40V, I_D = 20A$	-	45	-		
Gate-Source Charge	Q_{gs}		-	8.8	-		
Gate-Drain Charge	Q_{gd}		-	8	-		
Turn-On Delay Time	$t_{d(on)}$	$V_{GS} = 10V, V_{DD} = 40V, R_G = 10\Omega, I_D = 20A$	-	10.5	-	nS	
Rise Time	t_r		-	7	-		
Turn-Off Delay Time	$t_{d(off)}$		-	37	-		
Fall Time	t_f		-	8.8	-		
Drain-Source Body Diode Characteristics							
Diode Forward Voltage ²	V_{SD}	$I_S = 20A, V_{GS} = 0V$	-	-	1.2	V	
Reverse Recovery Time	t_{rr}	$V_R = 40V, I_F = 20A, di_F/dt = 400A/\mu s$	-	49	-	ns	
Reverse Recovery Charge	Q_{rr}		-	188	-	nC	

Notes:

- The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.
- The data tested by pulsed , pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
- The EAS data shows Max. rating . The test condition is $V_{DD}=25V, V_{GS}=10V, L=0.1\text{mH}, I_{AS}=65A$
- The power dissipation is limited by 150°C junction temperature




Figure 1. Output Characteristics




Figure 2. $R_{DS(on)}$ vs. V_{GS}




Figure3. Forward Characteristics of Reverse




Figure4. Gate Charge Characteristics




Figure 5. $R_{DS(on)}$ Vs I_D




Figure 6. Normalized $R_{DS(on)}$ vs. T_J




Figure 7. Capacitance Characteristics




Figure 8. Safe Operating Area




Figure 9. Normalized Maximum Transient Thermal Impedance




Figure 9. Switching Time Waveform







Figure 10. Unclamped Inductive Switching Waveform

Mechanical Dimensions for PDFN5060-8L

COMMON DIMENSIONS




SYMBOL	MM	
	MIN	MAX
A	0.90	1.17
A3	0.20	0.35
D	4.80	5.40
E	5.90	6.15
D1	3.61	4.31
E1	3.30	3.78
E2	5.65	5.85
k	1.10	-
b	0.30	0.51
e	1.27BSC	
L	0.38	0.71
L1	0.05	0.36
H	0.38	0.61
θ	0°	12°

Ordering Information

Part	Package	Marking	Packing method
WMB060N08LG2	PDFN5060-8L	B060N08L	Tape and Reel

Marking Information



B060N08L = Device code

WWXX XXX= Date code

Contact Information

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201207

Tel: 86-21-50310888 Fax: 86-21-50757680 Email: market@way-on.com

WAYON website: <http://www.way-on.com>

For additional information, please contact your local Sales Representative.

 © is registered trademarks of Wayon Corporation.

Disclaimer

WAYON reserves the right to make changes without further notice to any Products herein to improve reliability, function, or design. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. WAYON does not assume any liability for infringement of patents, copyrights, or other intellectual property rights of third parties by or arising from the use of Products or technical information described in this document.

单击下面可查看定价，库存，交付和生命周期等信息

[>>WAY-ON\(维安\)](#)