



SPECIFICATION

Contact Rating : 50mA, 12V DC
 Contact Resistance : 100mΩ max
 Insulation Resistance : 100mΩ min. 500V DC
 Dielectric Strength : 250V AC/1minute
 Travel : 0.20mm
 Operating Temp : -30°C ~ +85°C
 Storage Temp : -30°C ~ +80°C

CIRCUIT DIAGRAM



P.C.B MOUNTING HOLES



PACKING REEL TYPE 4,000/1REEL(EA)

PAPT NO	TS-1145A-X-X
Operating Force	A: 100gf B: 160gf C: 260gf
Height	H: 2.5
Keystone	A: PA46 B: Silica gel

SWITCH CONNECTOR

⑤	Terminal	—	4	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	Lcp		—
②	Cover	—	1	Brass	Plating Nickel	—
①	Keystone	—	1	Pa46		—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH		
DWN		DATE		VIEW:	PART NO.:		
CHKD		DATE		UNIT: mm	DWG NO.:		
APPD		DATE		SIZE: A4	TS-1145A-X-X		
UNSPECIFIED TOLERANCES				XKB INDUSTRIAL PRECISION CO., LIMITED	WEIGHT 1.0g	SHEET 1/1	REVISION A0

units:	mm
tolerance:	
X.X	±0.2mm
X.XX	±0.1mm
X.XXX	±0.05mm

ΔX	
ΔX	
ΔX	
MARK	DESCRIPTION

REVISIONS	DATE	REVISED	APPROVED
www.xk-dg.cn	www.helloxkb.com	www.helloxkb.cn	

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)