



Material:

- * Insulation:
Glass filled Polyamide UL 94V-0
Color Black
 - * Contact: Copper alloy, t=0.2mm
 - * Fixed Tab: Brass, t=0.2mm
 - * Plating code: Gold flash over Nickel
- DIM.A = 0.50 * No. of Spaces
 DIM.B = DIM.A + 3.0
 DIM.C = DIM.A + 0.5
 * Available in 10 through 80 circuits

X1015 W M-XX X-X

① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② Category: W-WAFER
- ③ Welding Board Angle: M-Male
- ④ No. of Circuits
- ⑤ Special No: S-With Positioning Column
- ⑥ Height:
 A: Dim.D = 2.0mm (Circuits: 10~80pin)
 C: DIM.D = 3.0mm (Circuits: 10~60pin)
 D: DIM.D = 3.5mm (Circuits: 10~60pin)

					ANGLAR	±5°	DSND		DATE	SCALE: N/A	MODEL TYPE: BTB CONNECTOR		
ΔX					L ≤ 4	±0.2	DWN		DATE	VIEW:	PART NO.:		
ΔX					4 < L ≤ 16	±0.3	CHKD		DATE	UNIT: mm	DWG NO.:		
ΔX					16 < L ≤ 63	±0.4	APPD		DATE	SIZE: A4	X1015WM-XXX-X		
MARK	DESCRIPTION	DATE	REVISED	APPROVED	L > 63	±0.5					WEIGHT	SHEET	REVISION
					UNSPECIFIED TOLERANCES		KKB INDUSTRIAL PRECISION CO., LIMITED				1.0g	1/1	A0
					REVISIONS								
					www.xk-dg.cn www.helloxkb.com www.helloxkb.cn								

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)