



CIRCUIT DIAGRAM

SPECIFICATION

Contact Rating: 50mA, 12V DC
 Contact Resistance: 100mΩ max
 Insulation Resistance: 100mΩ min. 500V DC
 Dielectric Strength: 250V AC/1minute
 Travel: 0.20mm
 Operating Temp: -30°C ~ +85°C
 Storage Temp: -30°C ~ +80°C

PAPT NO	TS-3737-X
Operating Force	B:160gf C:250gf
Height	H:0.4

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	4	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	LCP		—
②	Cover	—	1	Kapton filmPI	Plating Nickel	—
①	Keystake	—	1			—

广东星坤科技股份有限公司

生 Δ X 日期

效 Δ X 日期

MARK

文件工程章

REVISIONS	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE:
DESCRIPTION		DWN	DATE <td>VIEW: </td> <td>TACT SWITCH</td>	VIEW:	TACT SWITCH
DATE		CHKD	DATE <td>UNIT: mm/in</td> <td>PART NO.:</td>	UNIT: mm/in	PART NO.:
REVISED		APPD	DATE <td>SIZE: A4</td> <td>DWG NO.: TS-3737-X</td>	SIZE: A4	DWG NO.: TS-3737-X
APPROVED		XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT
					1.0g
					SHEET
					1/1
					REVISION
					A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)