



RECOMMENDED P.C.B. LAYOUT  
TOP VIEW (TOLRANCE: ±0.05)

**Material**  
Housing Material: LCP, UL94V-0, black  
Contact Terminal: Copper Alloy  
Metallic Shell: Sus  
**Electrical**  
Voltage Rating: 30 V AC  
Current Rating: Signal (Pins 2,3,4): 1.0A, Power (Pins 1,5): 1.8A  
Contact Resistance: 30mΩ Max  
Insulation resistance: 1000MΩ Min  
Dielectric withstanding voltage: 250V AC/Minute  
**Mechanical**  
Durability: 10,000 cycles  
Mating Force: 35N (3.57Kgf) Max  
Unmating Force: 8N (0.82Kgf) Min.

U254-05XX-4BH83-XXS

1:Au 1U"  
6:Au 30U"  
T:TIN  
N:NICKEL  
S:Sus  
1:With 2:Without  
S:Scrolls F:Flat

					ANGLAR	±5°	DSND		DATE	SCALE: N/A	MODEL TYPE:	MICRO USB																						
					L ≤ 4	±0.2	DWN		DATE	VIEW:	PART NO.:	U254-05XX-4BH83																						
					4 < L ≤ 16	±0.3	CHKD		DATE	UNIT: mm	DWG NO.:	U254-05XX-4BH83-XXS																						
					16 < L ≤ 63	±0.4	APPD		DATE	SIZE: A4																								
					L > 63	±0.5	KXB INDUSTRIAL PRECISION CO., LIMITED					WEIGHT	SHEET	REVISION																				
					UNSPECIFIED TOLERANCES							1.0g	1/1	A0																				
<table border="1"> <thead> <tr> <th>MARK</th> <th>DESCRIPTION</th> <th>DATE</th> <th>REVISED</th> <th>APPROVED</th> </tr> </thead> <tbody> <tr> <td>△X</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>△X</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>△X</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>												MARK	DESCRIPTION	DATE	REVISED	APPROVED	△X					△X					△X					REVISIONS www.xk-dg.cn www.1k0k.com www.1k0k.cn		
MARK	DESCRIPTION	DATE	REVISED	APPROVED																														
△X																																		
△X																																		
△X																																		

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)