



Specifications:

Voltage rating: 250V AC / DC

Current rating: 5A AC / DC

Withstanding voltage: 1000V AC/minute

Temperature range: -25°C~+85°C

Insulation resistance: ≥1000MΩ

Contact resistance: ≤10mΩ

After environmental testing: ≤20mΩ

C3030 H M-2*XX XX-N2 XX

① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② Category: H-HSG
- ③ Welding Board Angle: M-Male HSG
- ④ Row No.-Pin No.: 2*XX-2*01P~2*12P
- ⑤ Plug the Pin & special No.
- ⑥ Material: N2-PA66 94V-2
- ⑦ Color: Blank-Natural Color

| Poles | Dimensions(mm) | | Poles | Dimensions(mm) | |
|-------|----------------|-------|-------|----------------|-------|
| | A | B | | A | B |
| 2*01 | | | 2*07 | 18.00 | 21.85 |
| 2*02 | 3.00 | | 2*08 | 21.00 | 24.85 |
| 2*03 | 6.00 | 9.85 | 2*09 | 24.00 | 27.85 |
| 2*04 | 9.00 | 12.85 | 2*10 | 27.00 | 30.85 |
| 2*05 | 12.00 | 15.85 | 2*11 | 30.00 | 33.85 |
| 2*06 | 15.00 | 18.85 | 2*12 | 33.00 | 36.85 |

| | | | |
|-----------------|----------------|-----------------------|-----------------------|
| C3030HM-2*XX-N2 | Nylon 66 94V-2 | C3030TF | C3030W |
| PART NO | Material | Suitable XKB Terminal | Suitable XKB Terminal |

广东星坤科技股份有限公司

| | |
|------------------------|-----------|
| 生效 | 日期 |
| 文件工程章 | REVISIONS |
| DESCRIPTION | DATE |
| REVISOR | REVISED |
| APPROVED | DATE |
| UNSPECIFIED TOLERANCES | |

| | |
|------------|------------------------|
| units: | mm |
| tolerance: | |
| X.X | ±0.2mm |
| X.XX | ±0.1mm |
| X.XXX | ±0.05mm |
| | UNSPECIFIED TOLERANCES |

| | | | |
|---------------------------------------|-------|-------------|--------------------------------|
| DSND | DATE | SCALE: N/A | MODEL TYPE: |
| DWN | DATE | VIEW: | Wire to board connector |
| CHKD | DATE | UNIT: mm/in | PART NO.: |
| APPD | DATE | SIZE: A4 | 3.00 mm Crimp Style Connectors |
| XKB INDUSTRIAL PRECISION CO., LIMITED | | | DWG NO.: |
| | | | C3030HM-2*XX-N2 |
| WEIGHT | SHEET | REVISION | |
| 1.0g | 1/1 | A0 | |

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)