



- NOTES:
- MATERIAL:
    - MOLDING: LCP UL94 V-0
    - CONTACT: COPPER ALLOY.
  - Finished: contact area: plating Au 0.8u", solder tail: plating Au 0.8u", all plating Ni 40u" SHELL: SUS201-1/2H, T=0.30±0.03mm 50u" NICKEL PLATING OVER ALL.
  - MECHANICAL:
    - INSERTION: 5~20N.
    - EXTRACTION: 8~20N AFTER TEST.
    - DURABILITY: 8000 CYCLES
  - ELECTRICAL:
    - CURRENT: 5A FOR VBUS; 1.25A FOR GND PIN. 0.25A FOR OTHER.
    - VOLTAGE: 20 V MAX
    - WITHSTANDING VOLTAGE: 100V AC R.M.S.
    - CONTACT RESISTANCE: 40mΩ MAX.
    - INSULATION RESISTANCE: 100MΩ MIN.
  - ENVIRONMENTAL
    - TEMPERATURE RANGE -25°C ~ +85°C

U262-06XN-4BVC11

1: 0.8u"  
2: 5u"  
3: 10u"

					DSND		DATE		SCALE: N/A	MODEL TYPE:	3.1 TYPE C		
ΔX					ANGLAR		DATE		VIEW:	PART NO.:			
ΔX					L ≤ 4		DATE		UNIT: mm	DWG NO.:	U262-06XN-4BVC11		
ΔX					4 < L ≤ 16		DATE		SIZE: A4	WEIGHT	SHEET	REVISION	
MARK	DESCRIPTION	DATE	REVISED	APPROVED	L > 63		DATE			1.0g	1/1	A0	
					UNSPECIFIED TOLERANCES	XKB INDUSTRIAL PRECISION CO., LIMITED							

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)