



SCHEMATIC	
Model	DC-005
Center Pin	1.65
	2.0
	2.5

SPECIFICATIONS:

规格:

1. ELECTRICAL CHARACTERISTICS:

电气特性:

1-1. RATING:

等级:

1-2. CONTACT RESISTANCE: 30M Ω MAX. (INITIAL)

接触电阻: 最大30M Ω (初始)

1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE

介质耐受电压: 500V AC FOR ONE MINUTE

1-4. INSULATION RESISTANCE: 100M Ω MIN. MEASURED BY 500V DC

绝缘电阻: 500V 直流电测得的最小值为 100M Ω

2. MECHANICAL CHARACTERISTICS:

机械特性:

2-1. INSERTION FORCE: 0.3~3.0 KGf

插入力: 0.3~3.0 KGf

2-2. WITHDRAWAL FORCE: 0.3~3.0 KGf

拔出力: 0.3~3.0 KGf

3. UFE TEST: 5,000 CYCLES MIN.

UFE 试验: 至少 5000 次循环。

4. FOR REFLOW SOLDERING LEAD-FREE PROCESS.

用于回流焊无铅工艺。

5. REPRESENT CRITICAL DIMENSIONS.

表示关键尺寸

	MATERIAL	PLATING
center pin	Brass	tin
terminal 1	Brass	tin
terminal 2	Sus	tin
terminal 3	Brass	tin
plastic	Pbt	

广东星坤科技股份有限公司

生效	日期
文件工程章	

MARK	DESCRIPTION	REVISIONS	DATE	REVISED	APPROVED

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO.: DC-005-2.5A-2.5
APPD	DATE	SIZE: A4	WEIGHT / SHEET / REVISION
			1.0g / 1/1 / A0

VXP INDUSTRIAL PRECISION CO., LIMITED

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)