

PCB LAYOUT TOP VIEW
TOLERANCES: ±0.05

SPECIFICATIONS:

规格:

1. ELECTRICAL CHARACTERISTICS:

电气特性:

1-1. RATING:

等级:

1-2. CONTACT RESISTANCE: 30MQ MAX. (INITIAL)

接触电阻: 最大30MQ (初始)

1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE

介质耐受电压: 500V AC FOR ONE MINUTE

1-4. INSULATION RESISTANCE: 100MQ MIN. MEASURED BY 500V DC

绝缘电阻: 500V直流电测得的最小值为100MQ

2. MECHANICAL CHARACTERISTICS:

机械特性:

2-1. INSERTION FORCE: 0.3~3.0 KGF

插入力: 0.3~3.0 KGF

2-2. WITHDRAWAL FORCE: 0.3~3.0 KGF

拔出力: 0.3~3.0 KGF

3. LIFE TEST: 5,000 CYCLES MIN.





寿命试验: 至少5000次循环。

4. FOR REFLOW SOLDERING LEAD-FREE PROCESS.

用于回流焊无铅工艺。

5. REPRESENT CRITICAL DIMENSIONS.

表示关键尺寸



SCHEMATIC	
Model	DC-005
Center Pin	2.0
	2.5
	3.0

	MATERIAL	PLATING
center pin	Brass	silver
terminal 1	Brass	silver
terminal 2	Phosphor Bronze	silver
terminal 3	Brass	silver
plastic	Pbt	

广东星坤科技股份有限公司
星坤科技

生	日期
效	
Δ	
Δ	
Δ	
MARK	DESCRIPTION
文件	工程章
REVISIONS	DATE
REVISED	APPROVED
UNSPECIFIED TOLERANCES	

DSND	DATE	SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	DC-005-5A-2.0
WEIGHT	SHEET	REVISION	
1.0g	1/1	A0	

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)