




PCB LAYOUT TOP VIEW



SPECIFICATIONS:

规格:

1. ELECTRICAL CHARACTERISTICS:

电气特性:

1-1.RATING:

评级:

1-2. CONTACT RESISTANCE:30mΩ MAX.(INITIAL)

接触电阻: 最大30mΩ (初始)

1-3. DIELECTRIC WITHSTANDING VOLTAGE:

500V AC FOR ONE MINUTE

介质耐受电压:

500V AC FOR ONE MINUTE

1-4.INSULATION RESISTANCE:

100MΩ MIN. MEASURED BY 500V DC

绝缘电阻:

500V 直流电测得的最小值为100MΩ

2. MECHANICAL CHARACTERISTICS:

机械特性:

2-1. INSERTION FORCE:0.3~3.0 KGF

插入力: 0.3~3.0 KGF

2-2. WITHDRAWAL FORCE:0.3~3.0 KGF

拔出力: 0.3~3.0 KGF

3. LIFE TEST:5,000 CYCLES MIN.


寿命试验: 至少5000次循环.

4.FOR REFLOW SOLDERING LEAD-FREE PROCESS.

用于回流焊无铅工艺.

5.REPRESENT CRITICAL DIMENSIONS.

表示关键尺寸。



广东星坤科技股份有限公司

SCHEMATIC	
Model	DC-005E
Center Pin	Ø2.0 mm
	Ø2.5 mm

	MATERIAL	PLATING
center pin	Brass	tin
terminal 1	Brass	tin
terminal 2	Sus	tin
terminal 3	Brass	tin
plastic	Pbt	

生	日期									DSND		DATE		SCALE: N/A	MODEL TYPE: DC POWER JACK		
效										DWN		DATE		VIEW:	PART NO.:		
Δ*										CHKD		DATE		UNIT: mm/in	DWG NO.:		
MARK	文件工程章	DESCRIPTION	REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES			APPD		DATE		SIZE: A4	DC-005E-2.5A-2.5		
															WEIGHT 1.0g	SHEET 1/1	REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)