


1. Rated load: 30V 2.5A  
 1. 额定负载: 30V 2.5A  
 2. Contact Resistance:  $\leq 0.03\Omega$ ;  
 2. 接触电阻:  $\leq 0.03\Omega$ ;  
 3. Insulation Resistance:  $\geq 100M\Omega$ ;  
 3. 绝缘电阻:  $\geq 100M\Omega$ ;  
 4. Voltage withstand: AC500V(50Hz)/min;  
 4. 耐压: AC500V (50Hz) /min;  
 5. Insertion force: 3~20N;  
 5. 插入力: 3~20N;  
 life: 5,000次.  
 6. 寿命: 5000次.


SCHEMATIC	
Model	DC-005F-2.5A
Center Pin	$\varnothing 2.0$ mm
	$\varnothing 2.5$ mm

	MATERIAL	PLATING
center pin	Brass	CuSn
terminal 1	Brass	Ag
terminal 2	Phosphor copper	Ag
terminal 3	Brass	Ag
plastic	Pbt	

广东星坤科技股份有限公司

生	日期
效	
文件工程章	

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

DSND		DATE		SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN		DATE		VIEW: 	PART NO.:
CHKD		DATE		UNIT: mm/in	DWG NO.:
APPD		DATE		SIZE: A4	DC-005F-2.5A-2.5
				WEIGHT	SHEET
				1.0g	1/1
				REVISION	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)