

PCB LAYOUT  
TOP VIEW

SPECIFICATIONS:

规格:

RATING: 12V DC @ 1A

额定值: 12V DC@1A

CONTACT RESISTANCE: 30m OHMS MAX

接触电阻: 最大30m欧姆

INSULATION RESISTANCE: 100M OHMS MIN: 500V DC

绝缘电阻: 100M OHMS MIN: 500V DC

VOLTAGE WITHSTAND: 500V AC R.M.S. FOR 1 MINUTE


耐压: 500V AC R.M.S. FOR 1 MINUTE

LIFE: 5,000 CYCLES

寿命: 5000个周期

OPERATING TEMP: -20° ~ +85°C

工作温度: -20°C ~ +85°C



	MATERIAL	PLATING
center pin	Brass	tin
terminal 1	Brass	tin
terminal 2	Phosphor Bronze	tin
terminal 3	Brass	tin
plastic	Pbt	

广东星坤科技股份有限公司

生效日期

文件工程章

DSND		DATE		SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm/in	DWG NO.:
APPD		DATE		SIZE: A4	DC-023
UNSPECIFIED TOLERANCES				WEIGHT	SHEET
				1.0g	1/1
				REVISION	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)