








P.C.B LAYOUT



SPECIFICATION

规范

- Rating : DC 20V 10A;
额定值 : DC 20V 10A;
- Contact resistance: 0.03Ω;
接触电阻: 0.03Ω;
- Insulation resistance: ≥100MΩ (DC250V)
绝缘电阻: ≥100MΩ (DC250V)
- Withstand voltage: 500V AC
耐压: 500V AC
- Insertion and extraction force: 5-40N
插拔力: 5-40N
- life test: 5,000 cycles.
寿命试验: 5,000次循环。

广东星坤科技股份有限公司

生	日期
效	
Δ	
Δ	
Δ	
MARK	文件工程章
DESCRIPTION	REVISIONS
DATE	REVISED
APPROVED	
UNSPECIFIED TOLERANCES	
VXP INDUSTRIAL PRECISION CO., LIMITED	
WEIGHT	SHEET
1.0g	1/1
REVISION	A0

DSND	DATE	SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN	DATE	VIEW: 3	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	DC-042C-Z-2.5-A

ANGULAR	±5°
X.X	±0.2mm
X.XX	±0.1mm
X.XXX	±0.05mm

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)