



**SPECIFICATION**

- 规格  
 1 Rating : DC 12V 3A;  
 1. 额定值: DC 12V 3A;  
 2 Contact resistance: <0.03Ω;  
 2 接触电阻: <0.03Ω;  
 3 Insulation resistance: 100MΩ (DC250V);  
 3 绝缘电阻: 100MΩ (DC250V) ;  
 4 Withstand voltage: 500VAC;  
 4 耐压: 500VAC;  
 5 Insertion and extraction force: 5-30N;  
 5 插拔力: 5-30N;  
 6 life test: 5 000 cycles.  
 6 寿命试验: 5 000次循环  
 7 PLUG 插入后上下左右4个方向无断现象

	MATERIAL	PLATING
center pin	Brass	ag
coat	Phosphor Bronze	ni
terminal 2	Phosphor Bronze	ag
plastic	Lcp	

广东星坤科技股份有限公司

生	日期
效	
Δ	
Δ	
Δ	
MARK	DESCRIPTION
文件	工程章

DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	DC-042F-3A-1.65
			WEIGHT SHEET REVISION
			1.0g 1/1 A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)