

SPECIFICATION

规格

1 Rating: DC 20V 7A;

额定值: DC 20V 7A;

2 Contact resistance: 0.03Ω;

接触电阻: 0.03Ω;

3 Insulation resistance: ≥100MΩ (DC250V);

绝缘电阻: ≥100MΩ (DC250V);

4 Withstand voltage: 500VAC

耐压: 500VAC

5 Insertion and extraction force 5-30N;

插拔力: 5-30N;

6 life test: 5000 cycles.




寿命试验: 5000次循环。

7 After plug is inserted, there is no instantaneous

break in the up, down, left and right directions

PLUG插入后上下左右4个方向无瞬断现象。

DC-C024E-7A-1.65



SECTION A-A

	MATERIAL	PLATING
center pin	Brass	tin
coat	Sus	
terminal 1	Phosphor Bronze	tin
terminal 2	Phosphor Bronze	tin
terminal 3	Phosphor Bronze	tin
plastic	Pa9t	

广东星坤科技股份有限公司

生	日期
效	
Δ	
Δ	
Δ	
MARK	DESCRIPTION
文件	工程章
REVISIONS	
DATE	REVISED
APPROVED	
UNSPECIFIED TOLERANCES	

ANGULAR	±5°
X.X	±0.2mm
X.XX	±0.1mm
X.XXX	±0.05mm

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	DC POWER JACK
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.:
			DC-C024E-7A-1.65
		WEIGHT	SHEET
		1.0g	1/1
		REVISION	A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)