



RECOMMENDED PLUG

SPECIFICATION

规格

- 1 Rating: DC 20V 5.5A;
- 额定值: 高压20V 5.5A;
- 2 Contact resistance: $\leq 0.03\Omega$;
- 接触电阻: $\leq 0.03\Omega$;
- 3 Insulation resistance: 2100MΩ(DC250V)
- 绝缘电阻: 2100MΩ(DC250V)

www.helioxib.com

SCHEMATIC	
Model	DC-C033D-5.5A
Center Pin	$\varnothing 2.0$ mm
	$\varnothing 2.5$ mm

	MATERIAL	PLATING
center pin	Brass	tin
coat	Sus	
terminal 2	Phosphor Bronze	tin
terminal 3	Brass	tin
terminal 4	Brass	tin
terminal 5	Brass	tin
plastic	Pa9t	

广东星河科技股份有限公司
 附页: E001AC
 注册: 2010年05月20日
 地址: 深圳市宝安区西乡街道
 510554
 寿命试验: 5,000次循环

生效	日期
文件工程章	DESIGN
MARK	DESCRIPTION
REVISIONS	DATE
REVISED	APPROVED

ANGULAR	$\pm 5^\circ$	DSND	DATE	SCALE: N/A	MODEL TYPE:
X.X	± 0.2 mm	DWN	DATE	VIEW:	DC POWER JACK
X.XX	± 0.1 mm	CHKD	DATE	UNIT: mm/in	PART NO.:
X.XXX	± 0.05 mm	APPD	DATE	SIZE: A4	DWG NO.:
UNSPECIFIED TOLERANCES					DC-C033D-5.5A-2.0
					WEIGHT
					1.0g
					SHEET
					1/1
					REVISION
					A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)