


SPECIFICATION
 规格
Rating: DC 20V 5.5A
额定值: 直流20V 5.5A
Contact resistance: ≤0.03Ω
接触电阻: ≤0.03Ω
Insulation resistance: ≥100MΩ
绝缘电阻: ≥100MΩ
Withstand voltage: AC500V(50Hz)/min
耐受电压: AC500V(50Hz) /min
Insertion and extraction: 3-20N
插入和提取: 3-20N
Use temperature range: -30-70°C
使用温度范围: -30-70°C
Life test: 5000 cycles
寿命试验: 5000次循环


SCHEMATIC	
Model	DC-C300-5.5A
Center Pin	Ø1.65 mm
	Ø2.0 mm
	Ø2.5 mm

MATERIAL	PLATING
center pin	Brass tin
coat	Brass
cover palte	Sus
terminal 1	Phosphor Bronze tin
terminal 2	Phosphor Bronze tin
terminal 3	Phosphor Bronze tin
plastic	Ppa

广东星坤科技股份有限公司

生	日期
效	
Δ	
Δ	
Δ	

文件工程章

DSND		DATE		SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN		DATE		VIEW: 	PART NO.:
CHKD		DATE		UNIT: mm/in	DWG NO.:
APPD		DATE		SIZE: A4	DC-C300-5.5A-2.0
UNSPECIFIED TOLERANCES				VCP INDUSTRIAL PRECISION CO., LIMITED	WEIGHT 1.0g
					SHEET 1/1
					REVISION A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)