



SPECIFICATION

规格
Rating: DC 20V 5.5A
额定值: 直流20V 5.5A
Contact resistance: ≤0.03Ω
接触电阻: ≤0.03Ω
Insulation resistance: ≥100MΩ
绝缘电阻: ≥100MΩ
Withstand voltage: AC500V(50Hz)/min
耐受电压: AC500V (50Hz) /min
Insertion and extraction: 3-20N
插入和提取: 3-20N
Use temperature range: -30-70°C
使用温度范围: -30-70°C
Life test: 5000 cycles
寿命试验: 5000次循环

SCHEMATIC	
Model	DC-C300-5.5A
Center Pin	Ø1.65 mm
	Ø2.0 mm
	Ø2.5 mm

MATERIAL	PLATING
center pin	Brass tin
coat	Brass
cover palte	Sus
terminal 1	Phosphor Bronze tin
terminal 2	Phosphor Bronze tin
terminal 3	Phosphor Bronze tin
plastic	Ppa

广东星坤科技股份有限公司

生	日期
效	
Δ	
Δ	
Δ	
MARK	DESCRIPTION
文件	工程章

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	DC POWER JACK
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.:
UNSPECIFIED TOLERANCES			DC-C300-5.5A-2.5
VCP INDUSTRIAL PRECISION CO., LIMITED			WEIGHT SHEET REVISION
			1.0g 1/1 A0

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)