


- Technical Parameters
- 1.Electrical Rating: 0.1A 125/250VAC
3A/12VDC;0.1A/48VDC
 - 2.Electrical lifetime:100 000
 - 3.Mechanical lifetime:100 000
 - 4.Contact Resistance: ≤100mΩ
 - 5.Operating force:1.0~3.5N
 - 6.Pretravel:0.3~1.0mm
 - 7.Withstand Voltage:Feet and Feet 750V/5S/5mA
Feet and Shell 1500/5S/5mA
 - 8.Insulation Resistance:≥100MΩ(Test Voltage 500VDC)
 - 9.Proof Tracking Index(PTI):175V
 - 10.Ambient temperature:125°

Circuit diagram



Waterproof grade:IP67

1	Rubber shell	PA66
2	seal ring	Silica gel
3	base	Brass+PA66
4	According to sincerity	POM
5	Contact moving plate	C5191+AgNi10
6	Strut	SUS301-H

广东星坤科技股份有限公司

生	日期	units: mm	DSND	DATE	SCALE: N/A	MODEL TYPE: Microswitch
ΔX	日期	tolerance: X.X ±0.2mm	DWN	DATE	VIEW:	PART NO.:
ΔX	日期	X.XX ±0.1mm	CHKD	DATE	UNIT: mm/in	DWG NO.: DF1-000CY-1
ΔX	日期	X.XXX ±0.05mm	APPD	DATE	SIZE: A4	WEIGHT SHEET REVISION
MARK	文件工程章	UNSPECIFIED TOLERANCES	XKB INDUSTRIAL PRECISION CO., LIMITED			1.0g 1/1 A0
REVISIONS		DATE REVISED APPROVED				
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn						

单击下面可查看定价，库存，交付和生命周期等信息

[>>XKB Connectivity\(中国星坤\)](#)